OKS 250

Version	Revision Date:	Date of last issue: 31.07.2026	Print Date:
6.0	03.11.2026	Date of first issue: 23.06.2016	03.11.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 250

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Lubricant

Recommended restrictions on use : Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH
Ganghoferstr. 47
82216 Maisach
Germany
Tel.: +49 8142 3051-500
info@oks-germany.com

E-mail address of person responsible for the SDS : mcm@oks-germany.com

National contact : Klüber Lubrication Deutschland GmbH & Co. KG
Geisenhausenerstraße 7
81379 München
Germany
Tel: +49 89 7876 0
customer.service.de@klueber.com

1.4 Emergency telephone number

Emergency telephone number : +49 8142 3051 517

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Short-term (acute) aquatic hazard, Category 1	H400: Very toxic to aquatic life.

Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

H315	Causes skin irritation.
H318	Causes serious eye damage.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

P264	Wash skin thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/ eye protection/ face protection.

Response:

P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P391	Collect spillage.

Hazardous components which must be listed on the label:

calcium dihydroxide

Additional Labelling

EUH208	Contains Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : solid lubricant
Synthetic hydrocarbon oil

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
calcium dihydroxide	1305-62-0 215-137-3 01-2119475151-45-XXXX	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system)		>= 10 - < 20
Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]	800-362-7 01-2119974117-33-XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT RE 2; H373 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	M-Factor: 10/1	>= 2,5 - < 10
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8 265-158-7 649-468-00-3 01-2119487077-29-xxxx	Asp. Tox. 1; H304	Note L	>= 1 - < 10
Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate	947-946-9 01-2120772600-59-XXXX	Skin Irrit. 2; H315 Skin Sens. 1B; H317 Aquatic Chronic 4; H413		>= 0,25 - < 1

Substances with a workplace exposure limit :				
titanium dioxide; [in powder form containing <1 % of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7 236-675-5 01-2119489379-17-XXXX	Not classified		>= 20 - < 30
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25-XXXX	Not classified	Note L	>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact : Take off all contaminated clothing immediately.
Wash off immediately with soap and plenty of water.
Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
Get medical attention immediately.

If swallowed : Move the victim to fresh air.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
Do not induce vomiting without medical advice.
Obtain medical attention.
Rinse mouth with water.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	:	Skin contact may provoke the following symptoms: Erythema
Risks	:	Causes skin irritation. Causes serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	:	Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	:	High volume water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products	:	Carbon oxides Nitrogen oxides (NOx) Oxides of phosphorus Metal oxides

5.3 Advice for firefighters

Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposition products may be a hazard to health.
Further information	:	Standard procedure for chemical fires. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Evacuate personnel to safe areas. Ensure adequate ventilation. Do not breathe vapours, aerosols. Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions	:	Do not allow contact with soil, surface or ground water.

If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Pick up and transfer to properly labelled containers.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not use in areas without adequate ventilation.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
Do not get in eyes or mouth or on skin.
Do not get on skin or clothing.
Do not ingest.
Do not repack.
These safety instructions also apply to empty packaging which may still contain product residues.
Keep container closed when not in use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep container closed when not in use. Keep in a dry, cool and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with the particular national regulations. Keep in properly labelled containers.

Storage class (TRGS 510) : 11, Combustible Solids

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

OKS 250

Version	Revision Date:	Date of last issue: 31.07.2026	Print Date:
6.0	03.11.2026	Date of first issue: 23.06.2016	03.11.2026

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
titanium dioxide; [in powder form containing <1 % of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	MAK (measured as the alveolate fraction)	0,3 mg/m3	DE DFG MAK (2024-07-01)
	Peak-limit: excursion factor (category): 8; II			
	Further information: Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
		AGW (Inhalable fraction)	10 mg/m3 (Titanium dioxide)	DE TRGS 900 (2014-04-02)
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate fraction)	1,25 mg/m3 (Titanium dioxide)	DE TRGS 900 (2014-04-02)
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		BM (Alveolar dust fraction)	0,5 mg/m3	DE TRGS 527 (2020-02-19)
calcium dihydroxide	1305-62-0	TWA (Respirable fraction)	1 mg/m3	2017/164/EU (2017-02-01)
	Further information: Indicative			
		STEL (Respirable fraction)	4 mg/m3	2017/164/EU (2017-02-01)
	Further information: Indicative			
		MAK (inhalable fraction)	1 mg/m3	DE DFG MAK (2023-07-01)
	Peak-limit: excursion factor (category): 2; I			
	Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
		AGW (Inhalable fraction)	1 mg/m3	DE TRGS 900 (2014-12-08)
	Peak-limit: excursion factor (category): 2;(I)			

	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	64742-54-7	AGW (Vapour and aerosols)	5 mg/m3	DE TRGS 900 (2018-06-07)
	Peak-limit: excursion factor (category): 4;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8	AGW (Vapour and aerosols)	5 mg/m3	DE TRGS 900 (2018-06-07)
	Peak-limit: excursion factor (category): 4;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
Benzene, mono-C10-13-alkyl derivs., distn. residues	Workers	Inhalation	Long-term systemic effects	2,2 mg/m3
	Workers	Skin contact	Long-term systemic effects	3,15 mg/kg bw/day
calcium dihydroxide	Workers	Inhalation	Long-term local effects	1 mg/m3
	Workers	Inhalation	Acute local effects	4 mg/m3
Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]	Workers	Skin contact	Long-term systemic effects	0,04 mg/kg
	Workers	Inhalation	Long-term systemic effects	0,29 mg/m3
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	Workers	Inhalation	Long-term local effects	5,58 mg/m3
	Workers	Inhalation	Long-term systemic effects	2,73 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,97 mg/kg
Distillates (petroleum), hydrotreated light paraffinic; Baseoil —	Workers	Inhalation	Long-term systemic effects	2,73 mg/m3

unspecified				
	Workers	Inhalation	Long-term local effects	5,58 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,97 mg/kg bw/day
Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate	Workers	Inhalation	Long-term systemic effects	4,93 mg/m3
	Workers	Dermal	Long-term systemic effects	1,4 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
Benzene, mono-C10-13-alkyl derivs., distn. residues	Fresh water	0,001 mg/l
	Intermittent use/release	0,001 mg/l
	Marine water	0 mg/l
	Microbiological Activity in Sewage Treatment Systems	2 mg/l
	Fresh water sediment	16,5 mg/kg
	Marine sediment	1,65 mg/kg
	Soil	3,7 mg/kg
calcium dihydroxide	Fresh water	0,49 mg/l
	Marine water	0,32 mg/l
	Intermittent use/release	0,49 mg/l
	Microbiological Activity in Sewage Treatment Systems	3 mg/l
	Soil	1080 mg/kg
Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]	Fresh water	0,00638 mg/l
	Marine water	0,000638 mg/l
	Intermittent use/release	0,00509 mg/l
	Microbiological Activity in Sewage Treatment Systems	98,6 mg/l
	Fresh water sediment	204 mg/kg
	Marine sediment	20,4 mg/kg
	Soil	9,93 mg/kg
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	Oral	9,33 mg/kg
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	Oral	9,33 mg/kg

8.2 Exposure controls

Engineering measures

none

Personal protective equipment

Eye/face protection	:	Tightly fitting safety goggles
Hand protection		
Material	:	butyl-rubber
Break through time	:	> 10 min
Protective index	:	Class 1
Remarks	:	Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case. The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.
Skin and body protection	:	Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Respiratory protection	:	Not required; except in case of aerosol formation.
Filter type	:	Filter type A-P
Protective measures	:	The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Environmental exposure controls

Air	:	Should not be released into the environment.
Soil	:	Do not allow contact with soil, surface or ground water. The product should not be allowed to enter drains, water courses or the soil.
Water	:	Do not allow contact with soil, surface or ground water. The product should not be allowed to enter drains, water courses or the soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	solid
Form	:	paste

Colour	:	white
Odour	:	characteristic
Odour Threshold	:	No data available
Melting point/ range	:	No data available
Boiling point/boiling range	:	No data available
Flammability	:	Flammability (solid, gas): Combustible Solids
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
pH	:	Not applicable substance/mixture is non-soluble (in water)
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	Not applicable
Solubility(ies)		
Water solubility	:	insoluble

Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	< 0,001 hPa (20 °C)
Relative density	:	1,29 (20 °C) Reference substance: Water The value is calculated
Density	:	1,29 g/cm3 (20 °C)
Bulk density	:	No data available
Relative vapour density	:	No data available
Particle characteristics		
Particle size	:	Not applicable
Particle Size Distribution	:	Not applicable

9.2 Other information

Explosives	:	Not explosive
Oxidizing properties	:	No data available
Self-ignition	:	not auto-flammable
Metal corrosion rate	:	Not corrosive to metals
Evaporation rate	:	No data available
Sublimation point	:	No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : No conditions to be specially mentioned.

10.5 Incompatible materials

Materials to avoid : No materials to be especially mentioned.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity : Remarks: This information is not available.

Acute dermal toxicity : Symptoms: Redness, Local irritation

Components:

calcium dihydroxide:

Acute oral toxicity : LD50 (Rat, female): > 2.000 mg/kg
Method: OECD Test Guideline 425
GLP: yes
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat, male and female): > 6,04 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Method: OECD Test Guideline 436
GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male and female): > 2.500 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5,53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Acute dermal toxicity : Symptoms: Redness, Local irritation

titanium dioxide; [in powder form containing <1 % of particles with aerodynamic diameter ≤ 10 µm]:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : (Rat): > 5,09 mg/l
Method: OECD Test Guideline 403
GLP: no

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5,53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : This information is not available.

Components:

calcium dihydroxide:

Species : human skin
Assessment : Irritating to skin.
Method : OECD Test Guideline 431
Result : Irritating to skin.
GLP : yes

Species : Rabbit
Assessment : Irritating to skin.
Method : OECD Test Guideline 404
Result : Irritating to skin.
GLP : yes

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Species : Rabbit
Assessment : Irritating to skin.
Result : Irritating to skin.

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Species : Rabbit
Assessment : No skin irritation
Result : No skin irritation
GLP : yes

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Species	:	reconstructed human epidermis (RhE)
Exposure time	:	15 min
Assessment	:	Irritating to skin.
Method	:	OECD Test Guideline 439
Result	:	Irritating to skin.
GLP	:	yes

titanium dioxide; [in powder form containing <1 % of particles with aerodynamic diameter ≤ 10 µm]:

Species	:	Rabbit
Assessment	:	No skin irritation
Method	:	OECD Test Guideline 404
Result	:	No skin irritation
GLP	:	no

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Species	:	Rabbit
Assessment	:	No skin irritation
Method	:	OECD Test Guideline 404
Result	:	No skin irritation
GLP	:	yes

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks	:	This information is not available.

Components:

calcium dihydroxide:

Species	:	Rabbit
Assessment	:	Risk of serious damage to eyes.
Method	:	OECD Test Guideline 405
Result	:	Risk of serious damage to eyes.
GLP	:	yes

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Species	:	Rabbit
Assessment	:	Irritating to eyes.
Method	:	OECD Test Guideline 405
Result	:	Irritating to eyes.

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Species	:	Rabbit
Exposure time	:	48 h
Assessment	:	No eye irritation
Method	:	OECD Test Guideline 405
Result	:	No eye irritation
GLP	:	yes

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Species	:	Bovine cornea
Exposure time	:	10 min
Assessment	:	No eye irritation
Method	:	OECD Test Guideline 437
Result	:	No eye irritation
GLP	:	yes

titanium dioxide; [in powder form containing <1 % of particles with aerodynamic diameter ≤ 10 µm]:

Species	:	Rabbit
Assessment	:	No eye irritation
Method	:	OECD Test Guideline 405
Result	:	No eye irritation

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Species	:	Rabbit
Assessment	:	No eye irritation
Method	:	OECD Test Guideline 405
Result	:	No eye irritation
GLP	:	yes

Respiratory or skin sensitisation

Skin sensitisation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Product:

Remarks : This information is not available.

Components:

calcium dihydroxide:

Test Type	:	Local lymph node assay (LLNA)
Species	:	Mouse
Assessment	:	Does not cause skin sensitisation.
Method	:	OECD Test Guideline 429

Result	:	Does not cause skin sensitisation.
GLP	:	yes

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Assessment	:	Does not cause skin sensitisation.
Result	:	Does not cause skin sensitisation.

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Test Type	:	Buehler Test
Species	:	Guinea pig
Assessment	:	Did not cause sensitisation on laboratory animals.
Method	:	OECD Test Guideline 406
Result	:	Did not cause sensitisation on laboratory animals.
GLP	:	no

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Test Type	:	Local lymph node assay (LLNA)
Species	:	Mouse
Assessment	:	The product is a skin sensitiser, sub-category 1B.
Method	:	OECD Test Guideline 429
Result	:	The product is a skin sensitiser, sub-category 1B.
GLP	:	yes

titanium dioxide; [in powder form containing <1 % of particles with aerodynamic diameter ≤ 10 µm]:

Species	:	Mouse
Assessment	:	Does not cause skin sensitisation.
Method	:	OECD Test Guideline 429
Result	:	Does not cause skin sensitisation.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.
Method	:	OECD Test Guideline 406
Result	:	Does not cause skin sensitisation.
GLP	:	yes

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

calcium dihydroxide:

Genotoxicity in vitro : Test Type: Ames test
Method: OECD Test Guideline 471
Result: negative
GLP: yes

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
GLP: yes

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
GLP: yes

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Genotoxicity in vitro : Test Type: Ames test
Result: negative

Germ cell mutagenicity-Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Germ cell mutagenicity-Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
GLP: yes

Test Type: in vitro micronucleus test
Test system: Human lymphocytes
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 487
Result: negative

GLP: yes

Test Type: In vitro mammalian cell gene mutation test
Test system: mouse lymphoma cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 490
Result: negative
GLP: yes

Germ cell mutagenicity-Assessment : Weight of evidence does not support classification as a germ cell mutagen.

titanium dioxide; [in powder form containing <1 % of particles with aerodynamic diameter ≤ 10 µm]:

Germ cell mutagenicity-Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Carcinogenicity

Based on available data, the classification criteria are not met.

Product:

Remarks : No data available

Components:

calcium dihydroxide:

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

titanium dioxide; [in powder form containing <1 % of particles with aerodynamic diameter ≤ 10 µm]:

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Product:

Effects on fertility	:	Remarks: No data available
Effects on foetal development	:	Remarks: No data available

Components:

calcium dihydroxide:

Reproductive toxicity - Assessment	:	- Fertility - No toxicity to reproduction - Teratogenicity - No effects on or via lactation

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Reproductive toxicity - Assessment	:	- Fertility - No toxicity to reproduction - Teratogenicity - No toxicity to reproduction

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Reproductive toxicity - Assessment	:	- Fertility - No toxicity to reproduction - Teratogenicity - No effects on or via lactation

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Reproductive toxicity - Assessment	:	- Fertility - Animal testing did not show any effects on fertility.

titanium dioxide; [in powder form containing <1 % of particles with aerodynamic diameter ≤ 10 µm]:

Reproductive toxicity - Assessment	:	- Fertility - No toxicity to reproduction - Teratogenicity - No effects on or via lactation

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Reproductive toxicity - Assessment : - Fertility -
No toxicity to reproduction

STOT - single exposure

Based on available data, the classification criteria are not met.

Product:

Remarks : No data available

Components:

calcium dihydroxide:

Assessment : May cause respiratory irritation.

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

titanium dioxide; [in powder form containing <1 % of particles with aerodynamic diameter ≤ 10 µm]:

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Product:

Remarks : No data available

Components:

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Exposure routes : Ingestion
Assessment : May cause damage to organs through prolonged or repeated exposure.

titanium dioxide; [in powder form containing <1 % of particles with aerodynamic diameter ≤ 10 µm]:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Components:

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Species	:	Rat, male and female
NOAEL	:	100 mg/kg
Application Route	:	oral (gavage)
Exposure time	:	28 d
Number of exposures	:	daily
Method	:	OECD Test Guideline 422
GLP	:	yes
Remarks	:	Not classified due to data which are conclusive although insufficient for classification.

Aspiration toxicity

Based on available data, the classification criteria are not met.

Product:

This information is not available.

Components:

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

May be fatal if swallowed and enters airways.

titanium dioxide; [in powder form containing <1 % of particles with aerodynamic diameter ≤ 10 µm]:

No aspiration toxicity classification

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

No aspiration toxicity classification

11.2 Information on other hazards

Endocrine disrupting properties

Based on available data, the classification criteria are not met.

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

Components:

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Remarks : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: Very toxic to aquatic organisms.

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

calcium dihydroxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 50,6 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 49,1 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 184,57 mg/l
Exposure time: 72 h
Test Type: static test

Method: OECD Test Guideline 201
GLP: yes

Ecotoxicology Assessment

Acute aquatic toxicity	:	This product has no known ecotoxicological effects.
Chronic aquatic toxicity	:	This product has no known ecotoxicological effects.

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Toxicity to fish	:	LC50 (Danio rerio (zebra fish)): > 0,1 - 1 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 0,1 - 1 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): > 0,01 - 0,1 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
M-Factor (Acute aquatic toxicity)	:	10
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	EC50: 1,41 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Test Type: semi-static test Method: OECD Test Guideline 211
M-Factor (Chronic aquatic toxicity)	:	1

Ecotoxicology Assessment

Acute aquatic toxicity	:	Very toxic to aquatic life.
Chronic aquatic toxicity	:	Toxic to aquatic life with long lasting effects.

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Test Type: semi-static test Method: OECD Test Guideline 203 GLP: yes Remarks: May cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202 GLP: yes
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 72 h Test Type: static test Method: OECD Test Guideline 201 GLP: yes
Toxicity to microorganisms	:	EC50 (activated sludge): > 1.000 mg/l Exposure time: 3 h Test Type: Respiration inhibition Analytical monitoring: no Method: OECD Test Guideline 209 GLP: yes

titanium dioxide; [in powder form containing <1 % of particles with aerodynamic diameter ≤ 10 µm]:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 203 GLP: yes
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10.000 mg/l Exposure time: 48 h Test Type: Immobilization Method: OECD Test Guideline 202 GLP: yes
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: 10 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Test Type: semi-static test

Method: OECD Test Guideline 211
GLP: yes

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

Components:

calcium dihydroxide:

Biodegradability : Remarks: The methods for determining the biological degradability are not applicable to inorganic substances.

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: rapidly biodegradable
Biodegradation: 65 %
Exposure time: 28 d
Method: OECD Test Guideline 301D
GLP: yes

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Biodegradability : Result: not rapidly degradable
Biodegradation: 31 %
Exposure time: 28 d

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Biodegradability : Result: Not rapidly biodegradable
Biodegradation: 11 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: Not rapidly biodegradable
Biodegradation: 3 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
GLP: yes

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

calcium dihydroxide:

Partition coefficient: n-octanol/water : log Pow: 0,05

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Partition coefficient: n-octanol/water : Pow: > 6
Remarks: Information given is based on data obtained from similar substances.

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Partition coefficient: n-octanol/water : log Pow: > 4

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Partition coefficient: n-octanol/water : log Pow: 10,16 - 24,9

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Components:

Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:

Assessment : Non-classified PBT substance. Non-classified vPvB substance

titanium dioxide; [in powder form containing <1 % of particles with aerodynamic diameter ≤ 10 µm]:

Assessment : Non-classified vPvB substance. Non-classified PBT substance

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Assessment : Non-classified vPvB substance. Non-classified PBT substance

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Components:

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Additional ecological information : May cause long lasting harmful effects to aquatic life.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging	:	Packaging that is not properly emptied must be disposed of as the unused product. Dispose of waste product or used containers according to local regulations. The following Waste Codes are only suggestions:
Waste Code	:	used product, unused product 12 01 12*, spent waxes and fats uncleaned packagings 15 01 10*, packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN	:	UN 3077
ADR	:	UN 3077
RID	:	UN 3077
IMDG	:	UN 3077
IATA	:	UN 3077

14.2 UN proper shipping name

ADN	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (fatty amine derivative)
ADR	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (fatty amine derivative)
RID	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (fatty amine derivative)
IMDG	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (fatty amine derivative)
IATA	:	Environmentally hazardous substance, solid, n.o.s. (fatty amine derivative)

14.3 Transport hazard class(es)

		Class	Subsidiary risks
ADN	:	9	

ADR : 9

RID : 9

IMDG : 9

IATA : 9

14.4 Packing group

ADN

Packing group	:	III
Classification Code	:	M7
Hazard Identification Number	:	90
Labels	:	9

ADR

Packing group	:	III
Classification Code	:	M7
Hazard Identification Number	:	90
Labels	:	9
Tunnel restriction code	:	(-)

RID

Packing group	:	III
Classification Code	:	M7
Hazard Identification Number	:	90
Labels	:	9

IMDG

Packing group	:	III
Labels	:	9
EmS Code	:	F-A, S-F

IATA (Cargo)

Packing instruction (cargo aircraft)	:	956
Packing instruction (LQ)	:	Y956
Packing group	:	III
Labels	:	Miscellaneous Dangerous Goods

IATA (Passenger)

Packing instruction (passenger aircraft)	:	956
Packing instruction (LQ)	:	Y956
Packing group	:	III
Labels	:	Miscellaneous Dangerous Goods

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG
Marine pollutant : yes

IATA (Passenger)
Environmentally hazardous : yes

IATA (Cargo)
Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries must be considered:: Number on list 75 If you intend to use this product as tattoo ink, please contact your vendor. Number on list 40 This substance/mixture shall not be used in aerosol dispensers intended for supply to the general public for entertainment and decorative purposes.
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). (EU SVHC)	:	This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).
Regulation (EU) No 2024/590 on substances that deplete the ozone layer (EC 2024/590)	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast) (EU POP)	:	Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals (EU PIC)	:	Not applicable
REACH - List of substances subject to authorisation (Annex XIV) (EU. REACH-Annex XIV)	:	Not applicable
Regulation (EU) 2019/1148 on the marketing and use of explosives precursors		Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	E1	ENVIRONMENTAL HAZARDS

Water hazard class (Germany)	:	WGK 3 highly hazardous to water Classification according to AwSV, Annex 1 (5.2)
TA Luft List (Germany)	:	5.2.1: Total dust: others: 51,81 % 5.2.5: Organic Substances: Class 1: 10,71 %
Volatile organic compounds	:	Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0,02 %

15.2 Chemical safety assessment

This information is not available.

OKS 250

Version	Revision Date:	Date of last issue: 31.07.2026	Print Date:
6.0	03.11.2026	Date of first issue: 23.06.2016	03.11.2026

SECTION 16: Other information

Full text of H-Statements

H304	:	May be fatal if swallowed and enters airways.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H335	:	May cause respiratory irritation.
H373	:	May cause damage to organs through prolonged or repeated exposure if swallowed.
H400	:	Very toxic to aquatic life.
H411	:	Toxic to aquatic life with long lasting effects.
H413	:	May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Note L	:	The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 (“Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extraction refractive index method”Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2017/164/EU	:	Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
DE DFG MAK	:	Germany. MAK BAT Annex IIa
DE TRGS 527	:	Germany. TRGS 527 - Activities with nanomaterials
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
2017/164/EU / STEL	:	Short term exposure limit
2017/164/EU / TWA	:	Limit Value - eight hours
DE DFG MAK / MAK	:	MAK value
DE TRGS 527 / BM	:	Assessment scale
DE TRGS 900 / AGW	:	Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; BGW - Biological Limit Values; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or

Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); LSPN - List of Hazardous Notified Substances (Chile); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:		**Classification procedure:**
Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
Aquatic Acute 1	H400	Calculation method
Aquatic Chronic 3	H412	Calculation method

|| Relevant changes compared to the last edition are highlighted at the left margin. This version replaces all previous editions.

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on

the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.