




# OKS 2811

## Leak Detector, frost-proof, Spray



### Description

Frost-proof liquid leak detector for the location of leaks in pressurised piping and containers that are made visible by immediate formation of bubbles at leak location.

### Applications

- Leak detector high detection sensitivity for pressurised piping and containers, e.g. on compressors, steel bottles, fittings, shut-off valves, breathing devices, oxyacetylene gas and inert-gas arc welding devices, Bunsen burners, valves, screw fittings of compressed-air lines etc.
- Suitable for compressed air, refrigerant, acetylene, butane, natural gas, carbon dioxide, gaseous oxygen, propane, town gas, nitrogen, hydrogen and, ammonia
- Suitable for checking the safety of systems with combustible gases and for avoiding financial losses through unrecognized leaks

### Advantages and benefits

- Frost-proof to -15°C
- Saves energy and warns of gas loss
- Contains corrosion protection inhibitors
- Tested by the DVGW in accordance with DIN EN 14291
- Non-combustible
- Economical in use

### Branches

- Rubber and plastic processing
- Plant and machine (tool) engineering
- Maintenance and servicing
- Paper and packaging industry
- Glass and foundry industry
- Shipbuilding and marine technology
- Municipal services
- Logistics
- Chemical industry
- Rail vehicle technology
- Iron and steel industry

### Application tips

Spray onto pressurised systems from approx. 30-50 cm distance. A leak is indicated by the formation of foam bubbles. In case of very small leaks observe for some time. After plastic parts have been checked, subsequent flushing with water immediately afterwards is recommended in view of possible stress corrosion cracking.

OKS 2811

Leak Detector, frost-proof, Spray

Packaging

- 400 ml Spray

Technical data

	Standard	Conditions	Unit	Value
Main components				
basis				water
additives				active ingredients
additives				corrosion protection
Application related technical data				
lower operating temperature			°C	-15
upper operating temperature			°C	50
colour				colourless
density (at 20°C)	DIN EN ISO 3838		g/cm³	1.02
Product specific technical data				
pH value				7-8
Properties and approvals				
UFI				WAU1-E0RP-F00E-X0XM
DVGW approval	DIN EN 14 291			Reg.-Nr. DG-5170D0160

OKS Spezialschmierstoffe GmbH

Ganghoferstraße 47

82216 Maisach

+49 8142 3051 - 500

info@oks-germany.com

www.oks-germany.com



The information in this publication reflects state-of-the-art technology, as well as extensive testing and experience. Due to the diversity of possible applications and technical realities, they can only serve as recommendations and are not arbitrarily transferable. Therefore, no obligations, liability or warranty claims can be derived from them. We only accept liability for the suitability of our products for particular purposes, and for certain properties of our products, in the event that we have accepted such liability in writing in the individual case. Any case of justified warranty claims shall be limited to the delivery of replacement goods free of defects, in the event that this subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular the liability for consequential injuries or damage, shall always be excluded. Prior to use, the customer must conduct its own testing to prove suitability. The data are subject to change for the sake of progress. ® = Registered trademark

**Product restricted to professional users.** Safety data sheet available for download at [www.oks-germany.com](http://www.oks-germany.com)

Our Customer and Technical service will be pleased to help should you have any further questions.