


OKS 2811

Leak Detector, frost-proof, Spray



Description

Frost-proof liquid leak detector for the location of leaks in pressurised piping and containers that are made visible by immediate formation of bubbles at leak location.

Applications

- Leak detector high detection sensitivity for pressurised piping and containers, e.g. on compressors, steel bottles, fittings, shut-off valves, breathing devices, oxyacetylene gas and inert-gas arc welding devices, Bunsen burners, valves, screw fittings of compressed-air lines etc.
- Suitable for compressed air, refrigerant, acetylene, butane, natural gas, carbon dioxide, gaseous oxygen, propane, town gas, nitrogen, hydrogen and, ammonia
- Suitable for checking the safety of systems with combustible gases and for avoiding financial losses through unrecognized leaks

Advantages and benefits

- Frost-proof to -15°C
- Saves energy and warns of gas loss
- Contains corrosion protection inhibitors
- Tested by the DVGW in accordance with DIN EN 14291
- Non-combustible
- Economical in use

Branches

- Rubber and plastic processing
- Plant and machine (tool) engineering
- Maintenance and servicing
- Paper and packaging industry
- Glass and foundry industry
- Shipbuilding and marine technology
- Municipal services
- Logistics
- Chemical industry
- Rail vehicle technology
- Iron and steel industry

Application tips

Spray onto pressurised systems from approx. 30-50 cm distance. A leak is indicated by the formation of foam bubbles. In case of very small leaks observe for some time. After plastic parts have been checked, subsequent flushing with water immediately afterwards is recommended in view of possible stress corrosion cracking.

OKS 2811

Leak Detector, frost-proof, Spray

Packaging

- 400 ml Spray

Technical data

	Standard	Conditions	Unit	Value
Main components				
basis				water
additives				active ingredients
additives				corrosion protection
Application related technical data				
lower operating temperature			°C	-15
upper operating temperature			°C	50
colour				colourless
density	DIN EN ISO 3838	at 20°C	g/cm ³	1.02
Product specific technical data				
pH value				7-8
Properties and approvals				
UFI				WAU1-E0RP-F00E-X0XM
DVGW approval	DIN EN 14 291			Reg.-Nr. DG-5170D0160

Klüber Lubrication München GmbH & Co. KG
 Geisenhausenerstraße 7 / 81379 München /
 Germany / phone +49 89 7876-0

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.