according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



**OKS 2351** 

VersionRevision Date:Date of last issue: 08.09.2021Print Date:3.220.01.2023Date of first issue: 26.10.201620.01.2023

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 2351

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Lubricant spray

stance/Mixture

Recommended restrictions

on use

Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com

E-mail address of person : mcm@oks-germany.com

responsible for the SDS Material Compliance Management

National contact

1.4 Emergency telephone number

Emergency telephone num: +49 8142 3051 517

ber

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

## Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

Specific target organ toxicity - single ex-

posure, Category 3, Central nervous

sveten

H336: May cause drowsiness or dizziness.

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters air-

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



**OKS 2351** 

VersionRevision Date:Date of last issue: 08.09.2021Print Date:3.220.01.2023Date of first issue: 26.10.201620.01.2023

ways.

Long-term (chronic) aquatic hazard, Cat-

egory 3

H412: Harmful to aquatic life with long lasting ef-

fects.

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H304 May be fatal if swallowed and enters air-

ways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting ef-

fects.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smokina.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use.

Response:

P301 + P310 IF SWALLOWED: Immediately call a

POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

## Hazardous components which must be listed on the label:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



**OKS 2351** 

Version **Revision Date:** Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : Active agent with propellant and solvent.

Components

Components		1	1	_
Chemical name	CAS-No.	Classification	specific concen-	Concentration
	EC-No.		tration limit	(% w/w)
			M-Factor	
	Index-No.		Notes	
	Registration number		Acute toxicity	
			estimate	
Hydrocarbons, C6-C7,		Flam. Liq.2; H225		>= 10 - < 20
n-alkanes, isoalkanes,	921-024-6	Skin Irrit.2; H315		
cyclics, <5% n-hexane	02.02.0	STOT SE3; H336		
dyellos, 30 % ii iiexaiie		Asp. Tox.1; H304		
	01-2119475514-35-	Aquatic Chronic2;		
	XXXX	H411		
	^^^^	11411		
Kaolin, calcined	92704-41-1	Eye Irrit.2; H319		>= 1 - < 10
radiiri, daldirida	296-473-8	STOT SE3; H335;		7 1 1 10
	230 473 0	EUH066		
		L011000		
Substances with a work	xplace exposure limit :			
butane	106-97-8	Flam. Gas1A;		>= 30 - < 50
	203-448-7	H220		
	200 110 /	Press. GasCompr.	Note U (table	
	601-004-00-0	Gas; H280	3.1), Note C	
	01-2119474691-32-	043, 11200	3.1), Note 0	
	XXXX			
	^^^^			
propane	74-98-6	Flam. Gas1A;		>= 10 - < 20
Propario	200-827-9	H220		7 10 \ 20
	200 021-9	Press. GasCompr.	Note U (table	
	601-003-00-5	Gas; H280	3.1)	
		Gas, FIZOU	3.1)	
	01-2119486944-21-			
	XXXX			
distillates (petroleum),	64742-54-7	Not classified		>= 10 - < 20
distillates (petroleum),	07172-04-1	I NOT CIASSITICA		/- 10 · \ 20

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



## **OKS 2351**

VersionRevision Date:Date of last issue: 08.09.2021Print Date:3.220.01.2023Date of first issue: 26.10.201620.01.2023

hydrotreated heavy paraffinic	265-157-1 649-467-00-8 01-2119484627-25- XXXX		Note L	
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified	64742-65-0 265-169-7 649-474-00-6 01-2119471299-27- XXXX	Not classified	Note L	>= 10 - < 20
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1 01-2119529243-45- XXXX	Flam. Sol.1; H228	Note T	>= 1 - < 10
isobutane	75-28-5 200-857-2 601-004-00-0 01-2119485395-27- XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 1 - < 10

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

If inhaled : Call a physician or poison control centre immediately.

Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial respira-

tion.

In case of skin contact : Take off all contaminated clothing immediately.

Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse. Wash off immediately with plenty of water.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



**OKS 2351** 

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

for at least 10 minutes.

If eye irritation persists, consult a specialist.

If swallowed : Move the victim to fresh air.

If accidentally swallowed obtain immediate medical attention.

Keep respiratory tract clear. Do NOT induce vomiting. Rinse mouth with water.

Aspiration hazard if swallowed - can enter lungs and cause

damage.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:

Unconsciousness

Dizziness Drowsiness Headache Nausea Tiredness

Skin contact may provoke the following symptoms:

Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Risks : Central nervous system depression

Risk of product entering the lungs on vomiting after ingestion.

Health injuries may be delayed.

Causes skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

# **SECTION 5: Firefighting measures**

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Fire Hazard

Do not let product enter drains.

Contains gas under pressure; may explode if heated.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Hazardous combustion prod- : Carbon oxides

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



**OKS 2351** 

VersionRevision Date:Date of last issue: 08.09.2021Print Date:3.220.01.2023Date of first issue: 26.10.201620.01.2023

ucts Nitrogen oxides (NOx)

Metal oxides

5.3 Advice for firefighters

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposi-

tion products may be a hazard to health.

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Cool containers/tanks with water spray.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Ensure adequate ventilation. Remove all sources of ignition.

Do not breathe vapours or spray mist.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8. Only qualified personnel equipped with suitable protective

equipment may intervene.

## 6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

# 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

Keep in suitable, closed containers for disposal.

Non-sparking tools should be used.

# 6.4 Reference to other sections

For personal protection see section 8.

## **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



**OKS 2351** 

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

Advice on safe handling : Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.

Keep away from fire, sparks and heated surfaces.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Wash hands and face before breaks and immediately after

handling the product.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest.

Do not use sparking tools.

These safety instructions also apply to empty packaging which

may still contain product residues.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn,

even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

## 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular national regulations.

Storage class (TRGS 510) : 2B, Aerosol cans and lighters

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
butane	106-97-8	AGW	1.000 ppm 2.400 mg/m3	DE TRGS 900 (2006-01-01)
	Peak-limit: ex	cursion factor (categ	ory): 4;(II)	
propane	74-98-6	AGW	1.000 ppm 1.800 mg/m3	DE TRGS 900



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



# **OKS 2351**

VersionRevision Date:Date of last issue: 08.09.2021Print Date:3.220.01.2023Date of first issue: 26.10.201620.01.2023

				(2006-01-01)
	Peak-limit: excursion factor (category): 4;(II)			
distillates (petrole- um), hydrotreated heavy paraffinic	64742-54-7	AGW (Vapour and aerosols)	5 mg/m3	DE TRGS 900 (2018-06-07)
	Peak-limit: ex	cursion factor (categ	ory): 4;(II)	
	Further inform	nation: When there is	compliance with the OEL are from the order of harming the unborn child	nd biological
Distillates (petrole- um), solvent- dewaxed heavy paraffinic; Baseoil — unspecified	64742-65-0	AGW (Vapour and aerosols)	5 mg/m3	DE TRGS 900 (2018-06-07)
	Peak-limit: excursion factor (category): 4;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
aluminium powder (stabilised)	7429-90-5	AGW (Inhalable fraction)	10 mg/m3	DE TRGS 900 (2014-04-02)
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological			
	tolerance valu	ies, there is no risk o	f harming the unborn child	
		AGW (Alveolate fraction)	1,25 mg/m3	DE TRGS 900 (2014-04-02)
	Peak-limit: ex	cursion factor (categ	ory): 2;(II)	,
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
isobutane	75-28-5	AGW	1.000 ppm 2.400 mg/m3	DE TRGS 900 (2006-01-01)
	Peak-limit: excursion factor (category): 4;(II)			

# **Biological occupational exposure limits**

Substance name	CAS-No.	Control parameters	Sampling time	Basis
aluminium powder (stabilised)	7429-90-5	Aluminium: 50 μg/g creatinine (Urine)	In case of long- term exposure: after more than one shift	TRGS 903 (2019-03- 29)

# Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
distillates (petroleum), hydrotreated heavy paraffinic	Workers	Inhalation	Long-term local effects	5,58 mg/m3
	Workers	Inhalation	Long-term systemic effects	2,73 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,97 mg/kg
Distillates (petrole- um), solvent-dewaxed	Workers	Inhalation	Long-term systemic effects	2,73 mg/m3



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



## **OKS 2351**

VersionRevision Date:Date of last issue: 08.09.2021Print Date:3.220.01.2023Date of first issue: 26.10.201620.01.2023

heavy paraffinic; Baseoil — unspecified				
•	Workers	Skin contact	Long-term systemic effects	0,97 mg/kg
Hydrocarbons, C6- C7, n-alkanes, isoal- kanes, cyclics, <5% n-hexane	Workers	Skin contact	Long-term systemic effects	773 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	2035 mg/m3
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3,72 mg/m3
	Workers	Inhalation	Long-term local ef- fects	3,72 mg/m3

## Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
distillates (petroleum), hy-	Oral	9,33 mg/kg
drotreated heavy paraffinic		
Distillates (petroleum), solvent-	Oral	9,33 mg/kg
dewaxed heavy paraffinic;		
Baseoil — unspecified		

#### 8.2 Exposure controls

## **Engineering measures**

Use only in an area equipped with explosion proof exhaust ventilation.

Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye protection : Safety glasses with side-shields

Hand protection

Material : butyl-rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each

case.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374

derived from it.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ven-

tilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



**OKS 2351** 

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

Short term only

Filter type : Filter type A-P

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

# **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state : aerosol

Colour : grey

Odour : characteristic

Odour Threshold : No data available

Melting point/range : No data available

Boiling point/boiling range : -44,5 °C (1.013 hPa)

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

10,9 %(V)

Lower explosion limit / Lower

flammability limit

0,8 %(V)

Flash point : -97,00 °C

Method: Abel-Pensky

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable

substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : < 20,5 mm2/s (40 °C)

Solubility(ies)

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



## **OKS 2351**

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 4.750 hPa (20 °C)

Relative density : 0,7 (20 °C)

Reference substance: Water The value is calculated

Density : 0,70 g/cm3

(20 °C)

Bulk density : No data available

Relative vapour density : No data available

9.2 Other information

Explosives : Not explosive

Oxidizing properties : No data available

Self-ignition : not auto-flammable

Metal corrosion rate : Not corrosive to metals

Evaporation rate : No data available

Sublimation point : No data available

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No hazards to be specially mentioned.

#### 10.2 Chemical stability

Stable under normal conditions.

## 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

Strong sunlight for prolonged periods.

Risk of receptacle bursting.

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



**OKS 2351** 

VersionRevision Date:Date of last issue: 08.09.2021Print Date:3.220.01.2023Date of first issue: 26.10.201620.01.2023

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

## 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

# **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

# **Acute toxicity**

**Product:** 

Acute oral toxicity : Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

Acute inhalation toxicity : Assessment: The substance or mixture is classified as specific

target organ toxicant, single exposure, category 3 with narcot-

ic effects.

Remarks: Respiration of solvent vapour may cause dizziness.

Symptoms: Inhalation may provoke the following symptoms:, Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fa-

tigue, Vertigo, Central nervous system depression

Acute dermal toxicity : Symptoms: Redness, Local irritation

## **Components:**

## Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): > 5.840 mg/kg

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 25,2 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2,8 g/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Kaolin, calcined:

Acute inhalation toxicity : Assessment: The substance or mixture is classified as specific

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



**OKS 2351** 

VersionRevision Date:Date of last issue: 08.09.2021Print Date:3.220.01.2023Date of first issue: 26.10.201620.01.2023

target organ toxicant, single exposure, category 3 with respira-

tory tract irritation.

butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h Test atmosphere: gas

distillates (petroleum), hydrotreated heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5,53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Method: OECD Test Guideline 402

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Method: OECD Test Guideline 402

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5,09 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h
Test atmosphere: gas

Skin corrosion/irritation

**Product:** 

Remarks : Irritating to skin.

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



## **OKS 2351**

VersionRevision Date:Date of last issue: 08.09.2021Print Date:3.220.01.2023Date of first issue: 26.10.201620.01.2023

#### **Components:**

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

Assessment : Irritating to skin.

Method : OECD Test Guideline 404

Result : Irritating to skin.

Kaolin, calcined:

Result : Repeated exposure may cause skin dryness or cracking.

## distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes

#### aluminium powder (stabilised):

Species : Rabbit

Assessment : No skin irritation Result : No skin irritation

## Serious eye damage/eye irritation

**Product:** 

Remarks : Contact with eyes may cause irritation.

#### Components:

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

Assessment : No eye irritation Result : No eye irritation

Kaolin, calcined:

Result : Irritating to eyes.

## distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



## **OKS 2351**

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

GLP : yes

## Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Species : Rabbit

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

GLP : yes

## aluminium powder (stabilised):

Species : Rabbit

Assessment : No eye irritation Result : No eye irritation

#### Respiratory or skin sensitisation

#### **Product:**

Remarks : This information is not available.

#### **Components:**

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Test Type : Maximisation Test

Exposure routes : Dermal Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Did not cause sensitisation on laboratory animals.

## distillates (petroleum), hydrotreated heavy paraffinic:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

GLP : yes

# Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

GLP : yes

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



# **OKS 2351**

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

#### aluminium powder (stabilised):

Species : Guinea pig

Assessment : Did not cause sensitisation on laboratory animals. Result : Did not cause sensitisation on laboratory animals.

#### Germ cell mutagenicity

**Product:** 

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

## **Components:**

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Test system: Rodent cell line Method: OECD Test Guideline 473

Result: negative

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Genotoxicity in vitro : Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Species: Mouse

**Application Route: Oral** 

Method: OECD Test Guideline 474

Result: negative

## Carcinogenicity

**Product:** 

Remarks : No data available

#### Components:

#### distillates (petroleum), hydrotreated heavy paraffinic:

Carcinogenicity - Assess-

: Not classifiable as a human carcinogen.

ment

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Species : Mouse Application Route : Dermal

Method : OECD Test Guideline 451

Result : negative

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



**OKS 2351** 

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

Reproductive toxicity

**Product:** 

Effects on fertility : Remarks: No data available

Effects on foetal develop-

ment

: Remarks: No data available

Components:

distillates (petroleum), hydrotreated heavy paraffinic:

Reproductive toxicity - As- : - Fertility -

sessment No toxicity to reproduction

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Effects on foetal develop-

ment

Species: Rat

Application Route: Dermal

General Toxicity Maternal: NOAEL: 30 mg/kg body weight Developmental Toxicity: NOAEL: 30 mg/kg body weight

Method: OECD Test Guideline 414

STOT - single exposure

**Components:** 

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

Kaolin, calcined:

Exposure routes : Inhalation

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 3 with respiratory tract

irritation.

STOT - repeated exposure

**Components:** 

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Exposure routes : inhalation (vapour)

Assessment : No significant health effects observed in animals at concentra-

tions of 1 mg/l/6h/d or less.

Repeated dose toxicity

**Product:** 

Remarks : This information is not available.

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



## **OKS 2351**

VersionRevision Date:Date of last issue: 08.09.2021Print Date:3.220.01.2023Date of first issue: 26.10.201620.01.2023

# **Aspiration toxicity**

#### **Product:**

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

#### **Components:**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

May be fatal if swallowed and enters airways.

distillates (petroleum), hydrotreated heavy paraffinic:

No aspiration toxicity classification

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

No aspiration toxicity classification

#### 11.2 Information on other hazards

## **Endocrine disrupting properties**

## **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

**Further information** 

**Product:** 

Remarks : Ingestion causes irritation of upper respiratory system and

gastrointestinal disturbance.

# **SECTION 12: Ecological information**

# 12.1 Toxicity

**Product:** 

Toxicity to fish : Remarks: Harmful to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic : Remarks: No data available

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



**OKS 2351** 

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

plants

Toxicity to microorganisms

Remarks: No data available

**Components:** 

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 22 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 3 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae/aquatic

plants

EbC50 (Pseudokirchneriella subcapitata (green algae)): 26

mg/

Exposure time: 72 h

Method: OECD Test Guideline 201

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

distillates (petroleum), hydrotreated heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10.000 mg/l

Exposure time: 48 h
Test Type: Immobilization

Method: OECD Test Guideline 202

GLP: yes

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 10 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test

Method: OECD Test Guideline 211

GLP: yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



**OKS 2351** 

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

> Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10.000 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOEC (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

NOEC: 10 mg/l Exposure time: 21 d

ic toxicity)

Species: Daphnia magna (Water flea)

aluminium powder (stabilised):

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 0,12 mg/l

> Exposure time: 96 h Test Type: static test

Remarks: No toxicity at the limit of solubility

**Ecotoxicology Assessment** 

Acute aquatic toxicity This product has no known ecotoxicological effects.

Chronic aquatic toxicity This product has no known ecotoxicological effects.

12.2 Persistence and degradability

**Product:** 

Biodegradability Remarks: No data available

Physico-chemical removabil- :

Remarks: No data available

ity

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Biodegradability : Result: Readily biodegradable.

distillates (petroleum), hydrotreated heavy paraffinic:

Biodegradability Test Type: aerobic

Inoculum: activated sludge Result: Not rapidly biodegradable

Biodegradation: 3 % Exposure time: 28 d



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



**OKS 2351** 

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

Method: OECD Test Guideline 301B

GLP: yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge Result: Not rapidly biodegradable

Biodegradation: 31 % Exposure time: 28 d

Method: OECD Test Guideline 301B

GLP: yes

12.3 Bioaccumulative potential

**Product:** 

Bioaccumulation : Remarks: This mixture contains no substance considered to

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

**Components:** 

butane:

Partition coefficient: n- :

octanol/water

log Pow: 2,89

Method: OECD Test Guideline 107

propane:

Partition coefficient: n-

octanol/water

log Pow: 2,36

distillates (petroleum), hydrotreated heavy paraffinic:

Partition coefficient: n-

octanol/water

: log Pow: > 2

isobutane:

Partition coefficient: n- : log Pow: 2,88

octanol/water Method: OECD Test Guideline 107

12.4 Mobility in soil

**Product:** 

Mobility : Remarks: No data available

Distribution among environ-

mental compartments

: Remarks: No data available



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



## **OKS 2351**

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

#### 12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

#### Components:

distillates (petroleum), hydrotreated heavy paraffinic:

Assessment : Non-classified vPvB substance. Non-classified PBT substance

#### 12.6 Endocrine disrupting properties

**Product:** 

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### 12.7 Other adverse effects

**Product:** 

Additional ecological infor-

mation

: Harmful to aquatic life with long lasting effects.

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Waste codes should be assigned by the user based on the

application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Offer empty spray cans to an established disposal company. Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied

16 05 04\*, gases in pressure containers (including halons)

containing hazardous substances

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



## **OKS 2351**

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

# **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

## 14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

IATA : Aerosols, flammable

#### 14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

#### 14.4 Packing group

#### ADN

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1

## **ADR**

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

#### **RID**

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

**IMDG** 

Packing group : Not assigned by regulation

Labels : 2.1

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



**OKS 2351** 

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

**EmS Code** : F-D, S-U

IATA (Cargo)

Packing instruction (cargo 203

aircraft)

Packing instruction (LQ) Y203

Packing group Not assigned by regulation

Labels Flammable Gas

IATA (Passenger)

Packing instruction (passen-203

ger aircraft)

Packing instruction (LQ) Y203

Packing group Not assigned by regulation

Labels Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous no

Environmentally hazardous no

Environmentally hazardous no

**IMDG** 

Marine pollutant no

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

: Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

(EU SVHC)

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH),

Article 57). Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

(EU. REACH-Annex XIV)

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



**OKS 2351** 

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer (EC 1005/2009)

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast) (EU POP)

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals

(EU PIC)

Not applicable

Regulation (EU) 2019/1148 on the marketing and use of :

explosives precursors

Listed

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant na-

tional contact point. Please see

https://ec.europa.eu/home-affairs/sites/ homeaffairs/files/what-we-do/policies/crisis-and-

terrorism/explosives/explosives-

precur-

sors/docs/list\_of\_competent\_authorities\_and\_national\_c

ontact points en.pdf

aluminium powder (stabilised) (ANNEX II)

: P2

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

FLAMMABLE AEROSOLS P3a

18 Liquefied extremely flammable gases (including LPG) and natural gas

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Water hazard class (Germa- : WGK 2 obviously hazardous to water

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



## **OKS 2351**

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

ny) Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : Total dust:

others: 2,53 %

Inorganic substances in powdered form:

Not applicable

Inorganic substances in vapour or gaseous form:

Not applicable Organic Substances: portion Class 1: 0,16 %

others: 89,82 %

Carcinogenic substances:

Not applicable Mutagenic: Not applicable Toxic to reproduction: Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 62,5 %

## Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

#### 15.2 Chemical safety assessment

This information is not available.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

EUH066 : Repeated exposure may cause skin dryness or cracking.

H220 : Extremely flammable gas.

H225 : Highly flammable liquid and vapour.

H228 : Flammable solid.

H280 : Contains gas under pressure; may explode if heated.

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H319
H335
H336
Causes serious eye irritation.
May cause respiratory irritation.
H336
May cause drowsiness or dizziness.

H411 : Toxic to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

#### Full text of other abbreviations



according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



**OKS 2351** 

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

Note C : Some organic substances may be marketed either in a specif-

ic isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the sub-

stance is a specific isomer or a mixture of isomers.

Note L : The harmonised classification as a carcinogen applies unless

it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extraction refractive index method"Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard

class.

Note T : This substance may be marketed in a form which does not

have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be in-

cluded in the safety data sheet.

Note U (table 3.1) : When put on the market gases have to be classified as "Gas-

es under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part

2, Section 2.3.2.1, Note 2).

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

TRGS 903 : TRGS 903 - Biological limit values

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good La-

according to Regulation (EC) No. 1907/2006 - DE (Commission Regulation (EU) 2020/878)



**OKS 2351** 

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

boratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

## Classification of the mixture: Classification procedure:

Aerosol 1	H222, H229	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
STOT SE 3	H336	Based on product data or assessment
Asp. Tox. 1	H304	Based on product data or assessment
Aquatic Chronic 3	H412	Calculation method

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.