



OKS 2610

Universal Cleaner





Description

Residue-free evaporating universal cleaner for cleaning machine parts and material surfaces.

Applications

- Degreasing all surfaces and parts of non-absorbent materials, e.g. metals, ceramic or plastics and elastomers
- Cleaning of adhesive surfaces for coatings, paints or adhesives and sealants
- Cleaning of friction surfaces on which high friction forces are transmitted such as clutch and brake linings (brake cleaners)
- Removal of aged and gummy oil and grease residues, of residues of brake fluids and silicones, as well as of residues of simple coatings, adhesives and sealants

Branches

- · Shipbuilding and marine technology
- · Rail vehicle technology
- · Plant and machine (tool) engineering
- Logistics
- · Maintenance and servicing
- · Iron and steel industry
- · Glass and foundry industry
- Paper and packaging industry
- Chemical industry
- · Rubber and plastic processing
- Municipal services

Application tips

Wetting of the surfaces to be cleaned to excess. Cleaning is made even more effective if you simultaneously rub away at the surface with paper or cellulose cloths. If necessary, repeat the process at stubborn soiling. Small parts can be cleaned immersed using a brush. Subsequently allow to dry completely at room temperature. Dab away running cleaner with absorbent material and allow to evaporate in open air. Use only in well-ventilated rooms or in the open air. Some types of plastic or rubber (e.g. thermoplastics such as PVC, plexiglass, polystyrene) and paints could be attacked. We recommend therefore that you check the resistance before use.

Advantages and benefits

- Modern active cleaner on the basis of a solvent mixture
- Highly effective due to actively cleaning substances
- Better initial dissolving of soiling than at brake cleaners thanks to longer soaking-in period
- No formation of condensate on the material surface
- OKS 2610 is suitable for use with the OKS Airspray system
- Also available as spray version OKS 2611 (propellant gas CO₂)









OKS 2610

Universal Cleaner

Packaging

• 5 l Canister

• 25 I Canister

• 200 l Drum

Technical data

	Standard	Conditions	Unit	Value
Main components				
basis				solvent mixture
Application related technical data				
viscosity	DIN 51 562-1	\$BEI_40_GRAD	mm²/s	< 0.76
flashing point			°C	> 21
colour				colourless
density	DIN EN ISO 3838	at 20°C	g/cm³	0.76
Properties and approvals				
UFI				25U1-E0CV-U00E-MASG

OKS Spezialschmierstoffe GmbH

Ganghoferstraße 47 82216 Maisach

4 +49 8142 3051 - 500

☑ info@oks-germany.com

★ www.oks-germany.com

a brand of



The information in this publication reflects state-of-the-art technology, as well as extensive testing and experience. Due to the diversity of possible applications and technical realities, they can only serve as recommendations and are not arbitrarily transferable. Therefore, no obligations, liability or warranty claims can be derived from them. We only accept liability for the suitability of our products for particular purposes, and for certain properties of our products, in the event that we have accepted such liability in writing in the individual case. Any case of justified warranty claims shall be limited to the delivery of replacement goods free of defects, in the event that this subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular the liability for consequential injuries or damage, shall always be excluded. Prior to use, the customer must conduct its own testing to prove suitability. The data are subject to change for the sake of progress. * = Registered trademark

Product restricted to professional users. Safety data sheet available for download at www.oks-germany.com Our Customer and Technical service will be pleased to help should you have any further questions.





