


OKS 2610 Universal Cleaner

a product brand of **KLÜBER**
LUBRICATION



Description

Residue-free evaporating universal cleaner for cleaning machine parts and material surfaces.

Applications

- Degreasing all surfaces and parts of non-absorbent materials, e.g. metals, ceramic or plastics and elastomers
- Cleaning of adhesive surfaces for coatings, paints or adhesives and sealants
- Cleaning of friction surfaces on which high friction forces are transmitted such as clutch and brake linings (brake cleaners)
- Removal of aged and gummy oil and grease residues, of residues of brake fluids and silicones, as well as of residues of simple coatings, adhesives and sealants

Advantages and benefits

- Modern active cleaner on the basis of a solvent mixture
- Highly effective due to actively cleaning substances
- Better initial dissolving of soiling than at brake cleaners thanks to longer soaking-in period
- No formation of condensate on the material surface
- OKS 2610 is suitable for use with the OKS Airspray system
- Also available as spray version OKS 2611 (propellant gas CO₂)

Branches

- Shipbuilding and marine technology
- Rail vehicle technology
- Plant and machine (tool) engineering
- Logistics
- Maintenance and servicing
- Iron and steel industry
- Glass and foundry industry
- Paper and packaging industry
- Chemical industry
- Rubber and plastic processing
- Municipal services

Application tips

Wetting of the surfaces to be cleaned to excess. Cleaning is made even more effective if you simultaneously rub away at the surface with paper or cellulose cloths. If necessary, repeat the process at stubborn soiling. Small parts can be cleaned immersed using a brush. Subsequently allow to dry completely at room temperature. Dab away running cleaner with absorbent material and allow to evaporate in open air. Use only in well-ventilated rooms or in the open air. Some types of plastic or rubber (e.g. thermoplastics such as PVC, plexiglass, polystyrene) and paints could be attacked. We recommend therefore that you check the resistance before use.



OKS 2610 Universal Cleaner

a product brand of **KLÜBER**
LUBRICATION

Packaging

- 5 l Canister
- 25 l Canister
- 200 l Drum

Technical data

	Standard	Conditions	Unit	Value
Main components				
basis				solvent mixture
Application related technical data				
viscosity	DIN 51 562-1	at 40°C	mm ² /s	< 0.76
flashing point			°C	> 21
colour				colourless
density	DIN EN ISO 3838	at 20°C	g/cm ³	0.76
Properties and approvals				
UFI				25U1-E0CV-U00E-MASG

Klüber Lubrication München GmbH & Co. KG
Geisenhausenerstraße 7 / 81379 München /
Germany / phone +49 89 7876-0

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.