



# **OKS 2681**

# **Adhesive and Paint Remover, Spray**



#### Description

Highly-effective cleaner for removing stubborn residues, such as residues of sealants, paints and adhesives in industry, trade and workshops.

### **Applications**

- Dissolving of a wide range of sealants and adhesives such as polyurethane residues, materials containing epoxies
- · Elimination of oily and greasy soiling
- Removal of bitumen and tar splashes
- · Dissolving of labels and adhesive strips
- Removal of paints on a PMMA and PU resin basis from metal surfaces

#### **Branches**

- · Paper and packaging industry
- · Iron and steel industry
- · Rubber and plastic processing
- · Plant and machine (tool) engineering
- · Municipal services
- · Rail vehicle technology
- Glass and foundry industry
- · Shipbuilding and marine technology
- Logistics
- · Chemical industry
- · Maintenance and servicing

### **Application tips**

Shake can well before use. Spray onto the surfaces to be cleaned and, depending on the degree of soiling, allow it to react for a longer period. Repeat if necessary. Subsequently wipe off with a moist cloth. Caution: When using on plastics and sensitive surfaces check compatibility beforehand.

#### **Packaging**

· 400 ml Spray

### **Advantages and benefits**

- Good infiltration of adhesive films allows easy removal of the residues from the surface
- · Good washable with water after use
- Applicable to surfaces of metal, stainless steel, glass, wood, ceramics. Do not apply on sensitive materials such as PVC, PS or on painted surfaces
- Low effect on the climate and no negative influence on the ozone layer (ozone-depleting potential: ODP = 0)
- Free of surfactants, halogenated and aromatic solvents











# **OKS 2681**

# Adhesive and Paint Remover, Spray

#### **Technical data**

	Standard	Conditions	Unit	Value
Main components				
basis				solvent mixture
Application related technical data				
flashing point			°C	88-92
colour				colourless
density (at 20°C)	DIN EN ISO 3838		g/cm³	0.86
Properties and approvals				
UFI				95J1-80W6-P00F-5GKQ

## **OKS Spezialschmierstoffe GmbH**

Ganghoferstraße 47 82216 Maisach

**4** +49 8142 3051 - 500

☑ info@oks-germany.com

★ www.oks-germany.com



The information in this publication reflects state-of-the-art technology, as well as extensive testing and experience. Due to the diversity of possible applications and technical realities, they can only serve as recommendations and are not arbitrarily transferable. Therefore, no obligations, liability or warranty claims can be derived from them. We only accept liability for the suitability of our products for particular purposes, and for certain properties of our products, in the event that we have accepted such liability in writing in the individual case. Any case of justified warranty claims shall be limited to the delivery of replacement goods free of defects, in the event that this subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular the liability for consequential injuries or damage, shall always be excluded. Prior to use, the customer must conduct its own testing to prove suitability. The data are subject to change for the sake of progress. © = Registered trademark

**Product restricted to professional users.** Safety data sheet available for download at www.oks-germany.com Our Customer and Technical service will be pleased to help should you have any further questions.





