


# OKS 3730

## Gear Oil, ISO VG 460



### Description

Fully synthetic oil of the ISO VG class 460 for lubricating gears and other machine elements in the food processing technology.

### Applications

- Lubrication of closed toothed gearing
- Liquid lubrication of chains, joints, guides, fittings
- Suitable for immersion-bath, immersion-bath circulation and injection lubrication

### Branches

- Catering equipment and food processing technology
- Shipbuilding and marine technology
- Plant and machine (tool) engineering
- Logistics
- Glass and foundry industry
- Municipal services
- Chemical industry
- Rail vehicle technology
- Rubber and plastic processing
- Paper and packaging industry
- Iron and steel industry

### Advantages and benefits

- NSF H1 registered
- Good oxidation and ageing stability through optimal additives
- Cold and hot water resistant
- Resistant to water steam, disinfectants and cleaning agents
- Wide operating temperature range
- Shear-stable and low-foaming
- Good wear protection
- Good corrosion protection
- Long economic operating times
- MOSH/MOAH-free (as per recipe)

### Application tips

Clean the lubricating point thoroughly for optimal effect. Before filling gears for first time, remove anti-corrosion agent. Fill the gears so that the immersing teeth transport the lubricant reliably. Apply a sufficient amount of lubricant with a brush, drip oiler, by immersion or using a suitable automatic lubrication system. Observe the gear and machine manufacturer's instructions. Assess the lubrication frequency and quantity on basis of service conditions. Only mix with suitable lubricants.

### Packaging

- 5 l Canister
- 25 l Canister
- 200 l Drum



# OKS 3730

## Gear Oil, ISO VG 460

### Technical data

|   | Standard          | Conditions          | Unit               | Value                                   |
|---|-------------------|---------------------|--------------------|---|
| <b>Main components</b>                    |                   |                     |                    |   |
| base oil                                  |                   |                     |                    | synthetic oil mixture                   |
| <b>Application related technical data</b> |                   |                     |                    |   |
| marking                                   | DIN 51 502        | DIN 51 825          |                    | CLP HC 460                              |
| viscosity at (40°C)                       | DIN 51 562-1      |                     | mm <sup>2</sup> /s | 460                                     |
| viscosity at (100°C)                      | DIN 51 562-1      |                     | mm <sup>2</sup> /s | 47                                      |
| viscosity index                           | DIN ISO 2909      |                     |                    | approx. 150                             |
| viscosity class                           | DIN ISO 3448      | DIN 51 562-1, 40°C  | ISO VG             | 460                                     |
| pour point                                | DIN ISO 3016      | 3°C step            | °C                 | < -30                                   |
| flashing point                            | DIN ISO 2592      | > 79, open crucible | °C                 | > 200                                   |
| lower operating temperature               |                   |                     | °C                 | -30                                     |
| upper operating temperature               |                   |                     | °C                 | 120                                     |
| colour                                    |                   |                     |                    | colourless-light yellow                 |
| density (at 20°C)                         | DIN EN ISO 3838   |                     | g/cm <sup>3</sup>  | 0.86                                    |
| SKF-EMCOR Copper                          | DIN EN ISO 2160   | 24h, 100°C          | corr. degree       | 1-100                                   |
| FZG wear protection test                  | DIN ISO 14 635-01 | A/8,3/90            | power level        | > 12                                    |
| <b>Properties and approvals</b>           |                   |                     |                    |   |
| approval for food processing technology   |                   |                     |                    | <a href="#">NSF H1, Reg.-Nr. 135753</a> |

### OKS Spezialschmierstoffe GmbH

Ganghoferstraße 47  
 82216 Maisach  
 +49 8142 3051 - 500  
 info@oks-germany.com  
 www.oks-germany.com



The information in this publication reflects state-of-the-art technology, as well as extensive testing and experience. Due to the diversity of possible applications and technical realities, they can only serve as recommendations and are not arbitrarily transferable. Therefore, no obligations, liability or warranty claims can be derived from them. We only accept liability for the suitability of our products for particular purposes, and for certain properties of our products, in the event that we have accepted such liability in writing in the individual case. Any case of justified warranty claims shall be limited to the delivery of replacement goods free of defects, in the event that this subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular the liability for consequential injuries or damage, shall always be excluded. Prior to use, the customer must conduct its own testing to prove suitability. The data are subject to change for the sake of progress. ® = Registered trademark  
**Product restricted to professional users.** Safety data sheet available for download at [www.oks-germany.com](http://www.oks-germany.com)  
 Our Customer and Technical service will be pleased to help should you have any further questions.

