




## OKS 1600

### Weld Parting Agent, water-based concentrate



#### Description

Environmentally friendly, water-based parting agent for arc and inert-gas arc welding.

#### Applications

- Protection of surfaces of all kinds and welding nozzles for oxyacetylene gas and inert-gas arc welding
- Prevents baking on of weld splatters on surface and welding nozzle

#### Branches

- Logistics
- Iron and steel industry
- Shipbuilding and marine technology
- Maintenance and servicing
- Chemical industry
- Glass and foundry industry
- Paper and packaging industry
- Rail vehicle technology
- Rubber and plastic processing
- Plant and machine (tool) engineering
- Municipal services

#### Advantages and benefits

- Later painting over, metallising and printing following prior cleaning easily possible
- Environmentally friendly, non-combustible
- Silicone-free
- Can be removed residue-free
- OKS 1600 is suitable for use with the OKS Airspray system
- Also available as spray version OKS 1601

#### Application tips

For optimum effect, clean the surfaces. Best way is to clean mechanically first and then with OKS 2610/OKS 2611 universal cleaner. Dilution of OKS 1600 with water in a ratio of up to 1:5 depending on the application possible. Spray on in an even, thin layer onto surfaces endangered by weld splatters. Protect packaging against frost.

#### Packaging

- 5 l Canister
- 25 l Canister

OKS 1600

Weld Parting Agent, water-based concentrate

Technical data

|                                    | Standard        | Conditions | Unit  | Value               |
|------------------------------------|-----------------|------------|-------|---------------------|
| Main components                    |                 |            |       |                     |
| base oil                           |                 |            |       | water               |
| additives                          |                 |            |       | natural greasy oil  |
| Application related technical data |                 |            |       |                     |
| colour                             |                 |            |       | whitish-transparent |
| density (at 20°C)                  | DIN EN ISO 3838 |            | g/cm³ | 0.98                |
| Properties and approvals           |                 |            |       |                     |
| UFI                                |                 |            |       |                     |

OKS Spezialschmierstoffe GmbH  
Ganghoferstraße 47  
82216 Maisach  
+49 8142 3051 - 500  
info@oks-germany.com  
www.oks-germany.com

a brand of  
 FREUDENBERG

The information in this publication reflects state-of-the-art technology, as well as extensive testing and experience. Due to the diversity of possible applications and technical realities, they can only serve as recommendations and are not arbitrarily transferable. Therefore, no obligations, liability or warranty claims can be derived from them. We only accept liability for the suitability of our products for particular purposes, and for certain properties of our products, in the event that we have accepted such liability in writing in the individual case. Any case of justified warranty claims shall be limited to the delivery of replacement goods free of defects, in the event that this subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular the liability for consequential injuries or damage, shall always be excluded. Prior to use, the customer must conduct its own testing to prove suitability. The data are subject to change for the sake of progress. ® = Registered trademark  
**Product restricted to professional users.** Safety data sheet available for download at [www.oks-germany.com](http://www.oks-germany.com)  
Our Customer and Technical service will be pleased to help should you have any further questions.