OKS 2611

Version	Revision Date:	Date of last issue: 31.07.2026	Print Date:
5.1	08.10.2026	Date of first issue: 28.06.2016	08.10.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 2611

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Detergent
Cleaning agent / Cleaner

Recommended restrictions on use : Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH
Ganghoferstr. 47
82216 Maisach
Germany
Tel.: +49 8142 3051-500
info@oks-germany.com

E-mail address of person responsible for the SDS : mcm@oks-germany.com

National contact : Klüber Lubrication Deutschland GmbH & Co. KG
Geisenhausenerstraße 7
81379 München
Germany
Tel.: +49 (0) 89 7876 0
customer.service.de@klueber.com

1.4 Emergency telephone number

Emergency telephone number : +49 8142 3051 517

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure, Category 2, Central nervous system	H373: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs (Central nervous system) through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe mist.

Response:

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331	Do NOT induce vomiting.

Storage:

P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:
propan-2-ol

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Propellant
Solvent mixture

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
propan-2-ol	67-63-0 200-661-7 603-117-00-0 02-2119457558-25-XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)		>= 20 - < 30
Hydrocarbons, C9-		Flam. Liq. 3; H226		>= 25 - < 30

OKS 2611

Version	Revision Date:	Date of last issue: 31.07.2026	Print Date:
5.1	08.10.2026	Date of first issue: 28.06.2016	08.10.2026

C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	927-241-2 01-2119471843-32-XXXX	STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412 EUH066	Note P	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	921-024-6 01-2119475514-35-XXXX	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411		>= 20 - < 25
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49-XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066		>= 10 - < 20
n-hexane	110-54-3 203-777-6 601-037-00-0 01-2119480412-44-XXXX	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361f STOT SE 3; H336 (Central nervous system) STOT RE 1; H372 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	**, ***	>= 1 - < 2,5
n-hexane	110-54-3 203-777-6 601-037-00-0	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361f STOT SE 3; H336 (Central nervous system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	**, ***	>= 0,25 - < 1
Substances with a workplace exposure limit :				
carbon dioxide	124-38-9 204-696-9	Press. Gas Compr. Gas; H280		>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Call a physician or poison control centre immediately.
Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact : Take off all contaminated clothing immediately.
Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
Wash off immediately with plenty of water.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
Get medical attention immediately.

If swallowed : Move the victim to fresh air.
If accidentally swallowed obtain immediate medical attention.
Keep respiratory tract clear.
Do NOT induce vomiting.
Rinse mouth with water.
Aspiration hazard if swallowed - can enter lungs and cause damage.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Aspiration may cause pulmonary oedema and pneumonitis.

Inhalation may provoke the following symptoms:
Unconsciousness
Dizziness
Drowsiness
Headache
Nausea
Tiredness

Risks : May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Central nervous system depression
Risk of product entering the lungs on vomiting after ingestion.
Health injuries may be delayed.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Fire Hazard
Do not let product enter drains.
Contains gas under pressure; may explode if heated.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion products : Carbon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Ensure adequate ventilation.
Remove all sources of ignition.

Do not breathe vapours or spray mist.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Refer to protective measures listed in sections 7 and 8.
Only qualified personnel equipped with suitable protective equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.
Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not use in areas without adequate ventilation.
Do not breathe vapours or spray mist.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin and eyes.
For personal protection see section 8.
Keep away from fire, sparks and heated surfaces.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
Do not get in eyes or mouth or on skin.
Do not get on skin or clothing.
Do not ingest.
Do not use sparking tools.
These safety instructions also apply to empty packaging which may still contain product residues.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular national regulations.

Storage class (TRGS 510) : 2B, Aerosol cans and lighters

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
propan-2-ol	67-63-0	MAK	200 ppm 500 mg/m3	DE DFG MAK (2023-07-01)
	Peak-limit: excursion factor (category): 2; II			
	Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
		AGW	200 ppm 500 mg/m3	DE TRGS 900 (2006-01-01)
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not Assigned	MAK	50 ppm 300 mg/m3	DE DFG MAK (2023-07-01)
	Peak-limit: excursion factor (category): 2; II			
	Further information: Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C			
		AGW	300 mg/m3	DE TRGS 900 (2017-11-30)
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Group exposure limit for hydrocarbon solvent mixtures			
acetone	67-64-1	TWA	500 ppm 1.210 mg/m3	2000/39/EC (1991-07-05)

OKS 2611

Version	Revision Date:	Date of last issue: 31.07.2026	Print Date:
5.1	08.10.2026	Date of first issue: 28.06.2016	08.10.2026

	Further information: Indicative			
		MAK	500 ppm 1.200 mg/m3	DE DFG MAK (2024-07-01)
	Peak-limit: excursion factor (category): 2; I			
	Further information: According to currently available information damage to the embryo or foetus cannot be excluded after exposure to concentrations at the level of the MAK and BAT values			
		AGW	500 ppm 1.200 mg/m3	DE TRGS 900 (2015-03-02)
	Peak-limit: excursion factor (category): 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
carbon dioxide	124-38-9	TWA	5.000 ppm 9.000 mg/m3	2006/15/EC (2006-02-09)
	Further information: Indicative			
		MAK	5.000 ppm 9.100 mg/m3	DE DFG MAK (2023-07-01)
	Peak-limit: excursion factor (category): 2; II			
		AGW	5.000 ppm 9.100 mg/m3	DE TRGS 900 (2006-01-01)
	Peak-limit: excursion factor (category): 2;(II)			
n-hexane	110-54-3	TWA	20 ppm 72 mg/m3	2006/15/EC (2006-02-09)
	Further information: Indicative			
		MAK	50 ppm 180 mg/m3	DE DFG MAK (2023-07-01)
	Peak-limit: excursion factor (category): 8; II			
	Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
		AGW	50 ppm 180 mg/m3	DE TRGS 900 (2010-08-04)
	Peak-limit: excursion factor (category): 8;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
n-hexane	110-54-3	TWA	20 ppm 72 mg/m3	2006/15/EC (2006-02-09)
	Further information: Indicative			
		MAK	50 ppm 180 mg/m3	DE DFG MAK (2023-07-01)
	Peak-limit: excursion factor (category): 8; II			
	Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
		AGW	50 ppm 180 mg/m3	DE TRGS 900 (2010-08-04)
	Peak-limit: excursion factor (category): 8;(II)			
	Further information: When there is compliance with the OEL and biological			

	tolerance values, there is no risk of harming the unborn child

Further occupational exposure limits

Description	Value type	Control parameters	Basis
Calculated according to TRGS 900 RCP-method	AGW	300 mg/m3	DE TRGS 900

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
propan-2-ol	67-63-0	Acetone: 25 mg/l (Blood)	Immediately after exposition or after working hours	DE DFG BAT (2023-07-01)
		Acetone: 25 mg/l (Urine)	Immediately after exposition or after working hours	DE DFG BAT (2023-07-01)
		Acetone: 25 mg/l (Blood)	Immediately after exposure or after working hours	TRGS 903 (2013-04-04)
		Acetone: 25 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903 (2013-04-04)
acetone	67-64-1	Acetone: 50 mg/l (Urine)	Immediately after exposition or after working hours	DE DFG BAT (2023-07-01)
		Acetone: 50 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903 (2023-06-12)
n-hexane	110-54-3	2,5-hexanedione plus 4,5-dihydroxy-2-hexanone: 5 mg/l (Urine)	end of shift, for long-term exposures after several previous shifts, Immediately after exposition or after working hours	DE DFG BAT (2023-07-01)
		2,5-hexanedione plus 4,5-dihydroxy-2-hexanone: 5 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903 (2013-09-19)
n-hexane	110-54-3	2,5-hexanedione plus 4,5-dihydroxy-2-hexanone: 5 mg/l (Urine)	end of shift, for long-term exposures after several previous shifts, Immediately after exposition or after working hours	DE DFG BAT (2023-07-01)
		2,5-hexanedione plus 4,5-dihydroxy-2-hexanone: 5 mg/l	Immediately after exposure or after working hours	TRGS 903 (2013-09-19)

		(Urine)		

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Workers	Skin contact	Long-term systemic effects	773 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	2035 mg/m3
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	Workers	Inhalation	Long-term systemic effects	871 mg/m3
	Workers	Skin contact	Long-term systemic effects	77 mg/kg bw/day
acetone	Workers	Inhalation	Long-term systemic effects	1210 mg/m3
	Workers	Skin contact	Long-term systemic effects	186 mg/kg
propan-2-ol	Workers	Inhalation	Long-term systemic effects	500 mg/m3
	Workers	Skin contact	Long-term systemic effects	888 mg/kg
n-hexane	Workers	Inhalation	Long-term systemic effects	75 mg/m3
	Workers	Skin contact	Long-term systemic effects	11 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
acetone	Fresh water	10,6 mg/l
	Marine water	1,06 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	30,4 mg/kg
	Marine sediment	3,04 mg/kg
	Soil	29,5 mg/kg

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye/face protection : Safety glasses with side-shields

Hand protection
- Material : butyl-rubber
- Break through time : > 10 min
- Protective index : Class 1

Remarks	:	Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case. The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.
Skin and body protection	:	Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Filter type	:	Recommended Filter type: Organic gas and low boiling vapour type (AX)
Protective measures	:	The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Environmental exposure controls

Air	:	Should not be released into the environment.
Soil	:	Do not allow contact with soil, surface or ground water. The product should not be allowed to enter drains, water courses or the soil.
Water	:	Do not allow contact with soil, surface or ground water. The product should not be allowed to enter drains, water courses or the soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	aerosol
Colour	:	colourless
Odour	:	solvent-like
Odour Threshold	:	No data available

Melting point/ range	:	No data available
Boiling point/boiling range	:	56 °C (1.013 hPa)
Flammability	:	Flammability (solid, gas): Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	13 %(V)
Lower explosion limit / Lower flammability limit	:	0,6 %(V)
Flash point	:	-18 °C Method: Abel-Pensky
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
pH	:	Not applicable substance/mixture is non-soluble (in water)
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	< 20,5 mm2/s (40 °C)
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available

Vapour pressure	:	233 hPa (20 °C)
Relative density	:	0,7533 (20 °C) Reference substance: Water The value is calculated
Density	:	0,75 g/cm3 (20 °C)
Bulk density	:	No data available
Relative vapour density	:	No data available

9.2 Other information

Explosives	:	Not explosive
Oxidizing properties	:	No data available
Self-ignition	:	not auto-flammable
Metal corrosion rate	:	Not corrosive to metals
Evaporation rate	:	No data available
Sublimation point	:	No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

Strong sunlight for prolonged periods.
Risk of receptacle bursting.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.

Symptoms: Inhalation may provoke the following symptoms:, Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central nervous system depression

Acute dermal toxicity : Symptoms: Redness, Local irritation

Components:

propan-2-ol:

Acute oral toxicity : LD50 Oral (Rat): 5.840 mg/kg

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): > 5.840 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 25,2 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,8 g/kg
Assessment: The substance or mixture has no acute dermal toxicity

acetone:

Acute oral toxicity : LD50 Oral (Rat): 5.800 mg/kg

n-hexane:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 259,35 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 3.350 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

n-hexane:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 259,35 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : This information is not available.

Components:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Result : Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit
Assessment : Irritating to skin.
Method : OECD Test Guideline 404
Result : Irritating to skin.

acetone:

Result : Repeated exposure may cause skin dryness or cracking.

n-hexane:

Species : Rabbit
Assessment : Irritating to skin.
Method : OECD Test Guideline 404
Result : Irritating to skin.

n-hexane:

Species : Rabbit
Assessment : Irritating to skin.
Method : OECD Test Guideline 404
Result : Irritating to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : This information is not available.

Components:

propan-2-ol:

Species : Rabbit
Result : Eye irritation

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit
Assessment : No eye irritation
Result : No eye irritation

acetone:

Species : Rabbit
Result : Eye irritation

n-hexane:

Species	:	Rabbit
Assessment	:	No eye irritation
Method	:	OECD Test Guideline 405
Result	:	No eye irritation

n-hexane:

Species	:	Rabbit
Assessment	:	No eye irritation
Method	:	OECD Test Guideline 405
Result	:	No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Product:

Remarks	:	This information is not available.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Test Type	:	Maximisation Test
Exposure routes	:	Dermal
Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.
Method	:	OECD Test Guideline 406
Result	:	Did not cause sensitisation on laboratory animals.

n-hexane:

Species	:	Mouse
Assessment	:	Does not cause skin sensitisation.
Method	:	OECD Test Guideline 429
Result	:	Does not cause skin sensitisation.

n-hexane:

Species	:	Mouse
Assessment	:	Does not cause skin sensitisation.
Result	:	Does not cause skin sensitisation.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Test system: Rodent cell line
Method: OECD Test Guideline 473
Result: negative

n-hexane:

Germ cell mutagenicity-Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Carcinogenicity

Based on available data, the classification criteria are not met.

Product:

Remarks : No data available

Components:

n-hexane:

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

Reproductive toxicity

Based on available data, the classification criteria are not met.

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

Components:

n-hexane:

Reproductive toxicity - Assessment : - Fertility -
Suspected human reproductive toxicant

n-hexane:

Reproductive toxicity - Assessment : - Fertility -

Suspected human reproductive toxicant

STOT - single exposure

May cause drowsiness or dizziness.

Product:

Remarks : No data available

Components:

propan-2-ol:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

acetone:

Exposure routes : Inhalation
Assessment : May cause drowsiness or dizziness.

n-hexane:

Exposure routes : Inhalation
Target Organs : Central nervous system
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

n-hexane:

Exposure routes : Inhalation
Target Organs : Central nervous system
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

May cause damage to organs (Central nervous system) through prolonged or repeated exposure.

Product:

Remarks : No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Exposure routes : inhalation (vapour)
Assessment : No significant health effects observed in animals at

concentrations of 1 mg/l/6h/d or less.

n-hexane:

Target Organs	:	Central nervous system
Assessment	:	The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

n-hexane:

Exposure routes	:	Inhalation
Target Organs	:	Central nervous system
Assessment	:	The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Repeated dose toxicity

Product:

Remarks	:	This information is not available.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May be fatal if swallowed and enters airways.

Components:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

May be fatal if swallowed and enters airways.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

May be fatal if swallowed and enters airways.

n-hexane:

May be fatal if swallowed and enters airways.

n-hexane:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Based on available data, the classification criteria are not met.

Product:

Assessment	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according

to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 10 - < 30 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 22 - 46 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l
Exposure time: 72 h

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 22 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): 3 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 GLP: yes
Toxicity to algae/aquatic plants	:	EbC50 (Pseudokirchneriella subcapitata (green algae)): 26 mg/l Exposure time: 72 h Method: OECD Test Guideline 201

Ecotoxicology Assessment

Acute aquatic toxicity	:	Toxic to aquatic life.
Chronic aquatic toxicity	:	Toxic to aquatic life with long lasting effects.

n-hexane:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 12,51 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 21,85 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): 9,285 mg/l Exposure time: 72 h

n-hexane:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 12,51 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 21,85 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): 9,285 mg/l Exposure time: 72 h

12.2 Persistence and degradability

Product:

Biodegradability	:	Remarks: No data available
Physico-chemical removability	:	Remarks: No data available

Components:

propan-2-ol:

Biodegradability : Result: Readily biodegradable.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Biodegradability : Result: rapidly biodegradable

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Biodegradability : Result: Readily biodegradable.

acetone:

Biodegradability : Result: Readily biodegradable.

n-hexane:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: rapidly biodegradable
Biodegradation: 98 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

n-hexane:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: rapidly biodegradable
Biodegradation: 21 %
Exposure time: 28 d
GLP: yes

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

propan-2-ol:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 0,05

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Bioaccumulation : Remarks: Not applicable

Partition coefficient: n-octanol/water : Remarks: No data available

acetone:

Bioaccumulation : Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 0,2

n-hexane:

Bioaccumulation : Bioconcentration factor (BCF): 501,19

Partition coefficient: n-octanol/water : log Pow: 3,42 - 5,8 (20 °C)
pH: 7

n-hexane:

Bioaccumulation : Bioconcentration factor (BCF): 501,19

Partition coefficient: n-octanol/water : log Pow: 4 (20 °C)
pH: 7

carbon dioxide:

Partition coefficient: n-octanol/water : log Pow: 0,83

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Offer empty spray cans to an established disposal company.
Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied
16 05 04*, gases in pressure containers (including halons) containing hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1950

ADR : UN 1950

RID : UN 1950

IMDG : UN 1950

IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS

ADR : AEROSOLS

RID	:	AEROSOLS
IMDG	:	AEROSOLS
IATA	:	Aerosols, flammable

14.3 Transport hazard class(es)

		Class	Subsidiary risks
ADN	:	2	2.1
ADR	:	2	2.1
RID	:	2	2.1
IMDG	:	2.1	
IATA	:	2.1	

14.4 Packing group

ADN

Packing group	:	Not assigned by regulation
Classification Code	:	5F
Labels	:	2.1

ADR

Packing group	:	Not assigned by regulation
Classification Code	:	5F
Labels	:	2.1
Tunnel restriction code	:	(D)

RID

Packing group	:	Not assigned by regulation
Classification Code	:	5F
Hazard Identification Number	:	23
Labels	:	2.1

IMDG

Packing group	:	Not assigned by regulation
Labels	:	2.1
EmS Code	:	F-D, S-U

IATA (Cargo)

Packing instruction (cargo aircraft)	:	203
Packing instruction (LQ)	:	Y203
Packing group	:	Not assigned by regulation
Labels	:	Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft)	:	203
Packing instruction (LQ)	:	Y203
Packing group	:	Not assigned by regulation
Labels	:	Flammable Gas

14.5 Environmental hazards

ADN
Environmentally hazardous : no

ADR
Environmentally hazardous : no

RID
Environmentally hazardous : no

IMDG
Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries must be considered:: Number on list 40 This substance/mixture shall not be used in aerosol dispensers intended for supply to the general public for entertainment and decorative purposes. Number on list 75 If you intend to use this product as tattoo ink, please contact your vendor.
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). (EU SVHC)	:	n-hexane
Regulation (EU) No 2024/590 on substances that deplete the ozone layer (EC 2024/590)	:	Not applicable

OKS 2611

Version	Revision Date:	Date of last issue: 31.07.2026	Print Date:
5.1	08.10.2026	Date of first issue: 28.06.2016	08.10.2026

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) (EU POP)	:	Not applicable
Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals (EU PIC)	:	Not applicable
REACH - List of substances subject to authorisation (Annex XIV) (EU. REACH-Annex XIV)	:	Not applicable
Regulation (EU) 2019/1148 on the marketing and use of explosives precursors This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.		acetone (ANNEX II);
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	P3b	FLAMMABLE AEROSOLS

Water hazard class (Germany)	:	WGK 2 obviously hazardous to water Classification according to AwSV, Annex 1 (5.2)
TA Luft List (Germany)	:	5.2.5: Organic Substances: Class 1: 1,95 %
Volatile organic compounds	:	Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 96,39 %
Regulation (EC) No. 648/2004, as amended	:	Ingredients >= 30%: Aliphatic hydrocarbons

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

H225	:	Highly flammable liquid and vapour.
H226	:	Flammable liquid and vapour.
H280	:	Contains gas under pressure; may explode if heated.
H304	:	May be fatal if swallowed and enters airways.
H315	:	Causes skin irritation.
H319	:	Causes serious eye irritation.
H336	:	May cause drowsiness or dizziness.
H361f	:	Suspected of damaging fertility.
H372	:	Causes damage to organs through prolonged or repeated exposure.
H373	:	May cause damage to organs through prolonged or repeated exposure.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.
EUH066	:	Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

**	:	Route of exposure cannot be excluded: For certain hazard classes, e.g. STOT, the route of exposure should be indicated in the hazard statement only if it is conclusively proven that no other route of exposure can cause the hazard in accordance to the criteria in Annex I. Under Directive 67/548/EEC the route of exposure was indicated for classifications with R48 when there was data justifying the classification for this route of exposure. The classification under 67/548/EEC indicating the route of exposure has been translated into the corresponding class and category according to this Regulation, but with a general hazard statement not specifying the route of exposure as the necessary information is not available.
***	:	Hazard statements for reproductive toxicity: Hazard statements H360 and H361 indicate a general concern for effects on fertility and/or development: 'May damage/Suspected of damaging fertility or the unborn child'. According to the criteria, the general hazard statement can be replaced by the hazard statement indicating the specific effect of concern in accordance with Section 1.1.2.1.2. When the

		other differentiation is not mentioned, this is due to evidence proving no such effect, inconclusive data or no data and the obligations in Article 4(3) shall apply for that differentiation. In order not to lose information from the harmonised classifications for fertility and developmental effects under Directive 67/548/EEC, the classifications have been translated only for those effects classified under that Directive
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Note P	:	The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply.
Press. Gas	:	Gases under pressure
Repr.	:	Reproductive toxicity
Skin Irrit.	:	Skin irritation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC	:	Europe. Indicative occupational exposure limit values
DE DFG BAT	:	Germany. MAK BAT Annex XIII
DE DFG MAK	:	Germany. MAK BAT Annex IIa
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
TRGS 903	:	TRGS 903 - Biological limit values
2000/39/EC / TWA	:	Limit Value - eight hours
2006/15/EC / TWA	:	Limit Value - eight hours
DE DFG MAK / MAK	:	MAK value
DE TRGS 900 / AGW	:	Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; BGW - Biological Limit Values; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International

Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); LSPN - List of Hazardous Notified Substances (Chile); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:		**Classification procedure:**
Aerosol 1	H222, H229	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method
STOT RE 2	H373	Calculation method
Asp. Tox. 1	H304	Based on product data or assessment
Aquatic Chronic 3	H412	Calculation method

|| Relevant changes compared to the last edition are highlighted at the left margin. This version replaces all previous editions.

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.

OKS 2611

Version	Revision Date:	Date of last issue: 31.07.2026	Print Date:
5.1	08.10.2026	Date of first issue: 28.06.2016	08.10.2026

OKS 2611

Version	Revision Date:	Date of last issue: 31.07.2026	Print Date:
5.1	08.10.2026	Date of first issue: 28.06.2016	08.10.2026

Ingredients (Regulation (EC) No. 648/2004, as amended)

propan-2-ol
PARAFFINUM LIQUIDUM
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
acetone
CARBON DIOXIDE
HEXANE
n-hexane

https://ec.europa.eu/growth/tools-databases/cosing/index.cfm?fuseaction=search.simple