according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE



OKS 2671

Version Revision Date: Date of last issue: 03.03.2022 Print Date: 1.4 09.07.2025 Date of first issue: 23.06.2016 09.07.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 2671

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Cleaning agent / Cleaner

Substance/Mixture

Recommended restrictions

on use

Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

82216 Maisach-Gernlinden

Deutschland

Tel.: +49 8142 3051 500 Fax: +49 8142 3051 599 info@oks-germany.com

E-mail address of person responsible for the SDS

mcm@oks-germany.com

National contact

1.4 Emergency telephone number

Emergency telephone

: +49 8142 3051 517

number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE



OKS 2671

VersionRevision Date:Date of last issue: 03.03.2022Print Date:1.409.07.2025Date of first issue: 23.06.201609.07.2025

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters

airways.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms







Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H304 May be fatal if swallowed and enters

airways.

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Supplemental Hazard

Statements

EUH066

Repeated exposure may cause skin

dryness or cracking.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use.

Response:

P301 + P310 IF SWALLOWED: Immediately call a

POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

propan-2-ol

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics

ethyl acetate



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE



OKS 2671

 Version
 Revision Date:
 Date of last issue: 03.03.2022
 Print Date: 09.07.2025

 1.4
 09.07.2025
 Date of first issue: 23.06.2016
 09.07.2025

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Active substance with propellant

Solvent mixture

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
propan-2-ol	67-63-0 200-661-7 603-117-00-0 02-2119457558-25- XXXX	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336		>= 50 - < 70
Hydrocarbons, C11- C12, isoalkanes, < 2% aromatics	918-167-1 01-2119472146-39- XXXX	Flam. Liq.3; H226 Asp. Tox.1; H304; EUH066	Note P	>= 20 - < 30
ethyl acetate	141-78-6 205-500-4 607-022-00-5 01-21119475103-46-	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336; EUH066		>= 1 - < 10



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE



OKS 2671

 Version
 Revision Date:
 Date of last issue: 03.03.2022
 Print Date: 09.07.2025

 1.4
 09.07.2025
 Date of first issue: 23.06.2016
 09.07.2025

	xxxx		
Substances with a work	place exposure limit:		
carbon dioxide	124-38-9 204-696-9	Press. GasCompr. Gas; H280	>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Call a physician or poison control centre immediately.

Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial

respiration.

In case of skin contact : Take off all contaminated clothing immediately.

Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes. Seek medical advice.

If swallowed : Move the victim to fresh air.

If accidentally swallowed obtain immediate medical attention.

Keep respiratory tract clear. Do NOT induce vomiting. Rinse mouth with water.

Aspiration hazard if swallowed - can enter lungs and cause

damage.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:

Unconsciousness

Dizziness



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE



OKS 2671

Version Revision Date: Date of last issue: 03.03.2022 Print Date: 1.4 09.07.2025 Date of first issue: 23.06.2016 09.07.2025

Drowsiness Headache Nausea Tiredness

Skin contact may provoke the following symptoms:

Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Risks : May be fatal if swallowed and enters airways.

Causes serious eye irritation. May cause drowsiness or dizziness.

Repeated exposure may cause skin dryness or cracking.

Central nervous system depression Can be absorbed through skin.

Risk of product entering the lungs on vomiting after ingestion.

Health injuries may be delayed.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

Fire Hazard

Do not let product enter drains.

Contains gas under pressure; may explode if heated. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion

products

Carbon oxides

5.3 Advice for firefighters

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE



OKS 2671

Version Revision Date: Date of last issue: 03.03.2022 Print Date: 1.4 09.07.2025 Date of first issue: 23.06.2016 09.07.2025

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Ensure adequate ventilation. Remove all sources of ignition. Do not breathe vapours or spray mist.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8. Only qualified personnel equipped with suitable protective

equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.

Keep away from fire, sparks and heated surfaces. Smoking, eating and drinking should be prohibited in the



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE



OKS 2671

Version Revision Date: Date of last issue: 03.03.2022 Print Date: 1.4 09.07.2025 Date of first issue: 23.06.2016 09.07.2025

application area.

Wash hands and face before breaks and immediately after

handling the product.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest.

Do not use sparking tools.

These safety instructions also apply to empty packaging which

may still contain product residues.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or

burn, even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular

national regulations.

Storage class (TRGS 510) : 2B, Aerosol cans and lighters

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
propan-2-ol	67-63-0	MAK	200 ppm 500 mg/m3	DE DFG MAK (2023-07-01)	
	Peak-limit: ex	Peak-limit: excursion factor (category): 2; II			
		Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
		AGW	200 ppm 500 mg/m3	DE TRGS 900 (2006-01-01)	
	Peak-limit: ex	Peak-limit: excursion factor (category): 2;(II)			
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE $\,$



OKS 2671

VersionRevision Date:Date of last issue: 03.03.2022Print Date:1.409.07.2025Date of first issue: 23.06.201609.07.2025

	1		1	1	
ethyl acetate	141-78-6	TWA	200 ppm	2017/164/EU	
			734 mg/m3	(2017-02-01)	
	Further inform	Further information: Indicative			
		STEL	400 ppm	2017/164/EU	
			1.468 mg/m3	(2017-02-01)	
	Further inforr	nation: Indicative	-		
		MAK	200 ppm	DE DFG MAK	
			750 mg/m3	(2023-07-01)	
	Peak-limit: ex	cursion factor (cated			
	Further inform	nation: Damage to th	e embryo or foetus is unlikel	y when the	
	MAK value o	MAK value or the BAT value is observed			
		200 ppm	DE TRGS		
			730 mg/m3	900	
				(2017-06-08)	
	Peak-limit: excursion factor (category): 2;(I)				
	Further inform	mation: When there is	s compliance with the OEL ar	nd biological	
	tolerance val	tolerance values, there is no risk of harming the unborn child			
carbon dioxide	124-38-9	TWA	5.000 ppm	2006/15/EC	
			9.000 mg/m3	(2006-02-09)	
	Further inform	mation: Indicative			
		MAK	5.000 ppm	DE DFG MAK	
			9.100 mg/m3	(2023-07-01)	
	Peak-limit: ex	Peak-limit: excursion factor (category): 2; II			
		AGW	5.000 ppm	DE TRGS	
			9.100 mg/m3	900	
				(2006-01-01)	
	Peak-limit: ex	Peak-limit: excursion factor (category): 2;(II)			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
propan-2-ol	67-63-0	Acetone: 25 mg/l (Blood)	Immediately after exposition or after working hours	DE DFG BAT (2023-07- 01)
		Acetone: 25 mg/l (Urine)	Immediately after exposition or after working hours	DE DFG BAT (2023-07- 01)
		Acetone: 25 mg/l (Blood)	Immediately after exposure or after working hours	TRGS 903 (2013-04- 04)
		Acetone: 25 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903 (2013-04- 04)

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
propan-2-ol	Workers	Inhalation	Long-term systemic effects	500 mg/m3



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE



OKS 2671

VersionRevision Date:Date of last issue: 03.03.2022Print Date:1.409.07.2025Date of first issue: 23.06.201609.07.2025

	Workers	Skin contact	Long-term systemic effects	888 mg/kg
Hydrocarbons, C11- C12, isoalkanes, < 2% aromatics	Workers	Inhalation	Acute systemic effects	1286,4 mg/m3
	Workers	Inhalation	Long-term local effects	837,5 mg/m3
ethyl acetate	Workers	Inhalation	Long-term systemic effects	734 mg/m3
	Workers	Skin contact	Long-term systemic effects	63 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
ethyl acetate	Fresh water	0,24 mg/l
	Marine water	0,024 mg/l
	Sewage treatment plant	650 mg/l
	Fresh water sediment	1,15 mg/kg
	Marine sediment	0,115 mg/kg
	Soil	0,148 mg/kg

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation. Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye/face protection : Safety glasses with side-shields

Hand protection

Material : butyl-rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each

case.

The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard

EN 374 derived from it.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE



OKS 2671

Version Revision Date: Date of last issue: 03.03.2022 Print Date: 1.4 09.07.2025 Date of first issue: 23.06.2016 09.07.2025

Short term only

Filter type : Filter type A-P

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

Environmental exposure controls

Air :

Should not be released into the environment.

Soil

Do not allow contact with soil, surface or ground water. The product should not be allowed to enter drains, water

courses or the soil.

Water :

Do not allow contact with soil, surface or ground water. The product should not be allowed to enter drains, water

courses or the soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : aerosol

Colour : colourless

Odour : characteristic

Odour Threshold : No data available

Melting point/ range : No data available

Boiling point/boiling range : -161 °C (1.013 hPa)

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

: 12 %(V)



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE



OKS 2671

Version Revision Date: Date of last issue: 03.03.2022 Print Date: 1.4 09.07.2025 Date of first issue: 23.06.2016 09.07.2025

Lower explosion limit / Lower

flammability limit

: 0,6 %(V)

Flash point : -15 °C

Method: Abel-Pensky

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable

substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : < 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 3.600 hPa (20 °C)

Relative density : 0,78 (20 °C)

Reference substance: Water The value is calculated

Density : 0,78 g/cm3

(20 °C)

Bulk density : No data available

Relative vapour density : No data available

9.2 Other information

Explosives : Not explosive

Oxidizing properties : No data available

Self-ignition : No data available

Metal corrosion rate : Not corrosive to metals

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE



OKS 2671

Version Revision Date: Date of last issue: 03.03.2022 Print Date: 1.4 09.07.2025 Date of first issue: 23.06.2016 09.07.2025

Evaporation rate : No data available

Sublimation point : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

Strong sunlight for prolonged periods.

Risk of receptacle bursting.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.

Symptoms: Inhalation may provoke the following symptoms:, Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central nervous system depression

Acute dermal toxicity : Remarks: Prolonged or repeated skin contact with liquid may

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE



OKS 2671

Version Revision Date: Date of last issue: 03.03.2022 Print Date: 1.4 09.07.2025 Date of first issue: 23.06.2016 09.07.2025

cause defatting resulting in drying, redness and possible

blistering.

Symptoms: Skin disorders

Components:

propan-2-ol:

Acute oral toxicity : LD50 Oral (Rat): 5.840 mg/kg

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Method: OECD Test Guideline 402

ethyl acetate:

Acute oral toxicity : LD50 (Rat): 5.620 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 20.000 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Product:

Remarks : This information is not available.

Components:

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Result : Repeated exposure may cause skin dryness or cracking.

ethyl acetate:

Species : Rabbit

Result : Mild skin irritation

Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : This information is not available.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE



OKS 2671

VersionRevision Date:Date of last issue: 03.03.2022Print Date:1.409.07.2025Date of first issue: 23.06.201609.07.2025

Components:

propan-2-ol:

Result : Irritating to eyes.

ethyl acetate:

Assessment : Irritating to eyes. Result : Irritating to eyes.

Respiratory or skin sensitisation

Skin sensitisation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Product:

Remarks : This information is not available.

Components:

ethyl acetate:

Test Type : Maximisation Test

Exposure routes : Dermal Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity

Based on available data, the classification criteria are not met.

Product:

Remarks : No data available

Reproductive toxicity

Based on available data, the classification criteria are not met.

Product:



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE



OKS 2671

VersionRevision Date:Date of last issue: 03.03.2022Print Date:1.409.07.2025Date of first issue: 23.06.201609.07.2025

Effects on fertility : Remarks: No data available

Effects on foetal : Remarks: No data available

development

STOT - single exposure

May cause drowsiness or dizziness.

Product:

Remarks : No data available

Components:

propan-2-ol:

Assessment : May cause drowsiness or dizziness.

ethyl acetate:

Exposure routes : Inhalation

Target Organs : Respiratory system

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Product:

Remarks : No data available

Components:

ethyl acetate:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May be fatal if swallowed and enters airways.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE



OKS 2671

VersionRevision Date:Date of last issue: 03.03.2022Print Date:1.409.07.2025Date of first issue: 23.06.201609.07.2025

Components:

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Further information

Product:

Remarks : Risks of irreversible effects after a single exposure.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: May cause long-term adverse effects in the aquatic

environment.

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms

Remarks: No data available

Components:

ethyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 212,5 mg/l

Exposure time: 96 h Test Type: static test

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 154 mg/l

Exposure time: 48 h

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE



OKS 2671

VersionRevision Date:Date of last issue: 03.03.2022Print Date:1.409.07.2025Date of first issue: 23.06.201609.07.2025

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 2.500

mg/l

Exposure time: 96 h

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical

removability

Remarks: No data available

Components:

propan-2-ol:

Biodegradability : Result: Readily biodegradable.

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Biodegradability : Result: Not readily biodegradable.

ethyl acetate:

Biodegradability : Result: rapidly biodegradable

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

propan-2-ol:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-

octanol/water

: log Pow: 0,05

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Bioaccumulation : Remarks: No data available

Partition coefficient: n-

octanol/water

Remarks: No data available

ethyl acetate:

Partition coefficient: n-

octanol/water

log Pow: 0,68 (25 °C)



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE



OKS 2671

Version Revision Date: Date of last issue: 03.03.2022 Print Date: 1.4 09.07.2025 Date of first issue: 23.06.2016 09.07.2025

carbon dioxide:

Partition coefficient: n-

octanol/water

log Pow: 0,83

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among : Ren

environmental compartments

Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological

information

May cause long lasting harmful effects to aquatic life.

Global warming potential

Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the United Nations Framework Convention on Climate Change (UNFCCC)

Components:

carbon dioxide:

20-year global warming potential: 1 100-year global warming potential: 1 500-year global warming potential: 1 Radiative efficiency: 0,000013 Wm2ppb



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE



OKS 2671

Version Revision Date: Date of last issue: 03.03.2022 Print Date: 1.4 09.07.2025 Date of first issue: 23.06.2016 09.07.2025

Further information: Major Greenhouse Gases

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Waste codes should be assigned by the user based on the

application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Offer empty spray cans to an established disposal company. Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied

16 05 04*, gases in pressure containers (including halons)

containing hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADN : 2

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE



OKS 2671

Version Revision Date: Date of last issue: 03.03.2022 Print Date: 1.4 09.07.2025 Date of first issue: 23.06.2016 09.07.2025

ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADN

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1

ADR

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

IMDG

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction : 203

(passenger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE



OKS 2671

Date of last issue: 03.03.2022 Version **Revision Date:** Print Date: 09.07.2025 Date of first issue: 23.06.2016 09.07.2025 1.4

IMDG

Marine pollutant no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 75: If you intend to use this product as tattoo ink, please

contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

(EU SVHC)

This product does not contain substances of very high concern

(Regulation (EC) No 1907/2006 (REACH), Article 57).

Regulation (EU) No 2024/590 on substances that

deplete the ozone layer

(EC 2024/590)

: Not applicable

Regulation (EU) 2019/1021 on persistent organic

pollutants (recast)

(EU POP)

: Not applicable

Regulation (EU) No 649/2012 of the European

Parliament and the Council concerning the export and

import of dangerous chemicals

(EU PIC)

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

(EU. REACH-Annex XIV)

: Not applicable



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE



OKS 2671

Version Revision Date: Date of last issue: 03.03.2022 Print Date: 1.4 09.07.2025 Date of first issue: 23.06.2016 09.07.2025

Regulation (EU) 2019/1148 on the marketing and use of

explosives precursors

Not applicable

P5c

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous

substances.

P3b FLAMMABLE AEROSOLS

Water hazard class

(Germany)

WGK 1 slightly hazardous to water

Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : 5.2.5: Organic Substances:

Class 1: 9,8 %

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and

livestock rearing emissions (integrated pollution prevention and

control)

Volatile organic compounds (VOC) content: 98 %

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour. H226 : Flammable liquid and vapour.

H280 : Contains gas under pressure; may explode if heated.

H304 : May be fatal if swallowed and enters airways.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE



OKS 2671

VersionRevision Date:Date of last issue: 03.03.2022Print Date:1.409.07.2025Date of first issue: 23.06.201609.07.2025

H319 : Causes serious eye irritation. H336 : May cause drowsiness or dizziness.

EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Note P : The harmonised classification as a carcinogen or mutagen

applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which

case a classification in accordance with Title II of this

Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-

P262-P301 + P310-P331 shall apply.

2006/15/EC : Europe. Indicative occupational exposure limit values

2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a

fourth list of indicative occupational exposure limit values

DE DFG BAT : Germany. MAK BAT Annex XIII
DE DFG MAK : Germany. MAK BAT Annex IIa

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

TRGS 903 : TRGS 903 - Biological limit values

2006/15/EC / TWA : Limit Value - eight hours 2017/164/EU / STEL : Short term exposure limit 2017/164/EU / TWA : Limit Value - eight hours

DE DFG MAK / MAK : MAK value

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials: bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - DE



OKS 2671

VersionRevision Date:Date of last issue: 03.03.2022Print Date:1.409.07.2025Date of first issue: 23.06.201609.07.2025

Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Aerosol 1	H222, H229	Based on product data or assessment
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method
Asp. Tox. 1	H304	Based on product data or assessment

|| Relevant changes compared to the last edition are highlighted at the left margin. This version replaces all previous editions.

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.

