


OKS 621 Rust Remover, Spray



Description

OKS 621 is a fast-acting rust dissolver for industry, workshop and hobby applications. The solvent contained in OKS 621 cools down the assembled parts/screws rapidly to -40°C . This results in a slight shrinkage of the affected profile. Capillary cracks in the corrosion layer appear, allowing an easier penetration of the creeping oil.

Applications

- High-performance rust remover for fast and nondestructive disassembly of extremely seized-up parts or bolts, e.g. for vehicles, agricultural or construction machinery, vessels and port facilities; also for all machinery in industry and trade

Branches

- Rail vehicle technology
- Plant and machine (tool) engineering
- Chemical industry
- Municipal services
- Shipbuilding and marine technology
- Iron and steel industry
- Rubber and plastic processing
- Maintenance and servicing
- Glass and foundry industry
- Logistics
- Paper and packaging industry

Advantages and benefits

- Contrary to a heat treatment of seized-up bolts OKS 621 does not cause heating damages in the environment
- No damages through overheating
- Resin and acid-free
- Without silicone

Application tips

Clean components from dirt. Shake well before use. Spray from a distance of 10–15 cm on to the parts/screws and allow OKS 621 to react for 1–2 min. Repeat treatment if necessary.

Packaging

- 400 ml Spray

OKS 621
Rust Remover, Spray

Technical data

	Standard	Conditions	Unit	Value
Main components				
base oil				solvent
base oil				mineral oil
Application related technical data				
lower operating temperature			°C	-10
upper operating temperature			°C	40
colour				light-coloured
density	DIN EN ISO 3838	at 20°C	g/cm ³	0.6
Properties and approvals				
UFI				81Y1-60ER-M00P-DQ0D

Klüber Lubrication München GmbH & Co. KG
 Geisenhausenerstraße 7 / 81379 München /
 Germany / phone +49 89 7876-0

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.