



# OKS 641

## Maintenance Oil, Spray

### Technical data

	Standard	Conditions	Unit	Value
<b>Main components</b>				
base oil				mineral oil
<b>Application related technical data</b>				
viscosity	DIN 51 562-1	40°C, with solvent	mm <sup>2</sup> /s	3
flashing point	DIN ISO 2592		°C	> 64
lower operating temperature			°C	-30
upper operating temperature		with solvent	°C	60
upper operating temperature		after evaporation of the solvent	°C	150
colour				brown
density	DIN EN ISO 3838	at 20°C	g/cm <sup>3</sup>	0.83
salt spray test	DIN EN ISO 9227		h	> 100
coefficient of friction SRV (μ)	analogue to DIN 51 834-2	ball, disk		0.11
wear SRV	analogue to DIN 51 834-2	ball, disk	mm <sup>3</sup>	0.003
<b>Properties and approvals</b>				
UFI				5DH1-Q0PM-X000-6EC4

**Klüber Lubrication München GmbH & Co. KG**  
Geisenhausenerstraße 7 / 81379 München /  
Germany / phone +49 89 7876-0

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.