



## OKS 621 Rust Remover, Spray



### Description

OKS 621 is a fast-acting rust dissolver for industry, workshop and hobby applications. The solvent contained in OKS 621 cools down the assembled parts/screws rapidly to  $-40^{\circ}\text{C}$ . This results in a slight shrinkage of the affected profile. Capillary cracks in the corrosion layer appear, allowing an easier penetration of the creeping oil.

### Applications

- High-performance rust remover for fast and nondestructive disassembly of extremely seized-up parts or bolts, e.g. for vehicles, agricultural or construction machinery, vessels and port facilities; also for all machinery in industry and trade

### Branches

- Rail vehicle technology
- Plant and machine (tool) engineering
- Chemical industry
- Municipal services
- Shipbuilding and marine technology
- Iron and steel industry
- Rubber and plastic processing
- Maintenance and servicing
- Glass and foundry industry
- Logistics
- Paper and packaging industry

### Advantages and benefits

- Contrary to a heat treatment of seized-up bolts OKS 621 does not cause heating damages in the environment
- No damages through overheating
- Resin and acid-free
- Without silicone

### Application tips

Clean components from dirt. Shake well before use. Spray from a distance of 10–15 cm on to the parts/screws and allow OKS 621 to react for 1–2 min. Repeat treatment if necessary.

### Packaging

- 400 ml Spray

OKS 621

Rust Remover, Spray

Technical data

|                                    | Standard        | Conditions | Unit  | Value               |
|------------------------------------|-----------------|------------|-------|---------------------|
| Main components                    |                 |            |       |                     |
| base oil                           |                 |            |       | solvent             |
| base oil                           |                 |            |       | mineral oil         |
| Application related technical data |                 |            |       |                     |
| lower operating temperature        |                 |            | °C    | -10                 |
| upper operating temperature        |                 |            | °C    | 40                  |
| colour                             |                 |            |       | light-coloured      |
| density (at 20°C)                  | DIN EN ISO 3838 |            | g/cm³ | 0.6                 |
| Properties and approvals           |                 |            |       |                     |
| UFI                                |                 |            |       | 81Y1-60ER-M00P-DQ0D |

OKS Spezialschmierstoffe GmbH

Ganghoferstraße 47

82216 Maisach

+49 8142 3051 - 500

info@oks-germany.com

www.oks-germany.com



The information in this publication reflects state-of-the-art technology, as well as extensive testing and experience. Due to the diversity of possible applications and technical realities, they can only serve as recommendations and are not arbitrarily transferable. Therefore, no obligations, liability or warranty claims can be derived from them. We only accept liability for the suitability of our products for particular purposes, and for certain properties of our products, in the event that we have accepted such liability in writing in the individual case. Any case of justified warranty claims shall be limited to the delivery of replacement goods free of defects, in the event that this subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular the liability for consequential injuries or damage, shall always be excluded. Prior to use, the customer must conduct its own testing to prove suitability. The data are subject to change for the sake of progress. ® = Registered trademark

**Product restricted to professional users.** Safety data sheet available for download at [www.oks-germany.com](http://www.oks-germany.com)

Our Customer and Technical service will be pleased to help should you have any further questions.