


OKS 2661

Fast Cleaner, Spray



Description

Residue-free evaporating fast cleaner (brake cleaner) for cleaning machine parts and material surfaces.

Applications

- Degreasing all surfaces and parts of non-absorbent materials, e.g. metals, ceramic or plastics and elastomers
- Cleaning of adhesive surfaces for coatings, paints or adhesives and sealants
- Cleaning of friction surfaces on which high friction forces are transmitted such as clutch and brake linings (brake cleaners)
- Removal of aged and gummy oil and grease residues, of residues of brake fluids and silicones, as well as of residues of simple coatings, adhesives and sealants

Advantages and benefits

- Highly effective due to actively cleaning substances
- Modern cleaner on a solvent base
- Fast and residue-free evaporation of the cleaner
- OKS 2660 is suitable for use with the OKS Airspray system
- Also available as Duo label

Branches

- Municipal services
- Logistics
- Plant and machine (tool) engineering
- Shipbuilding and marine technology
- Glass and foundry industry
- Rail vehicle technology
- Rubber and plastic processing
- Paper and packaging industry
- Iron and steel industry
- Maintenance and servicing
- Chemical industry

Application tips

Wetting of the surfaces to be cleaned to excess. Cleaning is made even more effective if you simultaneously rub away at the surface with paper or cellulose cloths. If necessary, repeat the application at stubborn soiling. Subsequently allow to dry completely at room temperature. Dab away running cleaner with absorbent material and allow to evaporate in open air. Caution: Use only in well-ventilated rooms or in the open air. Some types of plastic or rubber (e.g. thermoplastics such as PVC, plexiglass, polystyrene) and paints could be attacked. We recommend therefore that you check the resistance before using the cleaner.

OKS 2661

Fast Cleaner, Spray

Packaging

- 600 ml Spray

Technical data

	Standard	Conditions	Unit	Value
Main components				
basis				solvent mixture
Application related technical data				
colour				colourless
density	DIN EN ISO 3838	at 20°C	g/cm ³	0.71
Properties and approvals				
UFI				EK30-KOP5-Q00M-UA57

OKS Spezialschmierstoffe GmbH

Ganghoferstraße 47

82216 Maisach

+49 8142 3051 - 500

info@oks-germany.com

www.oks-germany.com



The information in this publication reflects state-of-the-art technology, as well as extensive testing and experience. Due to the diversity of possible applications and technical realities, they can only serve as recommendations and are not arbitrarily transferable. Therefore, no obligations, liability or warranty claims can be derived from them. We only accept liability for the suitability of our products for particular purposes, and for certain properties of our products, in the event that we have accepted such liability in writing in the individual case. Any case of justified warranty claims shall be limited to the delivery of replacement goods free of defects, in the event that this subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular the liability for consequential injuries or damage, shall always be excluded. Prior to use, the customer must conduct its own testing to prove suitability. The data are subject to change for the sake of progress. ® = Registered trademark
Product restricted to professional users. Safety data sheet available for download at www.oks-germany.com
 Our Customer and Technical service will be pleased to help should you have any further questions.