

OKS 5200

Drain Tap

Description

Drain tap for OKS products

Applications

- For low-viscosity OKS products in 5 l canisters

Advantages and benefits

- Resistant to OKS products

Branches

- Catering equipment and food processing technology
- Logistics
- Rubber and plastic processing
- Shipbuilding and marine technology
- Plant and machine (tool) engineering
- Glass and foundry industry
- Iron and steel industry
- Paper and packaging industry
- Municipal services
- Maintenance and servicing
- Chemical industry
- Rail vehicle technology

Application tips

For low-viscosity OKS products in 5 l canisters

Technical data

	Standard	Conditions	Unit	Value
Product specific technical data				
Thread, external Ø			mm ±0.4	55.4
Weight			g	42.2
Thread, internal Ø			mm ±0.4	50.4

Klüber Lubrication München GmbH & Co. KG
Geisenhausenerstraße 7 / 81379 München /
Germany / phone +49 89 7876-0

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.