


OKS 2621

Contact Cleaner, Spray



Description

OKS 2621 is a contact cleaner to remove soiling that can cause creepage currents.

Applications

- Removal of loose oxide and electrode-erosion residues, dust deposits or creepage currents which cause soiling in moving contact areas such as motor-vehicle ignition distributors, relay contacts, resistance or potentiometer slideways, in static contact areas such as motor-vehicle spark plugs, plug-in connections, sliding and screw connections, in or on electrical and electronic equipment or devices of all kinds

Advantages and benefits

- Highly effective due to outstanding cleaning properties
- Broad range of uses for all maintenance and customer service work in electrical sector
- Fast evaporation after striking surface

Branches

- Logistics
- Municipal services
- Rail vehicle technology
- Glass and foundry industry
- Iron and steel industry
- Maintenance and servicing
- Rubber and plastic processing
- Chemical industry
- Shipbuilding and marine technology
- Paper and packaging industry
- Plant and machine (tool) engineering

Application tips

Disconnect voltage and shunt electrostatic charge prior to application. Spray on areas to be cleaned until the desired cleanliness is reached. Components are generally considered to be compatible with plastics, but because of the big variety of materials we recommend you to check the resistance before use.

Packaging

- 400 ml Spray

PRODUCT INFORMATION



KLÜBER
a product brand of **LUBRICATION**

OKS 2621

Contact Cleaner, Spray

Technical data

	Standard	Conditions	Unit	Value
Main components				
base oil				aliphatic hydrocarbons
Application related technical data				
colour				colourless
density	DIN EN ISO 3838	at 20°C	g/cm ³	0.72
Properties and approvals				
UFI				HQE1-109A-E00N-QU94

Klüber Lubrication München GmbH & Co. KG
Geisenhausenerstraße 7 / 81379 München /
Germany / phone +49 89 7876-0

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.