


OKS 2631

Multi-Foam Cleaner, Spray



Description

OKS 2631 is a multi-foam cleaner.

Applications

- Removes strongly adherent organic residues as well as coverings of nicotine, fat, silicone and rubber wear
- Suitable for in- and outdoor application
- Cleans aluminium and stainless steel parts, plastics, glass, chrome and rubber
- For the manifold application in the section of gastronomy, office and automotive, for hobby and sport equipment like e.g. kitchen furnishing, bars, mirrors, window glasses and frames, glass surfaces, tiles, china, screens, machine housings, boats, caravans, surfboards, bikes, polycarbonate screens and acryl glass, visor of helmets, windscreens, lights, a.s.o.

Branches

- Maintenance and servicing
- Municipal services
- Iron and steel industry
- Plant and machine (tool) engineering
- Shipbuilding and marine technology
- Glass and foundry industry
- Logistics
- Paper and packaging industry
- Rail vehicle technology
- Chemical industry
- Rubber and plastic processing

Application tips

Shake spray can very well before use. Spray evenly onto the surface from 20–30 cm distance. After a short residence time wipe away in a damp condition with a clean, non-fuzzing cloth or pulp. Test compatibility with special coatings. Store frost-free.

Advantages and benefits

- Easy application and through the active cleaning foam ideal suitable for vertical areas, no expiration
- Cleans material-gentle and without leaving stripes or streaks behind
- Does not attack paints, rubber or plastic and acts colour-refreshing
- Pleasant, citric like odour, eudermic
- Free from toxic substances like chlorine, CFC, PCB
- Silicone free
- Suitable for acryl-glasses
- Acts anti-static

OKS 2631

Multi-Foam Cleaner, Spray

Packaging

- 400 ml Spray

Technical data

	Standard	Conditions	Unit	Value
Main components				
basis				water
additives				additives
additives				anionic surfactants
Application related technical data				
colour				slightly bluish
density (at 20°C)	DIN EN ISO 3838		g/cm ³	0.99
Product specific technical data				
stress crack test	DIN EN ISO 22088-3			passed
Properties and approvals				
UFI				EJ22-X0R1-500Y-GPW1

OKS Spezialschmierstoffe GmbH

Ganghoferstraße 47

82216 Maisach

+49 8142 3051 - 500

info@oks-germany.com

www.oks-germany.com



The information in this publication reflects state-of-the-art technology, as well as extensive testing and experience. Due to the diversity of possible applications and technical realities, they can only serve as recommendations and are not arbitrarily transferable. Therefore, no obligations, liability or warranty claims can be derived from them. We only accept liability for the suitability of our products for particular purposes, and for certain properties of our products, in the event that we have accepted such liability in writing in the individual case. Any case of justified warranty claims shall be limited to the delivery of replacement goods free of defects, in the event that this subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular the liability for consequential injuries or damage, shall always be excluded. Prior to use, the customer must conduct its own testing to prove suitability. The data are subject to change for the sake of progress. ® = Registered trademark
Product restricted to professional users. Safety data sheet available for download at www.oks-germany.com
 Our Customer and Technical service will be pleased to help should you have any further questions.