

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version 4.0	Revision Date: 29.05.2026	Date of last issue: 20.01.2023 Date of first issue: 26.10.2016	Print Date: 29.05.2026
----------------	------------------------------	---	---------------------------

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 2351

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Lubricant spray

Recommended restrictions on use : Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH
Ganghoferstr. 47
82216 Maisach
Germany
Tel.: +49 8142 3051-500
info@oks-germany.com

E-mail address of person responsible for the SDS : mcm@oks-germany.com

National contact : Klüber Lubrication GmbH Ibérica S. en C.
Ctra C17, Km 15.5
08150 Parets del Vallès (Barcelona)
Espania
Telefono: +34 93 57384 00
Fax: +34 93 573 84 91
customer.service@es.klueber.com

1.4 Emergency telephone number

Emergency telephone number : +34 91 562 04 20

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2	H315: Causes skin irritation.
Specific target organ toxicity - single	H336: May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version 4.0	Revision Date: 29.05.2026	Date of last issue: 20.01.2023 Date of first issue: 26.10.2016	Print Date: 29.05.2026
----------------	------------------------------	---	---------------------------

exposure, Category 3, Central nervous system

Aspiration hazard, Category 1

H304: May be fatal if swallowed and enters airways.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
Storage:
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version 4.0	Revision Date: 29.05.2026	Date of last issue: 20.01.2023 Date of first issue: 26.10.2016	Print Date: 29.05.2026
----------------	------------------------------	---	---------------------------

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Active agent with propellant and solvent.

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	921-024-6 01-2119475514-35- XXXX	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411		>= 10 - < 20
n-hexane	110-54-3 203-777-6 601-037-00-0 01-2119480412-44- XXXX	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361f STOT SE 3; H336 (Central nervous system) STOT RE 1; H372 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	** , ***	>= 0,25 - < 1
Substances with a workplace exposure limit :				
butane	106-97-8 203-448-7 601-004-00-0	Flam. Gas 1; H220 Press. Gas Compr. Gas;	Note U (Table 3), Note C, Note	>= 30 - < 50

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version 4.0 Revision Date: 29.05.2026 Date of last issue: 20.01.2023 Print Date: 29.05.2026
Date of first issue: 26.10.2016

	01-2119474691-32-XXXX	H280	S	
propane	74-98-6 200-827-9 601-003-00-5 01-2119486944-21-XXXX	Flam. Gas 1; H220 Press. Gas Compr. Gas; H280	Note U (Table 3)	$\geq 10 - < 20$
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25-XXXX	Not classified	Note L	$\geq 10 - < 20$
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified	64742-65-0 265-169-7 649-474-00-6 01-2119471299-27-XXXX	Not classified		$\geq 10 - < 20$
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1 01-2119529243-45-XXXX	Flam. Sol. 1; H228	Note T	$\geq 1 - < 10$
isobutane	75-28-5 200-857-2 601-004-00-0 01-2119485395-27-XXXX	Flam. Gas 1A; H220 Press. Gas Compr. Gas; H280	Note U (Table 3), Note C	$\geq 1 - < 10$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Call a physician or poison control centre immediately.
Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact : Take off all contaminated clothing immediately.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version 4.0	Revision Date: 29.05.2026	Date of last issue: 20.01.2023 Date of first issue: 26.10.2016	Print Date: 29.05.2026
----------------	------------------------------	---	---------------------------

Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
Wash off immediately with plenty of water.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
If eye irritation persists, consult a specialist.

If swallowed : Move the victim to fresh air.
If accidentally swallowed obtain immediate medical attention.
Keep respiratory tract clear.
Do NOT induce vomiting.
Rinse mouth with water.
Aspiration hazard if swallowed - can enter lungs and cause damage.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:
Unconsciousness
Dizziness
Drowsiness
Headache
Nausea
Tiredness
Skin contact may provoke the following symptoms:
Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Risks : May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause drowsiness or dizziness.

Central nervous system depression
Risk of product entering the lungs on vomiting after ingestion.
Health injuries may be delayed.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing : High volume water jet

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version	Revision Date:	Date of last issue: 20.01.2023	Print Date:
4.0	29.05.2026	Date of first issue: 26.10.2016	29.05.2026

media

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Fire Hazard
Do not let product enter drains.
Contains gas under pressure; may explode if heated.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion products : Carbon oxides
Nitrogen oxides (NOx)
Metal oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not breathe vapours or spray mist.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Refer to protective measures listed in sections 7 and 8.
Only qualified personnel equipped with suitable protective equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version	Revision Date:	Date of last issue: 20.01.2023	Print Date:
4.0	29.05.2026	Date of first issue: 26.10.2016	29.05.2026

Keep in suitable, closed containers for disposal.
Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Do not use in areas without adequate ventilation.
Do not breathe vapours or spray mist.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin and eyes.
For personal protection see section 8.
Keep away from fire, sparks and heated surfaces.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
Do not get in eyes or mouth or on skin.
Do not get on skin or clothing.
Do not ingest.
Do not use sparking tools.
These safety instructions also apply to empty packaging which may still contain product residues.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
- Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular national regulations.

7.3 Specific end use(s)

- Specific use(s) : Specific instructions for handling, not required.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version 4.0 Revision Date: 29.05.2026 Date of last issue: 20.01.2023 Print Date: 29.05.2026
Date of first issue: 26.10.2016

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
butane	106-97-8	VLA-ED (gas)	1.000 ppm	ES VLA (2013-02-22)
propane	74-98-6	VLA-ED (gas)	1.000 ppm	ES VLA (2024-01-15)
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	64742-54-7	VLA-ED (Mist)	5 mg/m ³	ES VLA (2019-02-20)
		VLA-EC (Mist)	10 mg/m ³	ES VLA (2019-02-20)
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified	64742-65-0	VLA-ED (Mist)	5 mg/m ³	ES VLA (2019-02-20)
		VLA-EC (Mist)	10 mg/m ³	ES VLA (2019-02-20)
aluminium powder (stabilised)	7429-90-5	VLA-ED (respirable fraction)	1 mg/m ³	ES VLA (2021-04-01)
isobutane	75-28-5	VLA-ED (gas)	1.000 ppm	ES VLA (2013-02-22)
n-hexane	110-54-3	TWA	20 ppm 72 mg/m ³	2006/15/EC (2006-02-09)
Further information: Indicative				
		VLA-ED	20 ppm 72 mg/m ³	ES VLA (2011-03-03)

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
n-hexane	110-54-3	2,5-hexanedione: 0,2 mg/l (Urine)	At the end of the work week	ES VLB (2014-01-01)

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil —	Workers	Inhalation	Long-term local effects	5,58 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version 4.0 Revision Date: 29.05.2026 Date of last issue: 20.01.2023 Print Date: 29.05.2026
Date of first issue: 26.10.2016

unspecified				
	Workers	Inhalation	Long-term systemic effects	2,73 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,97 mg/kg
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified	Workers	Inhalation	Long-term systemic effects	2,73 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,97 mg/kg
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Workers	Skin contact	Long-term systemic effects	773 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	2035 mg/m3
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3,72 mg/m3
	Workers	Inhalation	Long-term local effects	3,72 mg/m3
n-hexane	Workers	Inhalation	Long-term systemic effects	75 mg/m3
	Workers	Skin contact	Long-term systemic effects	11 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	Oral	9,33 mg/kg
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified	Oral	9,33 mg/kg

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye/face protection : Safety glasses with side-shields

Hand protection

Material : butyl-rubber

Break through time : > 10 min

Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version 4.0	Revision Date: 29.05.2026	Date of last issue: 20.01.2023 Date of first issue: 26.10.2016	Print Date: 29.05.2026
----------------	------------------------------	---	---------------------------

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Short term only
- Filter type : Filter type A-P
- Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Environmental exposure controls

- Air : Should not be released into the environment.
- Soil : Do not allow contact with soil, surface or ground water. The product should not be allowed to enter drains, water courses or the soil.
- Water : Do not allow contact with soil, surface or ground water. The product should not be allowed to enter drains, water courses or the soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : aerosol
- Colour : grey
- Odour : characteristic
- Odour Threshold : No data available
- Melting point/ range : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version 4.0	Revision Date: 29.05.2026	Date of last issue: 20.01.2023 Date of first issue: 26.10.2016	Print Date: 29.05.2026
----------------	------------------------------	---	---------------------------

Boiling point/boiling range : -44,5 °C (1.013 hPa)

Flammability : Flammability (solid, gas):
Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 10,9 %(V)

Lower explosion limit / Lower flammability limit : 0,8 %(V)

Flash point : -97,00 °C
Method: Abel-Pensky

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable
substance/mixture is non-soluble (in water)

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : < 20,5 mm²/s (40 °C)

Solubility(ies)
Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 4.750 hPa (20 °C)

Relative density : 0,7 (20 °C)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version 4.0	Revision Date: 29.05.2026	Date of last issue: 20.01.2023 Date of first issue: 26.10.2016	Print Date: 29.05.2026
----------------	------------------------------	---	---------------------------

Reference substance: Water
The value is calculated

Density : 0,70 g/cm³
(20 °C)

Bulk density : No data available

Relative vapour density : No data available

9.2 Other information

Explosives : Not explosive

Oxidizing properties : No data available

Self-ignition : not auto-flammable

Metal corrosion rate : Not corrosive to metals

Evaporation rate : No data available

Sublimation point : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.
Strong sunlight for prolonged periods.
Risk of receptacle bursting.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version	Revision Date:	Date of last issue: 20.01.2023	Print Date:
4.0	29.05.2026	Date of first issue: 26.10.2016	29.05.2026

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

- Acute oral toxicity : Remarks: Effects due to ingestion may include:
Symptoms: Central nervous system depression
- Acute inhalation toxicity : Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.
Remarks: Respiration of solvent vapour may cause dizziness.
Symptoms: Inhalation may provoke the following symptoms:, Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central nervous system depression
- Acute dermal toxicity : Symptoms: Redness, Local irritation

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

- Acute oral toxicity : LD50 (Rat): > 5.840 mg/kg
Assessment: The substance or mixture has no acute oral toxicity
- Acute inhalation toxicity : LC50 (Rat): > 25,2 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rat): > 2,8 g/kg
Assessment: The substance or mixture has no acute dermal toxicity

|| n-hexane:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version 4.0	Revision Date: 29.05.2026	Date of last issue: 20.01.2023 Date of first issue: 26.10.2016	Print Date: 29.05.2026
----------------	------------------------------	---	---------------------------

Acute oral toxicity	:	LD50 (Rat): > 5.000 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	LC50 (Rat): 259,35 mg/l Exposure time: 4 h Test atmosphere: vapour Method: OECD Test Guideline 403
Acute dermal toxicity	:	LD50 (Rabbit): 3.350 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity

butane:

Acute inhalation toxicity	:	LC50 (Rat): 658 mg/l Exposure time: 4 h Test atmosphere: gas
---------------------------	---	--

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Acute oral toxicity	:	LD50 (Rat): > 5.000 mg/kg Method: OECD Test Guideline 401 GLP: yes
Acute inhalation toxicity	:	LC50 (Rat): > 5,53 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	:	LD50 (Rabbit): > 5.000 mg/kg Method: OECD Test Guideline 402

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Acute oral toxicity	:	LD50 (Rat): > 5.000 mg/kg Method: OECD Test Guideline 401
Acute dermal toxicity	:	LD50 (Rabbit): > 5.000 mg/kg Method: OECD Test Guideline 402

aluminium powder (stabilised):

Acute inhalation toxicity	:	LC50 (Rat): > 5,09 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity
---------------------------	---	--

isobutane:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version 4.0	Revision Date: 29.05.2026	Date of last issue: 20.01.2023 Date of first issue: 26.10.2016	Print Date: 29.05.2026
----------------	------------------------------	---	---------------------------

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: gas

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : This information is not available.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit
Assessment : Irritating to skin.
Method : OECD Test Guideline 404
Result : Irritating to skin.

n-hexane:

Species : Rabbit
Assessment : Irritating to skin.
Method : OECD Test Guideline 404
Result : Irritating to skin.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

aluminium powder (stabilised):

Species : Rabbit
Assessment : No skin irritation
Result : No skin irritation

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version	Revision Date:	Date of last issue: 20.01.2023	Print Date:
4.0	29.05.2026	Date of first issue: 26.10.2016	29.05.2026

Product:

Remarks : Contact with eyes may cause irritation.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit
Assessment : No eye irritation
Result : No eye irritation

n-hexane:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes

aluminium powder (stabilised):

Species : Rabbit
Assessment : No eye irritation
Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Product:

Remarks : This information is not available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version	Revision Date:	Date of last issue: 20.01.2023	Print Date:
4.0	29.05.2026	Date of first issue: 26.10.2016	29.05.2026

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Test Type	: Maximisation Test
Exposure routes	: Dermal
Species	: Guinea pig
Assessment	: Does not cause skin sensitisation.
Method	: OECD Test Guideline 406
Result	: Did not cause sensitisation on laboratory animals.

n-hexane:

Species	: Mouse
Assessment	: Does not cause skin sensitisation.
Method	: OECD Test Guideline 429
Result	: Does not cause skin sensitisation.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Species	: Guinea pig
Assessment	: Does not cause skin sensitisation.
Method	: OECD Test Guideline 406
Result	: Does not cause skin sensitisation.
GLP	: yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Species	: Guinea pig
Assessment	: Does not cause skin sensitisation.
Method	: OECD Test Guideline 406
Result	: Does not cause skin sensitisation.
GLP	: yes

aluminium powder (stabilised):

Species	: Guinea pig
Assessment	: Did not cause sensitisation on laboratory animals.
Result	: Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Product:

Genotoxicity in vitro	: Remarks: No data available
Genotoxicity in vivo	: Remarks: No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version 4.0	Revision Date: 29.05.2026	Date of last issue: 20.01.2023 Date of first issue: 26.10.2016	Print Date: 29.05.2026
----------------	------------------------------	---	---------------------------

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Test system: Rodent cell line
Method: OECD Test Guideline 473
Result: negative

n-hexane:

Germ cell mutagenicity-
Assessment : Weight of evidence does not support classification as a germ
cell mutagen.

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Genotoxicity in vitro : Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Species: Mouse
Application Route: Oral
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Based on available data, the classification criteria are not met.

Product:

Remarks : No data available

Components:

n-hexane:

Carcinogenicity -
Assessment : Weight of evidence does not support classification as a
carcinogen

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Carcinogenicity -
Assessment : Not classifiable as a human carcinogen.

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Species : Mouse
Application Route : Dermal
Method : OECD Test Guideline 451
Result : negative

Reproductive toxicity

Based on available data, the classification criteria are not met.

Product:

Effects on fertility : Remarks: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version 4.0	Revision Date: 29.05.2026	Date of last issue: 20.01.2023 Date of first issue: 26.10.2016	Print Date: 29.05.2026
----------------	------------------------------	---	---------------------------

Effects on foetal development : Remarks: No data available

Components:

n-hexane:

Reproductive toxicity - Assessment : - Fertility -
Suspected human reproductive toxicant

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Reproductive toxicity - Assessment : - Fertility -
No toxicity to reproduction

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Effects on foetal development : Species: Rat
Application Route: Dermal
General Toxicity Maternal: NOAEL: 30 mg/kg body weight
Developmental Toxicity: NOAEL: 30 mg/kg body weight
Method: OECD Test Guideline 414

STOT - single exposure

May cause drowsiness or dizziness.

Product:

Remarks : No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

n-hexane:

Exposure routes : Inhalation
Target Organs : Central nervous system
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Product:

Remarks : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version	Revision Date:	Date of last issue: 20.01.2023	Print Date:
4.0	29.05.2026	Date of first issue: 26.10.2016	29.05.2026

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Exposure routes : inhalation (vapour)
Assessment : No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

n-hexane:

Target Organs : Central nervous system
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May be fatal if swallowed and enters airways.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

May be fatal if swallowed and enters airways.

n-hexane:

May be fatal if swallowed and enters airways.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

No aspiration toxicity classification

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

No aspiration toxicity classification

11.2 Information on other hazards

Endocrine disrupting properties

Based on available data, the classification criteria are not met.

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version 4.0	Revision Date: 29.05.2026	Date of last issue: 20.01.2023 Date of first issue: 26.10.2016	Print Date: 29.05.2026
----------------	------------------------------	---	---------------------------

levels of 0.1% or higher.

Further information

Product:

Remarks : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms :
Remarks: No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 22 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : EbC50 (Pseudokirchneriella subcapitata (green algae)): 26 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version 4.0	Revision Date: 29.05.2026	Date of last issue: 20.01.2023 Date of first issue: 26.10.2016	Print Date: 29.05.2026
----------------	------------------------------	---	---------------------------

n-hexane:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 12,51 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 21,85 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): 9,285 mg/l Exposure time: 72 h

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 203 GLP: yes
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10.000 mg/l Exposure time: 48 h Test Type: Immobilization Method: OECD Test Guideline 202 GLP: yes
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: 10 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Test Type: semi-static test Method: OECD Test Guideline 211 GLP: yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 203 GLP: yes
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10.000 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	NOEC (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 72 h Test Type: static test Method: OECD Test Guideline 201

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version 4.0	Revision Date: 29.05.2026	Date of last issue: 20.01.2023 Date of first issue: 26.10.2016	Print Date: 29.05.2026
----------------	------------------------------	---	---------------------------

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

aluminium powder (stabilised):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0,12 mg/l
Exposure time: 96 h
Test Type: static test
Remarks: No toxicity at the limit of solubility

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Biodegradability : Result: Readily biodegradable.

n-hexane:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: rapidly biodegradable
Biodegradation: 98 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: Not rapidly biodegradable
Biodegradation: 3 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
GLP: yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version	Revision Date:	Date of last issue: 20.01.2023	Print Date:
4.0	29.05.2026	Date of first issue: 26.10.2016	29.05.2026

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: Not rapidly biodegradable
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
GLP: yes

aluminium powder (stabilised):

Biodegradability : Remarks: The methods for determining biodegradability are not applicable to inorganic substances.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

n-hexane:

Bioaccumulation : Bioconcentration factor (BCF): 501,19
Partition coefficient: n-octanol/water : log Pow: 3,42 - 5,8 (20 °C)
pH: 7

butane:

Partition coefficient: n-octanol/water : log Pow: 2,89
Method: OECD Test Guideline 107

propane:

Partition coefficient: n-octanol/water : log Pow: 2,36

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Partition coefficient: n-octanol/water : log Pow: 10,16 - 24,9

isobutane:

Partition coefficient: n-octanol/water : log Pow: 2,88
Method: OECD Test Guideline 107

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version 4.0	Revision Date: 29.05.2026	Date of last issue: 20.01.2023 Date of first issue: 26.10.2016	Print Date: 29.05.2026
----------------	------------------------------	---	---------------------------

Distribution among environmental compartments : Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Assessment : Non-classified vPvB substance. Non-classified PBT substance

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Offer empty spray cans to an established disposal company.
Pressurized container: Do not pierce or burn, even after use.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version 4.0	Revision Date: 29.05.2026	Date of last issue: 20.01.2023 Date of first issue: 26.10.2016	Print Date: 29.05.2026
----------------	------------------------------	---	---------------------------

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied
16 05 04*, gases in pressure containers (including halons)
containing hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS
IATA : Aerosols, flammable

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 2	2.1
RID	: 2	2.1
IMDG	: 2.1	
IATA	: 2.1	

14.4 Packing group

ADR
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

RID
Packing group : Not assigned by regulation
Classification Code : 5F
Hazard Identification Number : 23
Labels : 2.1

IMDG
Packing group : Not assigned by regulation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version 4.0	Revision Date: 29.05.2026	Date of last issue: 20.01.2023 Date of first issue: 26.10.2016	Print Date: 29.05.2026
----------------	------------------------------	---	---------------------------

Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 40
This substance/mixture shall not be used in aerosol dispensers intended for supply to the general public for entertainment and decorative purposes.

Number on list 75

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version 4.0	Revision Date: 29.05.2026	Date of last issue: 20.01.2023 Date of first issue: 26.10.2016	Print Date: 29.05.2026
----------------	------------------------------	---	---------------------------

If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). (EU SVHC) : n-hexane

Regulation (EU) No 2024/590 on substances that deplete the ozone layer (EC 2024/590) : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) (EU POP) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals (EU PIC) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) (EU. REACH-Annex XIV) : Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors : Not applicable

P2

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P3a FLAMMABLE AEROSOLS

18 Liquefied flammable gases (including LPG) and natural gas

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version	Revision Date:	Date of last issue: 20.01.2023	Print Date:
4.0	29.05.2026	Date of first issue: 26.10.2016	29.05.2026

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 62,5 %

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

H220 : Extremely flammable gas.
H225 : Highly flammable liquid and vapour.
H228 : Flammable solid.
H280 : Contains gas under pressure; may explode if heated.
H304 : May be fatal if swallowed and enters airways.
H315 : Causes skin irritation.
H336 : May cause drowsiness or dizziness.
H361f : Suspected of damaging fertility.
H372 : Causes damage to organs through prolonged or repeated exposure.
H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

** : Route of exposure cannot be excluded: For certain hazard classes, e.g. STOT, the route of exposure should be indicated in the hazard statement only if it is conclusively proven that no other route of exposure can cause the hazard in accordance to the criteria in Annex I. Under Directive 67/548/EEC the route of exposure was indicated for classifications with R48 when there was data justifying the classification for this route of exposure. The classification under 67/548/EEC indicating the route of exposure has been translated into the corresponding class and category according to this Regulation, but with a general hazard statement not specifying the route of exposure as the necessary information is not available.

*** : Hazard statements for reproductive toxicity: Hazard statements H360 and H361 indicate a general concern for effects on fertility and/or development: 'May damage/Suspected of damaging fertility or the unborn child'. According to the criteria, the general hazard statement can be

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version	Revision Date:	Date of last issue: 20.01.2023	Print Date:
4.0	29.05.2026	Date of first issue: 26.10.2016	29.05.2026

- replaced by the hazard statement indicating the specific effect of concern in accordance with Section 1.1.2.1.2. When the other differentiation is not mentioned, this is due to evidence proving no such effect, inconclusive data or no data and the obligations in Article 4(3) shall apply for that differentiation. In order not to lose information from the harmonised classifications for fertility and developmental effects under Directive 67/548/EEC, the classifications have been translated only for those effects classified under that Directive
- Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Flam. Gas : Flammable gases
Flam. Liq. : Flammable liquids
Flam. Sol. : Flammable solids
Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- Note L : The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extraction refractive index method" Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.
- Note S : This substance may not require a label according to Article 17 (see Section 1.3 of Annex I) (Table 3).
- Note T : This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be included in the safety data sheet.
- Note U (Table 3) : When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).
- Press. Gas : Gases under pressure
Repr. : Reproductive toxicity
Skin Irrit. : Skin irritation
STOT RE : Specific target organ toxicity - repeated exposure

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version	Revision Date:	Date of last issue: 20.01.2023	Print Date:
4.0	29.05.2026	Date of first issue: 26.10.2016	29.05.2026

STOT SE : Specific target organ toxicity - single exposure
2006/15/EC : Europe. Indicative occupational exposure limit values
ES VLA : Spain. Environmental Limits for exposure to Chemical agents
- Table 1: Occupational Exposure Values
ES VLB : Occupational Exposure Limits for Chemical Agents in Spain -
Biological Exposure Values
2006/15/EC / TWA : Limit Value - eight hours
ES VLA / VLA-ED : Environmental Daily Limit Value
ES VLA / VLA-EC : Environmental Short Term Value

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315
STOT SE 3	H336
Asp. Tox. 1	H304

Classification procedure:

Based on product data or assessment
Calculation method
Based on product data or assessment
Based on product data or assessment

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - ES



OKS 2351

Version 4.0	Revision Date: 29.05.2026	Date of last issue: 20.01.2023 Date of first issue: 26.10.2016	Print Date: 29.05.2026
----------------	------------------------------	---	---------------------------

Aquatic Chronic 3

H412

Calculation method

|| Relevant changes compared to the last edition are highlighted at the left margin. This version replaces all previous editions.

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.