




OKS 2670

Intensive Cleaner, for Food Processing Technology



Description

OKS 2670 is a highly-effective cleaner on a solvent basis for use in the food processing industry.

Applications

- Cleaning of bearings and machine parts
- Removal of aged and gummy oil and grease residues
- Dissolving of silicone and adhesive residues
- Preparation of surfaces for bonding

Branches

- Catering equipment and food processing technology
- Chemical industry
- Shipbuilding and marine technology
- Logistics
- Rail vehicle technology
- Plant and machine (tool) engineering
- Paper and packaging industry
- Rubber and plastic processing
- Municipal services
- Glass and foundry industry
- Iron and steel industry

Advantages and benefits

- High cleaning action through optimally matched mixture of active substances
- Rapid, residue-free evaporation of the cleaner
- NSF K1 K3 registered
- Good compatibility to common plastics such as polypropylene (PP), polycarbonate (PC), acrylonitrile-butadiene-styrene (ABS), polyethylene terephthalate (PET), polystyrene (PS), polyoxymethylene ((POM), polyvinyl chloride (PVC), polyethylene (PE), polytetrafluoroethylene (PTFE)
- OKS 2670 is suitable for use with the OKS Airspray system
- Also available as spray version OKS 2671

Application tips

Wetting of the surfaces to be cleaned to excess. Cleaning is made even more effective if you simultaneously rub away at the surface with paper or cellulose cloths. If necessary, repeat the application at stubborn soiling. Subsequently allow to dry completely at room temperature. Dab away running cleaner with absorbent material and allow to evaporate in open air. Caution: Use only in well-ventilated rooms or in the open air. Limitations for use on elastomers and plastics, such as materials made of EPDM, neoprene, polyurethane, silicone, fluoroelastomers. We recommend therefore that you check the resistance before using the cleaner. Caution: Observe the specifications of the NSF when used in the food processing industry.

Packaging

- 5 l Canister
- 25 l Canister

OKS 2670

Intensive Cleaner, for Food Processing Technology

Technical data

	Standard	Conditions	Unit	Value
Main components				
solvent				solvent mixture
Application related technical data				
flashing point				-15
colour				colourless
density (at 20°C)	DIN EN ISO 3838		g/cm ³	0.78
Properties and approvals				
UFI				AGW1-300M-300S-GJH7
approval for food processing technology				NSF K1, K3, Reg.-Nr. 149997

OKS Spezialschmierstoffe GmbH

Ganghoferstraße 47

82216 Maisach

+49 8142 3051 - 500

info@oks-germany.com

www.oks-germany.com

a brand of



FREUDENBERG

The information in this publication reflects state-of-the-art technology, as well as extensive testing and experience. Due to the diversity of possible applications and technical realities, they can only serve as recommendations and are not arbitrarily transferable. Therefore, no obligations, liability or warranty claims can be derived from them. We only accept liability for the suitability of our products for particular purposes, and for certain properties of our products, in the event that we have accepted such liability in writing in the individual case. Any case of justified warranty claims shall be limited to the delivery of replacement goods free of defects, in the event that this subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular the liability for consequential injuries or damage, shall always be excluded. Prior to use, the customer must conduct its own testing to prove suitability. The data are subject to change for the sake of progress. ® = Registered trademark

Product restricted to professional users. Safety data sheet available for download at [www.oks-germany.com](#)

Our Customer and Technical service will be pleased to help should you have any further questions.