according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



Print Date:

**OKS 2561** 

Version Revision Date: Date of last issue: -

1.0 16.09.2024 Date of first issue: 16.09.2024 17.09.2024

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 2561

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Corrosion inhibitor

Substance/Mixture

Recommended restrictions

on use

Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

82216 Maisach-Gernlinden

Deutschland

Tel.: +49 8142 3051 500 Fax: +49 8142 3051 599 info@oks-germany.com

E-mail address of person

responsible for the SDS

mcm@oks-germany.com

National contact

1.4 Emergency telephone number

Emergency telephone

: +34 91 562 04 20

number

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



**OKS 2561** 

Version Revision Date: Date of last issue: - Print Date: 1.0 16.09.2024 Date of first issue: 16.09.2024 17.09.2024

Long-term (chronic) aquatic hazard,

Category 2

H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard

Statements

EUH066

Repeated exposure may cause skin

dryness or cracking.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing mist.

P273 Avoid release to the environment.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

#### Hazardous components which must be listed on the label:

butanone

acetone

n-butyl acetate

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



#### **OKS 2561**

Version Revision Date: Date of last issue: - Print Date: 1.0 16.09.2024 Date of first issue: 16.09.2024 17.09.2024

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : Active agent with propellant and solvent.

Metal powder

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
butanone	78-93-3 201-159-0 606-002-00-3 01-2119457290-43- XXXX	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336; EUH066		>= 30 - < 50
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49- XXXX	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336; EUH066		>= 10 - < 20
cyclopentanone	120-92-3 204-435-9 606-025-00-9 01-2119495595-21- xxxx	Flam. Liq.3; H226 Skin Irrit.2; H315 Eye Irrit.2; H319		>= 1 - < 10
zinc powder — zinc dust (stabilised)	7440-66-6 231-175-3	Aquatic Acute1; H400	M-Factor: 1/1	>= 2,5 - < 10

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



#### **OKS 2561**

VersionRevision Date:Date of last issue: -Print Date:1.016.09.2024Date of first issue: 16.09.202417.09.2024

	030-001-01-9 01-2119467174-37- XXXX	Aquatic Chronic1; H410		
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29- XXXX	Flam. Liq.3; H226 STOT SE3; H336; EUH066		>= 1 - < 10
Substances with a wor	rkplace exposure limit:	-		
dimethyl ether	115-10-6 204-065-8 603-019-00-8 01-2119472128-37- XXXX	Flam. Gas1A; H220 Press. GasLiquefied gas; H280	Note U (table 3.1)	>= 30 - < 50
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1 01-2119529243-45- XXXX	Flam. Sol.1; H228	Note T	>= 1 - < 10

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

If inhaled : Call a physician or poison control centre immediately.

Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial

respiration.

In case of skin contact : Take off all contaminated clothing immediately.

Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

Wash skin thoroughly with soap and water or use recognized



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



**OKS 2561** 

Version Revision Date: Date of last issue: - Print Date: 1.0 16.09.2024 Date of first issue: 16.09.2024 17.09.2024

skin cleanser.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes. Seek medical advice.

If swallowed : Move the victim to fresh air.

If accidentally swallowed obtain immediate medical attention.

Keep respiratory tract clear. Do NOT induce vomiting. Rinse mouth with water.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:

Unconsciousness

Dizziness Drowsiness Headache Nausea Tiredness

Skin contact may provoke the following symptoms:

Erythema

Risks : Central nervous system depression

Can be absorbed through skin.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

### **SECTION 5: Firefighting measures**

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during : Fire Hazard

firefighting Do not let product enter drains.

Contains gas under pressure; may explode if heated. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion

products

Carbon oxides

Halogenated compounds



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



**OKS 2561** 

Version Revision Date: Date of last issue: - Print Date: 1.0 16.09.2024 Date of first issue: 16.09.2024 17.09.2024

Metal oxides

5.3 Advice for firefighters

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Cool containers/tanks with water spray.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Ensure adequate ventilation. Remove all sources of ignition.

Do not breathe vapours or spray mist.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8. Only qualified personnel equipped with suitable protective

equipment may intervene.

### 6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

Non-sparking tools should be used.

#### 6.4 Reference to other sections

For personal protection see section 8.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



**OKS 2561** 

Version Revision Date: Date of last issue: - Print Date: 1.0 16.09.2024 Date of first issue: 16.09.2024 17.09.2024

Advice on safe handling : Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.

Keep away from fire, sparks and heated surfaces. Smoking, eating and drinking should be prohibited in the

application area.

Wash hands and face before breaks and immediately after

handling the product.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest.

Do not use sparking tools.

These safety instructions also apply to empty packaging which

may still contain product residues.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or

burn, even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular

national regulations.

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

#### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form	Control parameters	Basis
		of exposure)		
butanone	78-93-3	STEL	300 ppm	2000/39/EC
			900 mg/m3	(2000-06-16)
	Further information: Indicative			
		TWA	200 ppm	2000/39/EC
			600 mg/m3	(2000-06-16)



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES  $\,$ 



# **OKS 2561**

VersionRevision Date:Date of last issue: -Print Date:1.016.09.2024Date of first issue: 16.09.202417.09.2024

	Further infor	mation: Indicative		
		VLA-EC	300 ppm 900 mg/m3	ES VLA (2011-03-03)
		VLA-ED	200 ppm 600 mg/m3	ES VLA (2011-03-03)
dimethyl ether	115-10-6	TWA	1.000 ppm 1.920 mg/m3	2000/39/EC (2000-06-16)
	Further infor	mation: Indicative		
		VLA-ED	1.000 ppm 1.920 mg/m3	ES VLA (2012-01-01)
acetone	67-64-1	TWA	500 ppm 1.210 mg/m3	2000/39/EC (2000-06-16)
	Further infor	mation: Indicative		
		VLA-ED	500 ppm 1.210 mg/m3	ES VLA (2011-03-03)
aluminium powder (stabilised)	7429-90-5	VLA-ED (respirable fraction)	1 mg/m3	ES VLA (2021-04-01)
n-butyl acetate	123-86-4	STEL	150 ppm 723 mg/m3	2019/1831/E U (2019-10-31)
	Further infor	mation: Indicative	·	
		TWA	50 ppm 241 mg/m3	2019/1831/E U (2019-10-31)
	Further information: Indicative			
		VLA-ED	50 ppm 241 mg/m3	ES VLA (2022-04-01)
		VLA-EC	150 ppm 723 mg/m3	ES VLA (2022-04-01)

# **Biological occupational exposure limits**

Substance name	CAS-No.	Control parameters	Sampling time	Basis
butanone	78-93-3	methyl ethyl	End of workday	ES VLB
		ketone: 2 mg/l		(2011-03-
		(Urine)		03)
acetone	67-64-1	Acetone: 50 mg/l	End of workday	ES VLB
		(Urine)		(2011-03-
				03)

# Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
butanone	Workers	Inhalation	Long-term systemic effects	600 mg/m3
	Workers	Skin contact	Long-term systemic effects	1161 mg/kg
dimethyl ether	Workers	Inhalation	Long-term exposure	1894 mg/m3
acetone	Workers	Inhalation	Long-term systemic effects	1210 mg/m3



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES  $\,$ 



# **OKS 2561**

VersionRevision Date:Date of last issue: -Print Date:1.016.09.2024Date of first issue: 16.09.202417.09.2024

	Workers	Skin contact	Long-term systemic effects	186 mg/kg
cyclopentanone	Workers	Inhalation	Long-term systemic effects	61 mg/m3
	Workers	Skin contact	Long-term systemic effects	7 mg/kg
zinc powder — zinc dust (stabilised)	Workers	Inhalation	Long-term systemic effects	5 mg/m3
	Workers	Skin contact	Long-term systemic effects	83 mg/kg
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3,72 mg/m3
	Workers	Inhalation	Long-term local effects	3,72 mg/m3
n-butyl acetate	Workers	Inhalation	Long-term systemic effects	300 mg/m3
	Workers	Inhalation	Acute systemic effects	600 mg/m3
	Workers	Dermal	Long-term local effects	11 mg/cm2

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
dimethyl ether	Fresh water	0,155 mg/l
	Marine water	0,016 mg/l
	Sewage treatment plant	160 mg/l
	Fresh water sediment	0,681 mg/kg
	Marine sediment	0,069 mg/kg
	Soil	0,045 mg/kg
acetone	Fresh water	10,6 mg/l
	Marine water	1,06 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	30,4 mg/kg
	Marine sediment	3,04 mg/kg
	Soil	29,5 mg/kg
zinc powder — zinc dust	Fresh water	0,0206 mg/l
(stabilised)		_
	Fresh water sediment	117,8 mg/kg
	Marine water	0,0061 mg/l
	Marine sediment	56,5 mg/kg
	Microbiological Activity in Sewage Treatment Systems	0,052 mg/l
	Soil	35,6 mg/kg
n-butyl acetate	Fresh water	0,18 mg/l
	Marine water	0,018 mg/l
	Microbiological Activity in Sewage	35,6 mg/l
	Treatment Systems	, ,
	Fresh water sediment	0,981 mg/kg
	Marine sediment	0,0981 mg/kg
	Soil	0,09 mg/kg



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



Print Date:

**OKS 2561** 

Version Revision Date: Date of last issue: -

1.0 16.09.2024 Date of first issue: 16.09.2024 17.09.2024

#### 8.2 Exposure controls

#### **Engineering measures**

Use only in an area equipped with explosion proof exhaust ventilation.

Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye/face protection : Safety glasses with side-shields

Hand protection

Material : Nitrile rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each

case.

The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard

EN 374 derived from it.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Recommended Filter type:

Organic gas and low boiling vapour type (AX)

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state : aerosol

Colour : silver

Odour : characteristic

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



**OKS 2561** 

Version Revision Date: Date of last issue: - Print Date: 1.0 16.09.2024 Date of first issue: 16.09.2024 17.09.2024

Odour Threshold : No data available

Melting point/range : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

15 %(V)

Lower explosion limit / Lower

flammability limit

1 %(V)

Flash point : -60 °C

Method: Abel-Pensky

Auto-ignition temperature : 365 °C

Decomposition temperature : No data available

pH : Not applicable

substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : < 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 5.500 hPa (20 °C)

Relative density : 0,69 (20 °C)

Reference substance: Water The value is calculated

Density : 0,69 g/cm3

(20 °C)

Bulk density : No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



**OKS 2561** 

Version Revision Date: Date of last issue: - Print Date: 1.0 16.09.2024 Date of first issue: 16.09.2024 17.09.2024

Relative vapour density : No data available

9.2 Other information

Explosives : Not explosive

Oxidizing properties : No data available

Self-ignition : No data available

Evaporation rate : No data available

Sublimation point : No data available

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No hazards to be specially mentioned.

#### 10.2 Chemical stability

Stable under normal conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

Strong sunlight for prolonged periods.

Risk of receptacle bursting.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

#### **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

**Product:** 

Acute oral toxicity : Remarks: Effects due to ingestion may include:



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



**OKS 2561** 

Version Revision Date: Date of last issue: - Print Date: 1.0 16.09.2024 Date of first issue: 16.09.2024 17.09.2024

Symptoms: Central nervous system depression

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.

Harmful by inhalation.

Symptoms: Inhalation may provoke the following symptoms:, Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central nervous system depression

Acute dermal toxicity : Remarks: Prolonged or repeated skin contact with liquid may

cause defatting resulting in drying, redness and possible

blistering.

Symptoms: Skin disorders

**Components:** 

butanone:

Acute oral toxicity : LD50 (Rat): 2.193 mg/kg

Method: OECD Test Guideline 423

GLP: yes

Acute inhalation toxicity : LC50 (Rat): 34 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Method: OECD Test Guideline 402

acetone:

Acute oral toxicity : LD50 Oral (Rat): 5.800 mg/kg

cyclopentanone:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

zinc powder — zinc dust (stabilised):

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Assessment: The substance or mixture has no acute oral

toxicity

Acute inhalation toxicity : LC50 (Rat): > 5,41 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

GLP: yes

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



**OKS 2561** 

Version Revision Date: Date of last issue: - Print Date: 1.0 16.09.2024 Date of first issue: 16.09.2024 17.09.2024

Assessment: The substance or mixture has no acute

inhalation toxicity

n-butyl acetate:

Acute oral toxicity : LD50 (Rat): 10.768 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Method: OECD Test Guideline 403

GLP: yes

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 17.600 mg/kg

dimethyl ether:

Acute inhalation toxicity : LC50 (Rat): 309 mg/l

Exposure time: 4 h
Test atmosphere: gas

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5,09 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute

inhalation toxicity

Skin corrosion/irritation

**Product:** 

Remarks : This information is not available.

**Components:** 

butanone:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

Result : Repeated exposure may cause skin dryness or cracking.

acetone:

Result : Repeated exposure may cause skin dryness or cracking.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



**OKS 2561** 

Version Date of last issue: -Revision Date:

Print Date: 16.09.2024 Date of first issue: 16.09.2024 17.09.2024 1.0

cyclopentanone:

**Species** Rabbit Result Skin irritation

zinc powder — zinc dust (stabilised):

**Species** 

Assessment No skin irritation Result No skin irritation

n-butyl acetate:

**Species** Rabbit

Assessment No skin irritation

Method OECD Test Guideline 404

Result Repeated exposure may cause skin dryness or cracking.

dimethyl ether:

Assessment No skin irritation Result No skin irritation

aluminium powder (stabilised):

**Species** Rabbit

Assessment No skin irritation No skin irritation Result

Serious eye damage/eye irritation

**Product:** 

Remarks Irritating to eyes.

**Components:** 

butanone:

**Species** Rabbit

Irritating to eyes. Assessment

Method OECD Test Guideline 405

Result Irritating to eyes.

acetone:

**Species** Rabbit Result Eye irritation

cyclopentanone:

**Species** Rabbit Result Eye irritation



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



Print Date:

**OKS 2561** 

Version Revision Date: Date of last issue: -

1.0 16.09.2024 Date of first issue: 16.09.2024 17.09.2024

zinc powder — zinc dust (stabilised):

Species : Rabbit Exposure time : 24 h

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

GLP : yes

n-butyl acetate:

Species : Rabbit

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

GLP : yes

dimethyl ether:

Assessment : No eye irritation Result : No eye irritation

aluminium powder (stabilised):

Species : Rabbit

Assessment : No eye irritation Result : No eye irritation

Respiratory or skin sensitisation

**Product:** 

Remarks : This information is not available.

**Components:** 

butanone:

Test Type : Buehler Test Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

GLP : yes

zinc powder - zinc dust (stabilised):

Species : Guinea pig

Assessment : Did not cause sensitisation on laboratory animals.

Method : OECD Test Guideline 406

Result : Did not cause sensitisation on laboratory animals.

GLP : yes

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



Print Date:

**OKS 2561** 

Version Revision Date: Date of last issue: -

1.0 16.09.2024 Date of first issue: 16.09.2024 17.09.2024

n-butyl acetate:

Test Type : Maximisation Test

Exposure routes : Dermal Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

dimethyl ether:

Assessment : Does not cause skin sensitisation. Result : Does not cause skin sensitisation.

aluminium powder (stabilised):

Species : Guinea pig

Assessment : Did not cause sensitisation on laboratory animals. Result : Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

**Product:** 

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

**Components:** 

butanone:

Germ cell mutagenicity-

Assessment

Tests on bacterial or mammalian cell cultures did not show

mutagenic effects.

zinc powder — zinc dust (stabilised):

Germ cell mutagenicity-

Assessment

Tests on bacterial or mammalian cell cultures did not show

mutagenic effects.

n-butyl acetate:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Test system: Chinese hamster cells Method: OECD Test Guideline 473

Result: negative



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



**OKS 2561** 

Version Revision Date: Date of last issue: - Print Date: 1.0 16.09.2024 Date of first issue: 16.09.2024 17.09.2024

Genotoxicity in vivo : Species: Mouse

Application Route: Oral

Method: OECD Test Guideline 474

Result: negative

Germ cell mutagenicity-

Assessment

Tests on bacterial or mammalian cell cultures did not show

mutagenic effects., Animal testing did not show any mutagenic

effects.

dimethyl ether:

Genotoxicity in vitro : Test Type: Ames test

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Species: Drosophila melanogaster (vinegar fly)

Application Route: inhalation (gas) Method: OECD Test Guideline 477

Result: negative

Carcinogenicity

**Product:** 

Remarks : No data available

**Components:** 

butanone:

Carcinogenicity - Assessment

: Not classifiable as a human carcinogen.

zinc powder — zinc dust (stabilised):

Carcinogenicity -

Assessment

: No evidence of carcinogenicity in animal studies.

n-butyl acetate:

Carcinogenicity -

: Not classifiable as a human carcinogen.

Assessment

dimethyl ether:

Species : Rat

Application Route : inhalation (gas) Exposure time : 2 Years

: 47 mg/l

Method : OECD Test Guideline 453

Result : negative

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



**OKS 2561** 

Version Revision Date: Date of last issue: - Print Date: 1.0 16.09.2024 Date of first issue: 16.09.2024 17.09.2024

Reproductive toxicity

**Product:** 

Effects on fertility : Remarks: No data available

Effects on foetal development

: Remarks: No data available

**Components:** 

butanone:

Reproductive toxicity - : - Fertility -

Assessment

No toxicity to reproduction

- Teratogenicity -

No effects on or via lactation

zinc powder - zinc dust (stabilised):

Reproductive toxicity - : - Fertility -

Assessment

No toxicity to reproduction

- Teratogenicity -

No effects on or via lactation

n-butyl acetate:

Effects on fertility : Test Type: Two-generation study

Species: Rat

Application Route: inhalation (vapour)
General Toxicity - Parent: NOAEC: 750 mg/l
General Toxicity F1: NOAEC: 750 mg/l
General Toxicity F2: NOAEC: 750 mg/l
Method: OECD Test Guideline 416

Result: Embryotoxic effects and adverse effects on the

offspring were detected.

Reproductive toxicity -

- Fertility -

Assessment

No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.

- Teratogenicity -

No toxicity to reproduction

dimethyl ether:

Reproductive toxicity -

- Fertility -

Assessment

Animal testing did not show any effects on fertility.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



**OKS 2561** 

Version Revision Date: Date of last issue: - Print Date: 1.0 16.09.2024 Date of first issue: 16.09.2024 17.09.2024

STOT - single exposure

**Product:** 

Remarks : No data available

**Components:** 

butanone:

Exposure routes : Inhalation

Target Organs : Respiratory system

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 3 with narcotic effects.,

May cause drowsiness or dizziness.

acetone:

Exposure routes : Inhalation

Assessment : May cause drowsiness or dizziness.

n-butyl acetate:

Exposure routes : Inhalation

Target Organs : Central nervous system

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

**Product:** 

Remarks : No data available

Components:

butanone:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

n-butyl acetate:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Repeated dose toxicity

**Product:** 

Remarks : This information is not available.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



**OKS 2561** 

Version Date of last issue: -Revision Date:

Print Date: 16.09.2024 Date of first issue: 16.09.2024 17.09.2024 1.0

#### Components:

n-butyl acetate:

**Species** Rat NOAEL 125 mg/kg **Application Route** Oral

#### **Aspiration toxicity**

#### **Product:**

This information is not available.

#### **Components:**

#### butanone:

No aspiration toxicity classification

#### zinc powder — zinc dust (stabilised):

No aspiration toxicity classification

#### n-butyl acetate:

No aspiration toxicity classification

#### dimethyl ether:

No aspiration toxicity classification

#### 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### **Product:**

Assessment The substance/mixture does not contain components

> considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### **Further information**

**Product:** 

Remarks : Risks of irreversible effects after a single exposure.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



Print Date:

**OKS 2561** 

Version Revision Date: Date of last issue: -

1.0 16.09.2024 Date of first issue: 16.09.2024 17.09.2024

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

**Product:** 

Toxicity to fish : Remarks: Toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms

Remarks: No data available

#### **Components:**

butanone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.993 mg/l

Exposure time: 96 h Test Type: static test

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 308 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 1.972

ma/l

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

GLP: yes

Toxicity to microorganisms : EC50 (Pseudomonas putida): 1.150 mg/l

Exposure time: 16 h Test Type: static test Method: DIN 38 412 Part 8

#### zinc powder — zinc dust (stabilised):

Toxicity to fish : LC50 (Oncorhynchus kisutch (coho salmon)): 0,727 mg/l

Exposure time: 96 h Test Type: static test

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0,937 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

a brand of
FREUDENBERG

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



**OKS 2561** 

Version **Revision Date:** Date of last issue: -Print Date: 17.09.2024 1.0 16.09.2024 Date of first issue: 16.09.2024

M-Factor (Acute aquatic

toxicity)

: 1

M-Factor (Chronic aquatic

toxicity)

**Ecotoxicology Assessment** 

Acute aquatic toxicity Very toxic to aquatic life.

Chronic aquatic toxicity Very toxic to aquatic life with long lasting effects.

n-butyl acetate:

LC50 (Pimephales promelas (fathead minnow)): 18 mg/l Toxicity to fish

Exposure time: 96 h

Test Type: flow-through test

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia (water flea)): 44 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): 397 mg/l

Exposure time: 72 h Test Type: static test

EC50 (Tetrahymena pyriformis): 356 mg/l Toxicity to microorganisms

> Exposure time: 40 h Test Type: Growth inhibition

Toxicity to daphnia and other :

aquatic invertebrates

(Chronic toxicity)

NOEC: 23 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: Reproduction Test

GLP: yes

dimethyl ether:

Toxicity to fish LC50 (Poecilia reticulata (guppy)): > 4.100 mg/l

> Exposure time: 96 h Test Type: semi-static test

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 4.400 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae/aquatic

plants

EC50 (green algae): 154,9 mg/l

Exposure time: 96 h

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



**OKS 2561** 

Version Date of last issue: -Revision Date: Print Date: 16.09.2024 Date of first issue: 16.09.2024 17.09.2024 1.0

aluminium powder (stabilised):

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 0,12 mg/l

Exposure time: 96 h Test Type: static test

Remarks: No toxicity at the limit of solubility

**Ecotoxicology Assessment** 

Acute aquatic toxicity This product has no known ecotoxicological effects.

Chronic aquatic toxicity This product has no known ecotoxicological effects.

12.2 Persistence and degradability

**Product:** 

Remarks: No data available Biodegradability

Physico-chemical

removability

Remarks: No data available

**Components:** 

butanone:

Biodegradability Test Type: aerobic

Inoculum: activated sludge Result: rapidly biodegradable Biodegradation: 98 %

Exposure time: 28 d

Method: OECD Test Guideline 301D

GLP: yes

acetone:

Biodegradability Result: rapidly biodegradable

cyclopentanone:

Biodegradability Result: rapidly biodegradable

n-butyl acetate:

Test Type: Primary biodegradation Biodegradability

> Result: rapidly biodegradable Biodegradation: 83 % Exposure time: 28 d

Method: OECD Test Guideline 301D

dimethyl ether:

Biodegradability Test Type: aerobic

Inoculum: activated sludge

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



**OKS 2561** 

Version Revision Date: Date of last issue: - Print Date: 1.0 16.09.2024 Date of first issue: 16.09.2024 17.09.2024

Result: Not readily biodegradable.

Biodegradation: 5 % Exposure time: 28 d

Method: OECD Test Guideline 301D

12.3 Bioaccumulative potential

**Product:** 

Bioaccumulation : Remarks: No data available

**Components:** 

butanone:

Bioaccumulation : Remarks: Due to the distribution coefficient n-octanol/water,

accumulation in organisms is not expected.

Partition coefficient: n-

octanol/water

log Pow: 0,3 (40 °C)

Method: OECD Test Guideline 117

GLP: yes

acetone:

Bioaccumulation : Remarks: Does not bioaccumulate.

Partition coefficient: n-

octanol/water

log Pow: 0,2

cyclopentanone:

Bioaccumulation : Remarks: No data available

n-butyl acetate:

Partition coefficient: n-

log Pow: 2,3 (25 °C)

octanol/water

pH: 7 Method: OECD Test Guideline 117

GLP: yes

dimethyl ether:

Partition coefficient: n-

octanol/water

log Pow: 0,07 (25 °C)

12.4 Mobility in soil

**Product:** 

Mobility : Remarks: No data available

Distribution among

environmental compartments

Remarks: No data available



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



Print Date:

**OKS 2561** 

Version Revision Date: Date of last issue: -

1.0 16.09.2024 Date of first issue: 16.09.2024 17.09.2024

#### 12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

**Components:** 

butanone:

Assessment : Non-classified PBT substance. Non-classified vPvB substance

n-butyl acetate:

Assessment : Non-classified PBT substance. Non-classified vPvB substance

dimethyl ether:

Assessment : Non-classified vPvB substance. Non-classified PBT substance

# 12.6 Endocrine disrupting properties

**Product:** 

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:** 

Additional ecological

information

: Toxic to aquatic life with long lasting effects.

# **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Waste codes should be assigned by the user based on the

application for which the product was used.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



**OKS 2561** 

Version Revision Date: Date of last issue: - Print Date: 1.0 16.09.2024 Date of first issue: 16.09.2024 17.09.2024

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Offer empty spray cans to an established disposal company. Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied

16 05 04\*\*, gases in pressure containers (including halons)

containing hazardous substances

### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

#### 14.4 Packing group

**ADR** 

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

**RID** 

Packing group : Not assigned by regulation

Classification Code : 5F

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



Print Date:

**OKS 2561** 

Version Revision Date: Date of last issue: -

1.0 16.09.2024 Date of first issue: 16.09.2024 17.09.2024

Hazard Identification Number : 23 Labels : 2.1

**IMDG** 

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo :

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

203

Labels : Flammable Gas

IATA (Passenger)

Packing instruction : 203

(passenger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

**IMDG** 

Marine pollutant : yes

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

#### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)  Conditions of restriction for the following entries should be considered:

Number on list 75

If you intend to use this product as tattoo ink, please contact your vendor.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



**OKS 2561** 

Version Date of last issue: -Revision Date: Print Date: 17.09.2024 1.0 16.09.2024 Date of first issue: 16.09.2024

zinc powder — zinc dust (stabilised)

(Number on list 75)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

(EU SVHC)

This product does not contain substances of very high concern

(Regulation (EC) No

1907/2006 (REACH), Article 57).

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

(EC 1005/2009)

Not applicable

Regulation (EU) 2019/1021 on persistent organic

pollutants (recast)

(EU POP)

Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and

import of dangerous chemicals

(EU PIC)

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

(EU. REACH-Annex XIV)

: Not applicable

Regulation (EU) 2019/1148 on the marketing and use of : acetone (ANNEX II)

explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant

disappearances and thefts should be reported to the

relevant national contact point.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous

substances.

P3a FLAMMABLE AEROSOLS

E2 **ENVIRONMENTAL HAZARDS** 

P<sub>5</sub>c



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



**OKS 2561** 

VersionRevision Date:Date of last issue: -Print Date:1.016.09.2024Date of first issue: 16.09.202417.09.2024

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 84,18 %

#### Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

#### 15.2 Chemical safety assessment

This information is not available.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H220 : Extremely flammable gas.

H225 : Highly flammable liquid and vapour. H226 : Flammable liquid and vapour.

H228 : Flammable solid.

H280 : Contains gas under pressure; may explode if heated.

H315 : Causes skin irritation.

H319 : Causes serious eye irritation.H336 : May cause drowsiness or dizziness.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

#### Full text of other abbreviations

Note T : This substance may be marketed in a form which does not

have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this

Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s)

shall be included in the safety data sheet.

Note U (table 3.1) : When put on the market gases have to be classified as



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



**OKS 2561** 

Version Revision Date: Date of last issue: - Print Date: 1.0 16.09.2024 Date of first issue: 16.09.2024 17.09.2024

"Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a

fifth list of indicative occupational exposure limit values

ES VLA : Spain. Environmental Limits for exposure to Chemical agents

- Table 1: Occupational Exposure Values

ES VLB : Occupational Exposure Limits for Chemical Agents in Spain -

Biological Exposure Values

2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit
2019/1831/EU / TWA : Limit Value - eight hours
2019/1831/EU / STEL : Short term exposure limit
ES VLA / VLA-ED : Environmental Daily Limit Value

ES VLA / VLA-ED : Environmental Daily Limit Value ES VLA / VLA-EC : Environmental Short Term Value

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention: PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 - ES



#### **OKS 2561**

VersionRevision Date:Date of last issue: -Print Date:1.016.09.2024Date of first issue: 16.09.202417.09.2024

Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

#### Classification of the mixture: Classification procedure:

Aerosol 1 H222, H229 Based on product data or assessment
Eye Irrit. 2 H319 Calculation method
STOT SE 3 H336 Calculation method
Aquatic Chronic 2 H411 Calculation method

|| Relevant changes compared to the last edition are highlighted at the left margin. This version replaces all previous editions.

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.

