



# **OKS 2901 Belt Tuning, Spray**



# Description

OKS 2901 is a clean, light-coloured film for increasing tensile strength and car of many kinds of belts.

# **Applications**

- Increases tensile force by up to 50 % for all kinds of V-belts, round and flat belts on fans, compressors, pumps, ventilators, • Prevents squeaking mills etc.
- Protects against drying out and wear, prevents belt squeaking and slip

# Advantages and benefits

- · Increases service life
- Prevents slip
- Increases belt tension force

# **Branches**

- Logistics
- · Iron and steel industry
- · Rubber and plastic processing
- · Glass and foundry industry
- · Shipbuilding and marine technology
- Paper and packaging industry
- Chemical industry
- Rail vehicle technology
- · Maintenance and servicing
- Plant and machine (tool) engineering •
- Municipal services

# **Application tips**

For optimum results clean belt carefully, best way is to clean mechanically first and then with Universal Cleaner OKS 2610/2611. Spray evenly on the belt. Let product take effect for approx. 30 min. before use. If necessary, repeat application. Belts made of SBR and CR are not compatible to OKS 2901.

#### Packaging

400 ml Spray











# **OKS 2901** Belt Tuning, Spray

#### **Technical data**

|                              | Standard   | Conditions | Unit  | Value                          |
|------------------------------|------------|------------|-------|--------------------------------|
| Main components              |            |            |       |                                |
| base oil                     |            |            |       | adhesive oil                   |
| solvent                      |            |            |       | special boiling point gasoline |
| Application related technica | al data    |            |       |                                |
| upper operating temperature  |            |            | °C    | 80                             |
| colour                       |            |            |       | yellowish                      |
| density (at 20°C)            | DIN 51 757 |            | g/cm³ | 0.7                            |
| Properties and approvals     |            |            |       |                                |
| UFI                          |            |            |       | 44M1-W0SA-Q00U-CC06            |

# **OKS Spezialschmierstoffe GmbH**

Ganghoferstraße 47 82216 Maisach **\$** +49 8142 3051 - 500 ⊠ info@oks-germany.com **d** www.oks-germany.com



The information in this publication reflects state-of-the-art technology, as well as extensive testing and experience. Due to the diversity of possible applications and technical realities, they can only serve as recommendations and are not arbitrarily transferable. Therefore, no obligations, liability or warranty claims can be derived from them. We only accept liability for the suitability of our products for particular purposes, and for certain properties of our products, in the event that we have accepted such liability in writing in the individual case. Any case of justified warranty claims shall be limited to the delivery of replacement goods free of defects, in the event that this subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular the liability for consequential injuries or damage, shall always be excluded. Prior to use, the customer must conduct its own testing to prove suitability. The data are subject to change for the sake of progress. <sup>®</sup> = Registered trademark

Product restricted to professional users. Safety data sheet available for download at www.oks-germany.com Our Customer and Technical service will be pleased to help should you have any further questions.





