

OKS 2801

Leak Detector, Spray



Description

Leak detector for locating of leaks on lines, apparatuses and containers under internal pressure.

Applications

- Piping and hoses, for example steel bottles, compressors, breathing devices, oxyacetylene gas and inert-gas arc welding devices and burners
- Fittings, flanges, valves, screwed connections, soldered and welded connections of pressure gas systems and lines
- Suitable for compressed air, refrigerant, acetylene, butane, natural gas, carbon dioxide, gaseous oxygen, propane, town gas, nitrogen, hydrogen and, ammonia

Advantages and benefits

- Acts non-corrosive
- Allows direct visual inspection of the leakage point through bubble formation
- Tested by the DVGW in accordance with DIN EN 14291
- Suitable for spraying overhead

Branches

- Paper and packaging industry
- Shipbuilding and marine technology
- Rail vehicle technology
- Rubber and plastic processing
- Glass and foundry industry
- Municipal services
- Maintenance and servicing
- Plant and machine (tool) engineering
- Logistics
- Iron and steel industry
- Chemical industry

Application tips

Spray OKS 2801 on. A leak is indicated by the formation of foam bubbles. Caution: When using on polyamide lines, wash off with water after the test. Protect packaging against frost.

Packaging

- 400 ml Spray



OKS 2801 Leak Detector, Spray

a product brand of **KLÜBER**
LUBRICATION

Technical data

	Standard	Conditions	Unit	Value
Main components				
basis				water
additives				corrosion protection
additives				active ingredients
Application related technical data				
lower operating temperature	DIN 51 805		°C	> 0
upper operating temperature	DIN 51 821-2		°C	50
colour				transparent
density	DIN EN ISO 3838	at 20°C	g/cm ³	1.02
Properties and approvals				
UFI				E6AE-C0R5-000Q-T1C1
DVGW approval	DIN EN 14 291			Reg.-Nr. NG-5170CM208

Klüber Lubrication München GmbH & Co. KG
Geisenhausenerstraße 7 / 81379 München /
Germany / phone +49 89 7876-0

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.