

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version	Revision Date:	Date of last issue: 30.01.2025	Print Date:
3.0	26.06.2026	Date of first issue: 22.06.2016	26.06.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 2101

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Anticorrosion additive

Recommended restrictions on use : Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH
Ganghoferstr. 47
82216 Maisach
Germany
Tel.: +49 8142 3051-500
info@oks-germany.com

E-mail address of person responsible for the SDS : mcm@oks-germany.com

National contact : Klüber Lubrication France S.A.S.
Z.I. des Auréats, 10 à 16 Allée Ducretet
26014 Valence Cedex
France
+33-4-75448426
Fax: +33-4-75449336
KLF.contact@fr.klueber.com

1.4 Emergency telephone number

Emergency telephone number : +33 1 45 42 59 59 ORFILA
+33 1 72 11 00 03 NCEC
+49 8142 3051 517

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

Skin irritation, Category 2	H315: Causes skin irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	   														
Signal word	:	Danger														
Hazard statements	:	<table><tr><td>H222</td><td>Extremely flammable aerosol.</td></tr><tr><td>H229</td><td>Pressurised container: May burst if heated.</td></tr><tr><td>H304</td><td>May be fatal if swallowed and enters airways.</td></tr><tr><td>H315</td><td>Causes skin irritation.</td></tr><tr><td>H336</td><td>May cause drowsiness or dizziness.</td></tr><tr><td>H411</td><td>Toxic to aquatic life with long lasting effects.</td></tr></table>	H222	Extremely flammable aerosol.	H229	Pressurised container: May burst if heated.	H304	May be fatal if swallowed and enters airways.	H315	Causes skin irritation.	H336	May cause drowsiness or dizziness.	H411	Toxic to aquatic life with long lasting effects.		
H222	Extremely flammable aerosol.															
H229	Pressurised container: May burst if heated.															
H304	May be fatal if swallowed and enters airways.															
H315	Causes skin irritation.															
H336	May cause drowsiness or dizziness.															
H411	Toxic to aquatic life with long lasting effects.															
Precautionary statements	:	Prevention: <table><tr><td>P210</td><td>Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</td></tr><tr><td>P211</td><td>Do not spray on an open flame or other ignition source.</td></tr><tr><td>P251</td><td>Do not pierce or burn, even after use.</td></tr><tr><td>P273</td><td>Avoid release to the environment.</td></tr></table> Response: <table><tr><td>P301 + P310</td><td>IF SWALLOWED: Immediately call a POISON CENTER/ doctor.</td></tr><tr><td>P331</td><td>Do NOT induce vomiting.</td></tr></table> Storage: <table><tr><td>P410 + P412</td><td>Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.</td></tr></table>	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	P211	Do not spray on an open flame or other ignition source.	P251	Do not pierce or burn, even after use.	P273	Avoid release to the environment.	P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.	P331	Do NOT induce vomiting.	P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.															
P211	Do not spray on an open flame or other ignition source.															
P251	Do not pierce or burn, even after use.															
P273	Avoid release to the environment.															
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.															
P331	Do NOT induce vomiting.															
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.															

Hazardous components which must be listed on the label:

pentane

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

|| Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics

|| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

|| Hydrocarbons, C9-C11, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Active substance with propellant
Solvent

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
pentane	109-66-0 203-692-4 601-006-00-1 01-2119459286-30-XXXX	Flam. Liq. 2; H225 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	Note C	>= 10 - < 20

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

propane	74-98-6 200-827-9 601-003-00-5 01-2119486944-21-XXXX	Flam. Gas 1; H220 Press. Gas Compr. Gas; H280	Note U (Table 3)	$\geq 10 - < 20$
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	918-167-1 01-2119472146-39-XXXX	Flam. Liq. 3; H226 Asp. Tox. 1; H304 EUH066	Note P	$\geq 1 - < 10$
isobutane	75-28-5 200-857-2 601-004-00-0 01-2119485395-27-XXXX	Flam. Gas 1A; H220 Press. Gas Compr. Gas; H280	Note U (Table 3), Note C	$\geq 1 - < 10$
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	919-857-5 01-2119463258-33-XXXX	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304	Note P	$\geq 1 - < 10$
Hydrocarbons, C9-C11, isoalkanes, cyclics, <2% aromatics	920-134-1 01-2119480153-44-XXXX	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	Note P	$\geq 2,5 - < 10$
Hydrocarbons, C6, isoalkanes, <5% n-hexane	931-254-9 01-2119484651-34-XXXX	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	Note P	$\geq 2,5 - < 10$
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	926-605-8 01-2119486291-36-XXXX	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	Note P	$\geq 2,5 - < 10$
cyclohexane	110-82-7 203-806-2	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336	M-Factor: 1/1	$\geq 2,5 - < 10$

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

	601-017-00-1	(Central nervous system) Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410		
2-butoxyethanol	111-76-2 203-905-0 603-014-00-0 01-2119475108-36-XXXX	Acute Tox. 4; H302 Acute Tox. 3; H331 Skin Irrit. 2; H315 Eye Irrit. 2; H319	ATE (Oral): 1.200 mg/kg ATE (Inhalation): 3 mg/l	$\geq 1 - < 10$
n-hexane	110-54-3 203-777-6 601-037-00-0	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361f STOT SE 3; H336 (Central nervous system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	 **, ***	$\geq 0,25 - < 1$
Substances with a workplace exposure limit :				
butane	106-97-8 203-448-7 601-004-00-0 01-2119474691-32-XXXX	Flam. Gas 1; H220 Press. Gas Compr. Gas; H280	Note U (Table 3), Note C, Note S	$\geq 30 - < 50$
Paraffin waxes and Hydrocarbon waxes	8002-74-2 232-315-6	Not classified		$\geq 1 - < 10$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Call a physician or poison control centre immediately.
Remove person to fresh air. If signs/symptoms continue, get medical attention.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact : Take off all contaminated clothing immediately.
Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
Wash off immediately with plenty of water.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
If eye irritation persists, consult a specialist.

If swallowed : Move the victim to fresh air.
If accidentally swallowed obtain immediate medical attention.
Keep respiratory tract clear.
Do NOT induce vomiting.
Rinse mouth with water.
Aspiration hazard if swallowed - can enter lungs and cause damage.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Aspiration may cause pulmonary oedema and pneumonitis.

Inhalation may provoke the following symptoms:

Unconsciousness

Dizziness

Drowsiness

Headache

Nausea

Tiredness

Skin contact may provoke the following symptoms:

Erythema

Risks : May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause drowsiness or dizziness.

Central nervous system depression

Risk of product entering the lungs on vomiting after ingestion.

Health injuries may be delayed.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version	Revision Date:	Date of last issue: 30.01.2025	Print Date:
3.0	26.06.2026	Date of first issue: 22.06.2016	26.06.2026

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Fire Hazard
Do not let product enter drains.
Contains gas under pressure; may explode if heated.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion products : Carbon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not breathe vapours or spray mist.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Refer to protective measures listed in sections 7 and 8.
Only qualified personnel equipped with suitable protective equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version	Revision Date:	Date of last issue: 30.01.2025	Print Date:
3.0	26.06.2026	Date of first issue: 22.06.2016	26.06.2026

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.
Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not use in areas without adequate ventilation.
Do not breathe vapours or spray mist.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Keep away from fire, sparks and heated surfaces.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
Do not get in eyes or mouth or on skin.
Do not get on skin or clothing.
Do not ingest.
Do not use sparking tools.
These safety instructions also apply to empty packaging which may still contain product residues.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular national regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
butane	106-97-8	VME	800 ppm 1.900 mg/m3	FR VLE (2005-02-01)
Further information: Permissible limit values (circular)				
pentane	109-66-0	TWA	1.000 ppm 3.000 mg/m3	2006/15/EC (2006-02-09)
Further information: Indicative				
		VME	1.000 ppm 3.000 mg/m3	FR VLE (2012-07-01)
Further information: Regulatory binding exposure limits				
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	Not Assigned	VME (Vapour)	1.000 mg/m3	FR VLE (2016-10-01)
Further information: Permissible limit values (circular)				
		VLCT (VLE) (Vapour)	1.500 mg/m3	FR VLE (2016-10-01)
Further information: Permissible limit values (circular)				
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not Assigned	VME (Vapour)	1.000 mg/m3	FR VLE (2016-10-01)
Further information: Permissible limit values (circular)				
		VLCT (VLE) (Vapour)	1.500 mg/m3	FR VLE (2016-10-01)
Further information: Permissible limit values (circular)				
Hydrocarbons, C9-C11, isoalkanes, cyclics, <2% aromatics	Not Assigned	VME (Vapour)	1.000 mg/m3	FR VLE (2016-10-01)
Further information: Permissible limit values (circular)				
		VLCT (VLE) (Vapour)	1.500 mg/m3	FR VLE (2016-10-01)
Further information: Permissible limit values (circular)				
cyclohexane	110-82-7	TWA	200 ppm 700 mg/m3	2006/15/EC (2006-02-09)
Further information: Indicative				
		VME	200 ppm 700 mg/m3	FR VLE (2012-07-01)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

	Further information: Regulatory binding exposure limits			
		VLCT (VLE)	375 ppm 1.300 mg/m3	FR VLE (2012-07-01)
	Further information: Permissible limit values (circular)			
Paraffin waxes and Hydrocarbon waxes	8002-74-2	VME (Fumes)	2 mg/m3	FR VLE (2012-05-10)
	Further information: Permissible limit values (circular)			
2-butoxyethanol	111-76-2	TWA	20 ppm 98 mg/m3	2000/39/EC (1991-07-05)
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	50 ppm 246 mg/m3	2000/39/EC (1991-07-05)
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		VLCT (VLE)	50 ppm 246 mg/m3	FR VLE (2012-07-01)
	Further information: Risk of penetration through skin, Regulatory binding exposure limits			
		VME	10 ppm 49 mg/m3	FR VLE (2012-07-01)
	Further information: Risk of penetration through skin, Regulatory binding exposure limits			
n-hexane	110-54-3	TWA	20 ppm 72 mg/m3	2006/15/EC (2006-02-09)
	Further information: Indicative			
		VME	20 ppm 72 mg/m3	FR VLE (2012-07-01)
	Further information: Reprotoxic category 2 - Possibly reprotoxic to humans, Regulatory binding exposure limits			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
pentane	Workers	Inhalation	Long-term systemic effects	3000 mg/m3
	Workers	Skin contact	Long-term systemic effects	432 mg/kg
Hydrocarbons, C6, isoalkanes, <5% n-hexane	Workers	Inhalation	Acute systemic effects	1286,4 mg/m3
	Workers	Inhalation	Long-term local effects	837,5 mg/m3
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	Workers	Inhalation	Acute systemic effects	1286,4 mg/m3
	Workers	Inhalation	Long-term local effects	837,5 mg/m3
2-butoxyethanol	Workers	Inhalation	Long-term systemic	98 mg/m3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version
3.0

Revision Date:
26.06.2026

Date of last issue: 30.01.2025
Date of first issue: 22.06.2016

Print Date:
26.06.2026

			effects	
	Workers	Inhalation	Acute systemic effects	1091 mg/m ³
	Workers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	89 mg/kg bw/day
	Workers	Inhalation	Acute local effects	246 mg/m ³
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	Workers	Inhalation	Long-term systemic effects	871 mg/m ³
	Workers	Dermal	Long-term systemic effects	77 mg/kg
Hydrocarbons, C9-C11, isoalkanes, cyclics, <2% aromatics	Workers	Inhalation	Long-term systemic effects	871 mg/m ³
	Workers	Dermal	Long-term systemic effects	77 mg/kg
cyclohexane	Workers	Inhalation	Long-term systemic effects	700 mg/m ³
	Workers	Skin contact	Long-term systemic effects	2016 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
2-butoxyethanol	Fresh water	8,8 mg/l
	Marine water	0,88 mg/l
	Sewage treatment plant	463 mg/l
	Fresh water sediment	34,6 mg/kg
	Marine sediment	3,46 mg/kg
	Soil	2,33 mg/kg
	Intermittent use/release	26,4 mg/l
cyclohexane	Fresh water	0,0447 mg/l
	Marine water	0,00447 mg/l
	Sewage treatment plant	3,24 mg/l
	Fresh water sediment	3,6 mg/kg
	Marine sediment	0,36 mg/kg
	Soil	0,694 mg/kg

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye/face protection : Safety glasses with side-shields

Hand protection
Material : Nitrile rubber

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.
The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Short term only

Filter type : Filter type A-P

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Environmental exposure controls

Air : Should not be released into the environment.
Soil : Do not allow contact with soil, surface or ground water.
The product should not be allowed to enter drains, water courses or the soil.
Water : Do not allow contact with soil, surface or ground water.
The product should not be allowed to enter drains, water courses or the soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : aerosol

Colour : yellow

Odour : characteristic

Odour Threshold : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

Melting point/ range : No data available

Boiling point/boiling range : -161 °C (1.013 hPa)

Flammability : Flammability (solid, gas):
Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 9,4 %(V)

Lower explosion limit / Lower flammability limit : 0,6 %(V)

Flash point : 0 °C
Method: Abel-Pensky

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable
substance/mixture is non-soluble (in water)

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : < 20,5 mm²/s (40 °C)

Solubility(ies)
Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

Vapour pressure	:	8.327 hPa (20 °C)
Relative density	:	0,638 (20 °C) Reference substance: Water The value is calculated
Density	:	0,64 g/cm ³ (20 °C)
Bulk density	:	No data available
Relative vapour density	:	No data available
Particle characteristics Particle size	:	No data available

9.2 Other information

Explosives	:	Not explosive
Oxidizing properties	:	No data available
Self-ignition	:	No data available
Metal corrosion rate	:	Not corrosive to metals
Evaporation rate	:	No data available
Sublimation point	:	No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.
Strong sunlight for prolonged periods.
Risk of receptacle bursting.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.

Symptoms: Inhalation may provoke the following symptoms:
Respiratory disorder, Dizziness, Drowsiness, Vomiting,
Fatigue, Vertigo, Central nervous system depression

Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Method: Calculation method

Acute dermal toxicity : Symptoms: Redness, Local irritation

Components:

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5,6 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.200 mg/kg
Method: OECD Test Guideline 402

Remarks: Prolonged or repeated skin contact with liquid may cause defatting resulting in drying, redness and possible blistering.

Symptoms: Skin disorders

isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: gas

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity
Remarks: No mortality observed at this dose.

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
Remarks: No mortality observed at this dose.

Hydrocarbons, C9-C11, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity
Remarks: No mortality observed at this dose.

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
Remarks: No mortality observed at this dose.

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

cyclohexane:

Acute oral toxicity : LD50 Oral: > 5.000 mg/kg
Method: OECD Test Guideline 401

2-butoxyethanol:

Acute oral toxicity : Acute toxicity estimate: 1.200 mg/kg
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

LD50 (Guinea pig): 1.414 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l
Test atmosphere: vapour
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

LC50: 3 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The component/mixture is toxic after short term
inhalation.

Acute dermal toxicity : LD50 (Guinea pig): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal
toxicity

n-hexane:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 259,35 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal
toxicity

butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: gas

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

Paraffin waxes and Hydrocarbon waxes:

Acute oral toxicity	: LD50 (Rat): > 5.000 mg/kg Method: OECD Test Guideline 420 GLP: yes Assessment: The substance or mixture has no acute oral toxicity
Acute dermal toxicity	: LD50 (Rabbit): > 2.000 mg/kg Method: OECD Test Guideline 402 GLP: yes Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : This information is not available.

Components:

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Result : Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species	: Rabbit
Assessment	: No skin irritation
Method	: OECD Test Guideline 404
Result	: No skin irritation
GLP	: yes
Remarks	: Based on data from similar materials

Hydrocarbons, C9-C11, isoalkanes, cyclics, <2% aromatics:

Species	: Rabbit
Assessment	: No skin irritation
Method	: OECD Test Guideline 404
Result	: No skin irritation
GLP	: yes
Remarks	: Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Result : Skin irritation

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

Species	: Rabbit
Result	: Skin irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version	Revision Date:	Date of last issue:	Print Date:
3.0	26.06.2026	30.01.2025 Date of first issue: 22.06.2016	26.06.2026

cyclohexane:

Result : Skin irritation

2-butoxyethanol:

Species : Rabbit
Assessment : Irritating to skin.
Result : Irritating to skin.

n-hexane:

Species : Rabbit
Assessment : Irritating to skin.
Method : OECD Test Guideline 404
Result : Irritating to skin.

Paraffin waxes and Hydrocarbon waxes:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Product:

Remarks : This information is not available.

Components:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes
Remarks : Based on data from similar materials

Hydrocarbons, C9-C11, isoalkanes, cyclics, <2% aromatics:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes
Remarks : Based on data from similar materials

2-butoxyethanol:

Species : Rabbit

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version	Revision Date:	Date of last issue: 30.01.2025	Print Date:
3.0	26.06.2026	Date of first issue: 22.06.2016	26.06.2026

Assessment : Irritating to eyes.
Result : Irritating to eyes.

n-hexane:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation

Paraffin waxes and Hydrocarbon waxes:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Product:

Remarks : This information is not available.

Components:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Test Type : Maximisation Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Result : Not a skin sensitizer.
GLP : yes

Remarks : Based on data from similar materials

Hydrocarbons, C9-C11, isoalkanes, cyclics, <2% aromatics:

Test Type : Maximisation Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Result : Not a skin sensitizer.
GLP : yes

Remarks : Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

2-butoxyethanol:

Test Type	: Maximisation Test
Species	: Guinea pig
Assessment	: Did not cause sensitisation on laboratory animals.
Result	: Did not cause sensitisation on laboratory animals.

n-hexane:

Species	: Mouse
Assessment	: Does not cause skin sensitisation.
Result	: Does not cause skin sensitisation.

Paraffin waxes and Hydrocarbon waxes:

Test Type	: Maximisation Test
Species	: Guinea pig
Assessment	: Does not cause skin sensitisation.
Method	: OECD Test Guideline 406
Result	: Does not cause skin sensitisation.
GLP	: yes

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Germ cell mutagenicity- Assessment	: Weight of evidence does not support classification as a germ cell mutagen.
---------------------------------------	---

Hydrocarbons, C9-C11, isoalkanes, cyclics, <2% aromatics:

Germ cell mutagenicity- Assessment	: Weight of evidence does not support classification as a germ cell mutagen.
---------------------------------------	---

2-butoxyethanol:

Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative Remarks: In vitro tests did not show mutagenic effects
-----------------------	--

Genotoxicity in vivo	: Test Type: In vivo micronucleus test Species: Rat Method: OECD Test Guideline 474
----------------------	---

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

Result: negative

Germ cell mutagenicity-
Assessment : In vitro tests did not show mutagenic effects

Paraffin waxes and Hydrocarbon waxes:

Germ cell mutagenicity-
Assessment : In vitro tests did not show mutagenic effects

Carcinogenicity

Based on available data, the classification criteria are not met.

Product:

Remarks : No data available

Components:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Carcinogenicity -
Assessment : Weight of evidence does not support classification as a
carcinogen

Hydrocarbons, C9-C11, isoalkanes, cyclics, <2% aromatics:

Carcinogenicity -
Assessment : Weight of evidence does not support classification as a
carcinogen

2-butoxyethanol:

Carcinogenicity -
Assessment : Animal testing did not show any carcinogenic effects.

Paraffin waxes and Hydrocarbon waxes:

Carcinogenicity -
Assessment : Weight of evidence does not support classification as a
carcinogen

Reproductive toxicity

Based on available data, the classification criteria are not met.

Product:

Effects on fertility : Remarks: No data available

Effects on foetal
development : Remarks: No data available

Components:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Reproductive toxicity -
Assessment : - Fertility -

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

Weight of evidence does not support classification for reproductive toxicity

Hydrocarbons, C9-C11, isoalkanes, cyclics, <2% aromatics:

Reproductive toxicity -
Assessment

: - Fertility -

Weight of evidence does not support classification for reproductive toxicity

2-butoxyethanol:

Reproductive toxicity -
Assessment

: - Fertility -

No toxicity to reproduction
- Teratogenicity -

Animal testing did not show any effects on foetal development.

n-hexane:

Reproductive toxicity -
Assessment

: - Fertility -

Suspected human reproductive toxicant

Paraffin waxes and Hydrocarbon waxes:

Reproductive toxicity -
Assessment

: - Fertility -

No toxicity to reproduction

STOT - single exposure

May cause drowsiness or dizziness.

Product:

Remarks : No data available

Components:

pentane:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Exposure routes

: Inhalation

Assessment

: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

Hydrocarbons, C9-C11, isoalkanes, cyclics, <2% aromatics:

Exposure routes

: Inhalation

Assessment

: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version	Revision Date:	Date of last issue: 30.01.2025	Print Date:
3.0	26.06.2026	Date of first issue: 22.06.2016	26.06.2026

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

cyclohexane:

Exposure routes : Inhalation
Assessment : May cause drowsiness or dizziness.

2-butoxyethanol:

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

n-hexane:

Exposure routes : Inhalation
Target Organs : Central nervous system
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

Paraffin waxes and Hydrocarbon waxes:

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Product:

Remarks : No data available

Components:

2-butoxyethanol:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

n-hexane:

Exposure routes : Inhalation
Target Organs : Central nervous system
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Paraffin waxes and Hydrocarbon waxes:

Assessment : The substance or mixture is not classified as specific target

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

II organ toxicant, repeated exposure.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May be fatal if swallowed and enters airways.

Components:

pentane:

May be fatal if swallowed and enters airways.

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

May be fatal if swallowed and enters airways.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

May be fatal if swallowed and enters airways.

Hydrocarbons, C9-C11, isoalkanes, cyclics, <2% aromatics:

May be fatal if swallowed and enters airways.

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

May be fatal if swallowed and enters airways.

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

May be fatal if swallowed and enters airways.

cyclohexane:

May be fatal if swallowed and enters airways.

2-butoxyethanol:

No aspiration toxicity classification

n-hexane:

May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version	Revision Date:	Date of last issue: 30.01.2025	Print Date:
3.0	26.06.2026	Date of first issue: 22.06.2016	26.06.2026

Paraffin waxes and Hydrocarbon waxes:
No aspiration toxicity classification

11.2 Information on other hazards

Endocrine disrupting properties

Based on available data, the classification criteria are not met.

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

pentane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4,26 mg/l
End point: mortality
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2,7 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version	Revision Date:	Date of last issue:	Print Date:
3.0	26.06.2026	30.01.2025 Date of first issue: 22.06.2016	26.06.2026

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Toxicity to fish	: LL50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EL0 (Daphnia magna (Water flea)): 1.000 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	: EL50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l

Hydrocarbons, C9-C11, isoalkanes, cyclics, <2% aromatics:

Toxicity to fish	: LL50 (Oncorhynchus mykiss (rainbow trout)): 3,6 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): 22 - 46 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: EL50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l Exposure time: 24 h Method: OECD Test Guideline 201
Toxicity to microorganisms	: EL50 (Tetrahymena pyriformis): 0,868 mg/l Exposure time: 48 h

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l Exposure time: 48 h
---	---

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

cyclohexane:

Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 0,9 mg/l Exposure time: 48 h
M-Factor (Acute aquatic	: 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

toxicity)

M-Factor (Chronic aquatic toxicity) : 1

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

2-butoxyethanol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.474 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.550 mg/l
Exposure time: 48 h
Test Type: Immobilization
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 1.840 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 286 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: > 100 mg/l
Exposure time: 21 d
Species: Danio rerio (zebra fish)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 100 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: Reproduction Test
Method: OECD Test Guideline 211

n-hexane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 12,51 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 21,85 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 9,285 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

Exposure time: 72 h

Paraffin waxes and Hydrocarbon waxes:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10.000 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

Components:

pentane:

Biodegradability : Result: Readily biodegradable.

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Biodegradability : Result: Readily biodegradable.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Biodegradability : Result: Readily biodegradable.

Hydrocarbons, C9-C11, isoalkanes, cyclics, <2% aromatics:

Biodegradability : Result: Readily biodegradable.

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Biodegradability : Result: Not rapidly biodegradable

cyclohexane:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

Biodegradability : Result: Readily biodegradable.
Biodegradation: 77 %
Exposure time: 28 d

2-butoxyethanol:

Biodegradability : Test Type: aerobic
Result: rapidly biodegradable
Biodegradation: 90 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

n-hexane:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: rapidly biodegradable
Biodegradation: 21 %
Exposure time: 28 d
GLP: yes

Paraffin waxes and Hydrocarbon waxes:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
GLP: yes

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

pentane:

Bioaccumulation : Bioconcentration factor (BCF): 171

propane:

Partition coefficient: n-octanol/water : log Pow: 2,36

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Bioaccumulation : Remarks: No data available

Partition coefficient: n-octanol/water : Remarks: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

||

isobutane:

Partition coefficient: n-octanol/water : log Pow: 2,88
Method: OECD Test Guideline 107

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Bioaccumulation : Remarks: No data available

Partition coefficient: n-octanol/water : log Pow: 4

||

cyclohexane:

Bioaccumulation : Bioconcentration factor (BCF): 167

Partition coefficient: n-octanol/water : log Pow: 3,44 (20 °C)

2-butoxyethanol:

Bioaccumulation : Bioconcentration factor (BCF): 3,16

Partition coefficient: n-octanol/water : log Pow: 0,81 (25 °C)
Method: OECD Test Guideline 107

||

n-hexane:

Bioaccumulation : Bioconcentration factor (BCF): 501,19

Partition coefficient: n-octanol/water : log Pow: 4 (20 °C)
pH: 7

butane:

Partition coefficient: n-octanol/water : log Pow: 2,89
Method: OECD Test Guideline 107

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Components:

Paraffin waxes and Hydrocarbon waxes:

Assessment : Non-classified vPvB substance. Non-classified PBT substance

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Offer empty spray cans to an established disposal company.
Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied
16 05 04*, gases in pressure containers (including halons)
containing hazardous substances

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version	Revision Date:	Date of last issue: 30.01.2025	Print Date:
3.0	26.06.2026	Date of first issue: 22.06.2016	26.06.2026

SECTION 14: Transport information

14.1 UN number or ID number

ADN	:	UN 1950
ADR	:	UN 1950
RID	:	UN 1950
IMDG	:	UN 1950
IATA	:	UN 1950

14.2 UN proper shipping name

ADN	:	AEROSOLS
ADR	:	AEROSOLS
RID	:	AEROSOLS
IMDG	:	AEROSOLS
II	:	(Pentane, naphtha (petroleum), hydrotreated heavy)
IATA	:	Aerosols, flammable

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 2	2.1
ADR	: 2	2.1
RID	: 2	2.1
IMDG	: 2.1	
IATA	: 2.1	

14.4 Packing group

ADN	
Packing group	: Not assigned by regulation
Classification Code	: 5F
Labels	: 2.1
ADR	
Packing group	: Not assigned by regulation
Classification Code	: 5F
Labels	: 2.1
Tunnel restriction code	: (D)
RID	
Packing group	: Not assigned by regulation
Classification Code	: 5F
Hazard Identification Number	: 23
Labels	: 2.1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

IMDG

Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3: 2-butoxyethanol
Number on list 40

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

||

This substance/mixture shall not be used in aerosol dispensers intended for supply to the general public for entertainment and decorative purposes.

Number on list 57: cyclohexane

Number on list 75
If you intend to use this product as tattoo ink, please contact your vendor.

||

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).
(EU SVHC)

: n-hexane

Regulation (EU) No 2024/590 on substances that deplete the ozone layer
(EC 2024/590)

: Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast)
(EU POP)

: Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals
(EU PIC)

: Not applicable

REACH - List of substances subject to authorisation (Annex XIV)
(EU. REACH-Annex XIV)

: Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors

Not applicable

P2

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a FLAMMABLE AEROSOLS

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version 3.0	Revision Date: 26.06.2026	Date of last issue: 30.01.2025 Date of first issue: 22.06.2016	Print Date: 26.06.2026
----------------	------------------------------	---	---------------------------

E2 ENVIRONMENTAL HAZARDS

18 Liquefied flammable gases
(including LPG) and natural gas

34 Petroleum products: (a) gasolines
and naphthas, (b) kerosenes
(including jet fuels), (c) gas oils
(including diesel fuels, home heating
oils and gas oil blending
streams),(d) heavy fuel oils (e)
alternative fuels serving the same
purposes and with similar properties
as regards flammability and
environmental hazards as the
products referred to in points (a) to
(d)

Installations classified for the : 4320, 4511, 4718, 4310, 4734, 1436
protection of the environment
(Environment Code R511-9)

Occupational Illnesses (R- : 84, 36, 59, 36 bis
461-3, France)

Reinforced medical : The product has no CMR properties category 1, 1A or 1B
supervision (R4624-23)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and
livestock rearing emissions (integrated pollution prevention and
control)
Volatile organic compounds (VOC) content: 93,32 %

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations,
where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national
regulations, where applicable.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version	Revision Date:	Date of last issue: 30.01.2025	Print Date:
3.0	26.06.2026	Date of first issue: 22.06.2016	26.06.2026

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

H220	: Extremely flammable gas.
H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H280	: Contains gas under pressure; may explode if heated.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H331	: Toxic if inhaled.
H336	: May cause drowsiness or dizziness.
H361f	: Suspected of damaging fertility.
H373	: May cause damage to organs through prolonged or repeated exposure.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

**	: Route of exposure cannot be excluded: For certain hazard classes, e.g. STOT, the route of exposure should be indicated in the hazard statement only if it is conclusively proven that no other route of exposure can cause the hazard in accordance to the criteria in Annex I. Under Directive 67/548/EEC the route of exposure was indicated for classifications with R48 when there was data justifying the classification for this route of exposure. The classification under 67/548/EEC indicating the route of exposure has been translated into the corresponding class and category according to this Regulation, but with a general hazard statement not specifying the route of exposure as the necessary information is not available.
***	: Hazard statements for reproductive toxicity: Hazard statements H360 and H361 indicate a general concern for effects on fertility and/or development: 'May damage/Suspected of damaging fertility or the unborn child'. According to the criteria, the general hazard statement can be replaced by the hazard statement indicating the specific effect of concern in accordance with Section 1.1.2.1.2. When the other differentiation is not mentioned, this is due to evidence proving no such effect, inconclusive data or no data and the obligations in Article 4(3) shall apply for that differentiation. In order not to lose information from the harmonised

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version	Revision Date:	Date of last issue: 30.01.2025	Print Date:
3.0	26.06.2026	Date of first issue: 22.06.2016	26.06.2026

	classifications for fertility and developmental effects under Directive 67/548/EEC, the classifications have been translated only for those effects classified under that Directive
Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Gas	: Flammable gases
Flam. Liq.	: Flammable liquids
Note C	: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
Note P	: The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply.
Note S	: This substance may not require a label according to Article 17 (see Section 1.3 of Annex I) (Table 3).
Note U (Table 3)	: When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).
Press. Gas	: Gases under pressure
Repr.	: Reproductive toxicity
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC	: Europe. Indicative occupational exposure limit values
FR VLE	: France. Occupational Exposure Limits
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2006/15/EC / TWA	: Limit Value - eight hours
FR VLE / VME	: Time Weighted Average
FR VLE / VLCT (VLE)	: Short Term Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version	Revision Date:	Date of last issue: 30.01.2025	Print Date:
3.0	26.06.2026	Date of first issue: 22.06.2016	26.06.2026

Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315
STOT SE 3	H336
Asp. Tox. 1	H304
Aquatic Chronic 2	H411

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Based on product data or assessment
Calculation method

|| Relevant changes compared to the last edition are highlighted at the left margin. This version replaces all previous editions.

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2101

Version	Revision Date:	Date of last issue: 30.01.2025	Print Date:
3.0	26.06.2026	Date of first issue: 22.06.2016	26.06.2026

from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.