

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version	Revision Date:	Date of last issue:	Print Date:
1.1	04.04.2025	19.09.2024 Date of first issue: 19.09.2024	04.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 2571

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Corrosion inhibitor

Recommended restrictions on use : Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialechmierstoffe GmbH
Ganghoferstr. 47
82216 Maisach-Gernlinden
Deutschland
Tel.: +49 8142 3051 500
Fax: +49 8142 3051 599
info@oks-germany.com

E-mail address of person responsible for the SDS : mcm@oks-germany.com

National contact :

1.4 Emergency telephone number

Emergency telephone number : +33 1 45 42 59 59 ORFILA
+33 1 72 11 00 03 NCEC
+49 8142 3051 517

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version 1.1	Revision Date: 04.04.2025	Date of last issue: 19.09.2024 Date of first issue: 19.09.2024	Print Date: 04.04.2025
----------------	------------------------------	---	---------------------------

Eye irritation, Category 2

H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous system

H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

: Danger

Hazard statements

:	H222	Extremely flammable aerosol.
	H229	Pressurised container: May burst if heated.
	H315	Causes skin irritation.
	H319	Causes serious eye irritation.
	H336	May cause drowsiness or dizziness.
	H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing mist.
P264	Wash skin thoroughly after handling.

Storage:

P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
-------------	---

Hazardous components which must be listed on the label:

butanone

acetone

n-butyl acetate

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version	Revision Date:	Date of last issue: 19.09.2024	Print Date:
1.1	04.04.2025	Date of first issue: 19.09.2024	04.04.2025

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Active agent with propellant and solvent.
Metal powder

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
butanone	78-93-3 201-159-0 606-002-00-3 01-2119457290-43-XXXX	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336; EUH066		>= 30 - < 50
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49-XXXX	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336; EUH066		>= 10 - < 20
cyclopentanone	120-92-3 204-435-9 606-025-00-9 01-2119495595-21-	Flam. Liq.3; H226 Skin Irrit.2; H315 Eye Irrit.2; H319		>= 10 - < 20

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version 1.1	Revision Date: 04.04.2025	Date of last issue: 19.09.2024 Date of first issue: 19.09.2024	Print Date: 04.04.2025
----------------	------------------------------	---	---------------------------

	xxxx			
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29-XXXX	Flam. Liq.3; H226 STOT SE3; H336; EUH066		$\geq 1 - < 10$
zinc powder — zinc dust (stabilised)	7440-66-6 231-175-3 030-001-01-9 01-2119467174-37-XXXX	Aquatic Acute1; H400 Aquatic Chronic1; H410	M-Factor: 1/1	$\geq 1 - < 2,5$
Substances with a workplace exposure limit :				
dimethyl ether	115-10-6 204-065-8 603-019-00-8 01-2119472128-37-XXXX	Flam. Gas1A; H220 Press. GasLiquefied gas; H280	Note U (Table 3)	$\geq 30 - < 50$
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1 01-2119529243-45-XXXX	Flam. Sol.1; H228	Note T	$\geq 1 - < 10$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- If inhaled : Call a physician or poison control centre immediately.
Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash off immediately with soap and plenty of water.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version 1.1	Revision Date: 04.04.2025	Date of last issue: 19.09.2024 Date of first issue: 19.09.2024	Print Date: 04.04.2025
----------------	------------------------------	---	---------------------------

Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
Seek medical advice.

If swallowed : Move the victim to fresh air.
If accidentally swallowed obtain immediate medical attention.
Keep respiratory tract clear.
Do NOT induce vomiting.
Rinse mouth with water.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:
Unconsciousness
Dizziness
Drowsiness
Headache
Nausea
Tiredness

Risks : Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.

Central nervous system depression

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Fire Hazard
Do not let product enter drains.
Contains gas under pressure; may explode if heated.
Beware of vapours accumulating to form explosive

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version 1.1	Revision Date: 04.04.2025	Date of last issue: 19.09.2024 Date of first issue: 19.09.2024	Print Date: 04.04.2025
----------------	------------------------------	---	---------------------------

concentrations. Vapours can accumulate in low areas.

Hazardous combustion products : Carbon oxides
Metal oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not breathe vapours or spray mist.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Refer to protective measures listed in sections 7 and 8.
Only qualified personnel equipped with suitable protective equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.
Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version	Revision Date:	Date of last issue:	Print Date:
1.1	04.04.2025	19.09.2024 Date of first issue: 19.09.2024	04.04.2025

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Do not use in areas without adequate ventilation.
Do not breathe vapours or spray mist.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin and eyes.
For personal protection see section 8.
Keep away from fire, sparks and heated surfaces.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
Do not get in eyes or mouth or on skin.
Do not get on skin or clothing.
Do not ingest.
Do not use sparking tools.
These safety instructions also apply to empty packaging which may still contain product residues.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
- Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular national regulations.

7.3 Specific end use(s)

- Specific use(s) : Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
butanone	78-93-3	STEL	300 ppm	2000/39/EC

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version
1.1

Revision Date:
04.04.2025

Date of last issue: 19.09.2024
Date of first issue: 19.09.2024

Print Date:
04.04.2025

			900 mg/m3	(2000-06-16)
	Further information: Indicative			
		TWA	200 ppm 600 mg/m3	2000/39/EC (2000-06-16)
	Further information: Indicative			
		VME	200 ppm 600 mg/m3	FR VLE (2012-05-10)
	Further information: Risk of penetration through skin, Regulatory binding exposure limits			
		VLCT (VLE)	300 ppm 900 mg/m3	FR VLE (2012-05-10)
	Further information: Risk of penetration through skin, Regulatory binding exposure limits			
dimethyl ether	115-10-6	TWA	1.000 ppm 1.920 mg/m3	2000/39/EC (2000-06-16)
	Further information: Indicative			
		VME	1.000 ppm 1.920 mg/m3	FR VLE (2005-02-01)
	Further information: Regulatory indicative exposure limits			
acetone	67-64-1	TWA	500 ppm 1.210 mg/m3	2000/39/EC (2000-06-16)
	Further information: Indicative			
		VME	500 ppm 1.210 mg/m3	FR VLE (2007-12-01)
	Further information: Regulatory binding exposure limits			
		VLCT (VLE)	1.000 ppm 2.420 mg/m3	FR VLE (2007-12-01)
	Further information: Regulatory binding exposure limits			
aluminium powder (stabilised)	7429-90-5	VME	10 mg/m3	FR VLE (2016-10-01)
	Further information: Permissible limit values (circular)			
		VME (powder)	5 mg/m3	FR VLE (2016-10-01)
	Further information: Permissible limit values (circular)			
n-butyl acetate	123-86-4	STEL	150 ppm 723 mg/m3	2019/1831/E U (2019-10-31)
	Further information: Indicative			
		TWA	50 ppm 241 mg/m3	2019/1831/E U (2019-10-31)
	Further information: Indicative			
		VME	50 ppm 241 mg/m3	FR VLE (2021-12-29)
	Further information: Regulatory binding exposure limits			
		VLCT (VLE)	150 ppm 723 mg/m3	FR VLE (2021-12-29)
	Further information: Regulatory binding exposure limits			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version
1.1

Revision Date:
04.04.2025

Date of last issue: 19.09.2024
Date of first issue: 19.09.2024

Print Date:
04.04.2025

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
butanone	Workers	Inhalation	Long-term systemic effects	600 mg/m3
	Workers	Skin contact	Long-term systemic effects	1161 mg/kg
dimethyl ether	Workers	Inhalation	Long-term exposure	1894 mg/m3
acetone	Workers	Inhalation	Long-term systemic effects	1210 mg/m3
	Workers	Skin contact	Long-term systemic effects	186 mg/kg
cyclopentanone	Workers	Inhalation	Long-term systemic effects	61 mg/m3
	Workers	Skin contact	Long-term systemic effects	7 mg/kg
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3,72 mg/m3
	Workers	Inhalation	Long-term local effects	3,72 mg/m3
n-butyl acetate	Workers	Inhalation	Long-term systemic effects	300 mg/m3
	Workers	Inhalation	Acute systemic effects	600 mg/m3
	Workers	Dermal	Long-term local effects	11 mg/cm2
zinc powder — zinc dust (stabilised)	Workers	Inhalation	Long-term systemic effects	5 mg/m3
	Workers	Skin contact	Long-term systemic effects	83 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
dimethyl ether	Fresh water	0,155 mg/l
	Marine water	0,016 mg/l
	Sewage treatment plant	160 mg/l
	Fresh water sediment	0,681 mg/kg
	Marine sediment	0,069 mg/kg
	Soil	0,045 mg/kg
acetone	Fresh water	10,6 mg/l
	Marine water	1,06 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	30,4 mg/kg
	Marine sediment	3,04 mg/kg
	Soil	29,5 mg/kg
n-butyl acetate	Fresh water	0,18 mg/l
	Marine water	0,018 mg/l
	Microbiological Activity in Sewage Treatment Systems	35,6 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version	Revision Date:	Date of last issue: 19.09.2024	Print Date:
1.1	04.04.2025	Date of first issue: 19.09.2024	04.04.2025

	Fresh water sediment	0,981 mg/kg
	Marine sediment	0,0981 mg/kg
	Soil	0,09 mg/kg
zinc powder — zinc dust (stabilised)	Fresh water	0,0206 mg/l
	Fresh water sediment	117,8 mg/kg
	Marine water	0,0061 mg/l
	Marine sediment	56,5 mg/kg
	Microbiological Activity in Sewage Treatment Systems	0,052 mg/l
	Soil	35,6 mg/kg

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye/face protection : Safety glasses with side-shields

Hand protection

Material : butyl-rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.
The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Recommended Filter type:
Organic gas and low boiling vapour type (AX)

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version	Revision Date:	Date of last issue: 19.09.2024	Print Date:
1.1	04.04.2025	Date of first issue: 19.09.2024	04.04.2025

Environmental exposure controls

Air : Should not be released into the environment.

Soil :
Do not allow contact with soil, surface or ground water.
The product should not be allowed to enter drains, water courses or the soil.

Water :
Do not allow contact with soil, surface or ground water.
The product should not be allowed to enter drains, water courses or the soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : aerosol

Colour : silver

Odour : characteristic

Odour Threshold : No data available

Melting point/ range : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 14,3 %(V)

Lower explosion limit / Lower flammability limit : 1 %(V)

Flash point : -60 °C
Method: Abel-Pensky

Auto-ignition temperature : 365 °C

Decomposition temperature : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version 1.1	Revision Date: 04.04.2025	Date of last issue: 19.09.2024 Date of first issue: 19.09.2024	Print Date: 04.04.2025
----------------	------------------------------	---	---------------------------

pH : Not applicable
substance/mixture is non-soluble (in water)

Viscosity
Viscosity, dynamic : No data available
Viscosity, kinematic : < 20,5 mm²/s (40 °C)

Solubility(ies)
Water solubility : insoluble
Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 5.600 hPa (20 °C)

Relative density : 0,67 (20 °C)
Reference substance: Water
The value is calculated

Density : 0,67 g/cm³
(20 °C)

Bulk density : No data available

Relative vapour density : No data available

9.2 Other information

Explosives : Not explosive
Oxidizing properties : No data available
Self-ignition : No data available
Evaporation rate : No data available
Sublimation point : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version	Revision Date:	Date of last issue:	Print Date:
1.1	04.04.2025	19.09.2024 Date of first issue: 19.09.2024	04.04.2025

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.
Strong sunlight for prolonged periods.
Risk of receptacle bursting.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity	: Remarks: Effects due to ingestion may include: Symptoms: Central nervous system depression
Acute inhalation toxicity	: Remarks: Respiration of solvent vapour may cause dizziness. Symptoms: Inhalation may provoke the following symptoms: Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central nervous system depression
Acute dermal toxicity	: Symptoms: Redness, Local irritation

Components:

butanone:

Acute oral toxicity	: LD50 (Rat): 2.193 mg/kg Method: OECD Test Guideline 423 GLP: yes
Acute inhalation toxicity	: LC50 (Rat): 34 mg/l Exposure time: 4 h Test atmosphere: vapour

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version 1.1	Revision Date: 04.04.2025	Date of last issue: 19.09.2024 Date of first issue: 19.09.2024	Print Date: 04.04.2025
----------------	------------------------------	---	---------------------------

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
Method: OECD Test Guideline 402

acetone:

Acute oral toxicity : LD50 Oral (Rat): 5.800 mg/kg

cyclopentanone:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

n-butyl acetate:

Acute oral toxicity : LD50 (Rat): 10.768 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
GLP: yes
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 17.600 mg/kg

zinc powder — zinc dust (stabilised):

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 401
GLP: yes
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 5,41 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: yes
Assessment: The substance or mixture has no acute inhalation toxicity

dimethyl ether:

Acute inhalation toxicity : LC50 (Rat): 309 mg/l
Exposure time: 4 h
Test atmosphere: gas

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5,09 mg/l
Exposure time: 4 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version	Revision Date:	Date of last issue: 19.09.2024	Print Date:
1.1	04.04.2025	Date of first issue: 19.09.2024	04.04.2025

Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute
inhalation toxicity

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : This information is not available.

Components:

butanone:

Species	: Rabbit
Assessment	: No skin irritation
Method	: OECD Test Guideline 404
Result	: No skin irritation
Result	: Repeated exposure may cause skin dryness or cracking.

acetone:

Result	: Repeated exposure may cause skin dryness or cracking.
--------	---

cyclopentanone:

Species	: Rabbit
Result	: Skin irritation

n-butyl acetate:

Species	: Rabbit
Assessment	: No skin irritation
Method	: OECD Test Guideline 404
Result	: Repeated exposure may cause skin dryness or cracking.

zinc powder — zinc dust (stabilised):

Species	: Rabbit
Assessment	: No skin irritation
Result	: No skin irritation

dimethyl ether:

Assessment	: No skin irritation
Result	: No skin irritation

aluminium powder (stabilised):

Species	: Rabbit
Assessment	: No skin irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version	Revision Date:	Date of last issue: 19.09.2024	Print Date:
1.1	04.04.2025	Date of first issue: 19.09.2024	04.04.2025

Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : This information is not available.

Components:

butanone:

Species : Rabbit
Assessment : Irritating to eyes.
Method : OECD Test Guideline 405
Result : Irritating to eyes.

acetone:

Species : Rabbit
Result : Eye irritation

cyclopentanone:

Species : Rabbit
Result : Eye irritation

n-butyl acetate:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes

zinc powder — zinc dust (stabilised):

Species : Rabbit
Exposure time : 24 h
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes

dimethyl ether:

Assessment : No eye irritation
Result : No eye irritation

aluminium powder (stabilised):

Species : Rabbit

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version	Revision Date:	Date of last issue: 19.09.2024	Print Date:
1.1	04.04.2025	Date of first issue: 19.09.2024	04.04.2025

Assessment : No eye irritation
Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Product:

Remarks : This information is not available.

Components:

butanone:

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.
GLP : yes

n-butyl acetate:

Test Type : Maximisation Test
Exposure routes : Dermal
Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.

zinc powder — zinc dust (stabilised):

Species : Guinea pig
Assessment : Did not cause sensitisation on laboratory animals.
Method : OECD Test Guideline 406
Result : Did not cause sensitisation on laboratory animals.
GLP : yes

dimethyl ether:

Assessment : Does not cause skin sensitisation.
Result : Does not cause skin sensitisation.

aluminium powder (stabilised):

Species : Guinea pig

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version 1.1	Revision Date: 04.04.2025	Date of last issue: 19.09.2024 Date of first issue: 19.09.2024	Print Date: 04.04.2025
----------------	------------------------------	---	---------------------------

Assessment : Did not cause sensitisation on laboratory animals.
Result : Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

butanone:

Germ cell mutagenicity-
Assessment : Tests on bacterial or mammalian cell cultures did not show
mutagenic effects.

n-butyl acetate:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Test system: Chinese hamster cells
Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Species: Mouse
Application Route: Oral
Method: OECD Test Guideline 474
Result: negative

Germ cell mutagenicity-
Assessment : Tests on bacterial or mammalian cell cultures did not show
mutagenic effects., Animal testing did not show any mutagenic
effects.

zinc powder — zinc dust (stabilised):

Germ cell mutagenicity-
Assessment : Tests on bacterial or mammalian cell cultures did not show
mutagenic effects.

dimethyl ether:

Genotoxicity in vitro : Test Type: Ames test
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Species: Drosophila melanogaster (vinegar fly)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version	Revision Date:	Date of last issue: 19.09.2024	Print Date:
1.1	04.04.2025	Date of first issue: 19.09.2024	04.04.2025

Application Route: inhalation (gas)
Method: OECD Test Guideline 477
Result: negative

Carcinogenicity

Based on available data, the classification criteria are not met.

Product:

Remarks : No data available

Components:

butanone:

Carcinogenicity - : Not classifiable as a human carcinogen.
Assessment

n-butyl acetate:

Carcinogenicity - : Not classifiable as a human carcinogen.
Assessment

zinc powder — zinc dust (stabilised):

Carcinogenicity - : No evidence of carcinogenicity in animal studies.
Assessment

dimethyl ether:

Species : Rat
Application Route : inhalation (gas)
Exposure time : 2 Years
: 47 mg/l
Method : OECD Test Guideline 453
Result : negative

Reproductive toxicity

Based on available data, the classification criteria are not met.

Product:

Effects on fertility : Remarks: No data available

Effects on foetal : Remarks: No data available
development

Components:

butanone:

Reproductive toxicity - : - Fertility -
Assessment
No toxicity to reproduction

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version 1.1	Revision Date: 04.04.2025	Date of last issue: 19.09.2024 Date of first issue: 19.09.2024	Print Date: 04.04.2025
----------------	------------------------------	---	---------------------------

- Teratogenicity -

No effects on or via lactation

n-butyl acetate:

Effects on fertility : Test Type: Two-generation study
Species: Rat
Application Route: inhalation (vapour)
General Toxicity - Parent: NOAEC: 750 mg/l
General Toxicity F1: NOAEC: 750 mg/l
General Toxicity F2: NOAEC: 750 mg/l
Method: OECD Test Guideline 416
Result: Embryotoxic effects and adverse effects on the offspring were detected.

Reproductive toxicity -
Assessment

: - Fertility -
No evidence of adverse effects on sexual function and fertility,
or on development, based on animal experiments.
- Teratogenicity -
No toxicity to reproduction

zinc powder — zinc dust (stabilised):

Reproductive toxicity -
Assessment : - Fertility -
No toxicity to reproduction
- Teratogenicity -
No effects on or via lactation

dimethyl ether:

Reproductive toxicity -
Assessment : - Fertility -
Animal testing did not show any effects on fertility.

STOT - single exposure

May cause drowsiness or dizziness.

Product:

Remarks : No data available

Components:

butanone:

Exposure routes : Inhalation
Target Organs : Respiratory system
Assessment : The substance or mixture is classified as specific target organ
toxicant, single exposure, category 3 with narcotic effects.,
May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version	Revision Date:	Date of last issue: 19.09.2024	Print Date:
1.1	04.04.2025	Date of first issue: 19.09.2024	04.04.2025

acetone:

Exposure routes : Inhalation
Assessment : May cause drowsiness or dizziness.

n-butyl acetate:

Exposure routes : Inhalation
Target Organs : Central nervous system
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Product:

Remarks : No data available

Components:

butanone:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

n-butyl acetate:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Components:

n-butyl acetate:

Species : Rat
NOAEL : 125 mg/kg
Application Route : Oral

Aspiration toxicity

Based on available data, the classification criteria are not met.

Product:

This information is not available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version	Revision Date:	Date of last issue:	Print Date:
1.1	04.04.2025	19.09.2024 Date of first issue: 19.09.2024	04.04.2025

Components:

butanone:

No aspiration toxicity classification

n-butyl acetate:

No aspiration toxicity classification

zinc powder — zinc dust (stabilised):

No aspiration toxicity classification

dimethyl ether:

No aspiration toxicity classification

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Risks of irreversible effects after a single exposure.
Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.
Possible risk of irreversible effects.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic : Remarks: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version 1.1	Revision Date: 04.04.2025	Date of last issue: 19.09.2024 Date of first issue: 19.09.2024	Print Date: 04.04.2025
----------------	------------------------------	---	---------------------------

plants

Toxicity to microorganisms :
Remarks: No data available

Components:

butanone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.993 mg/l
Exposure time: 96 h
Test Type: static test

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 308 mg/l
aquatic invertebrates
Exposure time: 48 h
Test Type: static test

Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (green algae)): 1.972
plants
mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

Toxicity to microorganisms : EC50 (Pseudomonas putida): 1.150 mg/l
Exposure time: 16 h
Test Type: static test
Method: DIN 38 412 Part 8

n-butyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l
Exposure time: 96 h
Test Type: flow-through test
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 44 mg/l
aquatic invertebrates
Exposure time: 48 h
Test Type: static test

Toxicity to algae/aquatic : EC50 (Desmodesmus subspicatus (green algae)): 397 mg/l
plants
Exposure time: 72 h
Test Type: static test

Toxicity to microorganisms : EC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h
Test Type: Growth inhibition

Toxicity to daphnia and other : NOEC: 23 mg/l
aquatic invertebrates
(Chronic toxicity)
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: Reproduction Test

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version 1.1	Revision Date: 04.04.2025	Date of last issue: 19.09.2024 Date of first issue: 19.09.2024	Print Date: 04.04.2025
----------------	------------------------------	---	---------------------------

GLP: yes

zinc powder — zinc dust (stabilised):

Toxicity to fish : LC50 (Oncorhynchus kisutch (coho salmon)): 0,727 mg/l
Exposure time: 96 h
Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,937 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

dimethyl ether:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 4.100 mg/l
Exposure time: 96 h
Test Type: semi-static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 4.400 mg/l
Exposure time: 48 h
Test Type: static test

Toxicity to algae/aquatic plants : EC50 (green algae): 154,9 mg/l
Exposure time: 96 h

aluminium powder (stabilised):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0,12 mg/l
Exposure time: 96 h
Test Type: static test
Remarks: No toxicity at the limit of solubility

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version	Revision Date:	Date of last issue: 19.09.2024	Print Date:
1.1	04.04.2025	Date of first issue: 19.09.2024	04.04.2025

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical
removability : Remarks: No data available

Components:

butanone:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: rapidly biodegradable
Biodegradation: 98 %
Exposure time: 28 d
Method: OECD Test Guideline 301D
GLP: yes

acetone:

Biodegradability : Result: rapidly biodegradable

cyclopentanone:

Biodegradability : Result: rapidly biodegradable

n-butyl acetate:

Biodegradability : Test Type: Primary biodegradation
Result: rapidly biodegradable
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

dimethyl ether:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version 1.1	Revision Date: 04.04.2025	Date of last issue: 19.09.2024 Date of first issue: 19.09.2024	Print Date: 04.04.2025
----------------	------------------------------	---	---------------------------

Components:

butanone:

Bioaccumulation : Remarks: Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

Partition coefficient: n-octanol/water : log Pow: 0,3 (40 °C)
Method: OECD Test Guideline 117
GLP: yes

acetone:

Bioaccumulation : Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 0,2

cyclopentanone:

Bioaccumulation : Remarks: No data available

n-butyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2,3 (25 °C)
pH: 7
Method: OECD Test Guideline 117
GLP: yes

dimethyl ether:

Partition coefficient: n-octanol/water : log Pow: 0,07 (25 °C)

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version	Revision Date:	Date of last issue: 19.09.2024	Print Date:
1.1	04.04.2025	Date of first issue: 19.09.2024	04.04.2025

Components:

butanone:

Assessment : Non-classified PBT substance. Non-classified vPvB substance

n-butyl acetate:

Assessment : Non-classified PBT substance. Non-classified vPvB substance

dimethyl ether:

Assessment : Non-classified vPvB substance. Non-classified PBT substance

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Offer empty spray cans to an established disposal company.
Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied
16 05 04*, gases in pressure containers (including halons)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version	Revision Date:	Date of last issue: 19.09.2024	Print Date:
1.1	04.04.2025	Date of first issue: 19.09.2024	04.04.2025

containing hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN	:	UN 1950
ADR	:	UN 1950
RID	:	UN 1950
IMDG	:	UN 1950
IATA	:	UN 1950

14.2 UN proper shipping name

ADN	:	AEROSOLS
ADR	:	AEROSOLS
RID	:	AEROSOLS
IMDG	:	AEROSOLS
IATA	:	Aerosols, flammable

14.3 Transport hazard class(es)

ADN	:	2
ADR	:	2
RID	:	2
IMDG	:	2.1
IATA	:	2.1

14.4 Packing group

ADN	:	
Packing group	:	Not assigned by regulation
Classification Code	:	5F
Labels	:	2.1

ADR	:	
Packing group	:	Not assigned by regulation
Classification Code	:	5F
Labels	:	2.1
Tunnel restriction code	:	(D)

RID	:	
Packing group	:	Not assigned by regulation
Classification Code	:	5F
Hazard Identification Number	:	23

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version 1.1	Revision Date: 04.04.2025	Date of last issue: 19.09.2024 Date of first issue: 19.09.2024	Print Date: 04.04.2025
----------------	------------------------------	---	---------------------------

Labels : 2.1

IMDG

Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Conditions of restriction for the following entries should be considered: Number on list 75 If you intend to use this product as
--	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version 1.1	Revision Date: 04.04.2025	Date of last issue: 19.09.2024 Date of first issue: 19.09.2024	Print Date: 04.04.2025
----------------	------------------------------	---	---------------------------

tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). (EU SVHC) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Regulation (EU) No 2024/590 on substances that deplete the ozone layer (EC 2024/590) : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) (EU POP) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals (EU PIC) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) (EU. REACH-Annex XIV) : Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors : acetone (ANNEX II)

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

P5c

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P3a FLAMMABLE AEROSOLS

Installations classified for the protection of the environment (Environment Code R511-9) : 4320

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version	Revision Date:	Date of last issue: 19.09.2024	Print Date:
1.1	04.04.2025	Date of first issue: 19.09.2024	04.04.2025

Occupational Illnesses (R-461-3, France) : 84, 51, 44

Reinforced medical supervision (R4624-23) : The product has no CMR properties category 1, 1A or 1B

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 88,52 %

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

H220	: Extremely flammable gas.
H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H228	: Flammable solid.
H280	: Contains gas under pressure; may explode if heated.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H336	: May cause drowsiness or dizziness.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Note T : This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version	Revision Date:	Date of last issue: 19.09.2024	Print Date:
1.1	04.04.2025	Date of first issue: 19.09.2024	04.04.2025

- does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be included in the safety data sheet.
- Note U (Table 3) : When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).
- 2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
- 2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
- FR VLE : France. Occupational Exposure Limits
- 2000/39/EC / TWA : Limit Value - eight hours
- 2000/39/EC / STEL : Short term exposure limit
- 2019/1831/EU / TWA : Limit Value - eight hours
- 2019/1831/EU / STEL : Short term exposure limit
- FR VLE / VME : Time Weighted Average
- FR VLE / VLCT (VLE) : Short Term Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 2571

Version	Revision Date:	Date of last issue: 19.09.2024	Print Date:
1.1	04.04.2025	Date of first issue: 19.09.2024	04.04.2025

Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

|| Relevant changes compared to the last edition are highlighted at the left margin. This version replaces all previous editions.

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.