

## OKS 2711 Refrigerating Spray

---



### Description

OKS 2711 is a refrigerating spray for undercooling of machine elements.

### Applications

- For fast determination of thermally-dependent interruptions in electrical circuits or components
- Avoidance of heat damage when soldering electrical components
- For heat protection of neighbouring components
- Shrinking of inner parts for removal of seized taper plugs, pins, plugs or bearing bushes
- Generation of shrink seats for assembly of inner parts
- For rapid temperature adjustment during materials testing
- For simulation of cold-starting conditions with motor-vehicle automatic starting systems

### Advantages and benefits

- Highly effective due to outstanding undercooling effect
- Excellently suited for simple cooling of parts
- Immediate cooling of smaller surfaces or parts down to  $-45^{\circ}\text{C}$  depending on spraying duration
- Evaporates very quickly without residues
- Also provides good cleaning effect
- No negative affects on plastics and insulating materials

### Branches

- Logistics
- Chemical industry
- Shipbuilding and marine technology
- Rubber and plastic processing
- Iron and steel industry
- Maintenance and servicing
- Paper and packaging industry
- Plant and machine (tool) engineering
- Municipal services
- Rail vehicle technology
- Glass and foundry industry

### Application tips

Spray on respective parts for some seconds depending on desired temperature. For accurate spraying insert attached capillary tube in the jet orifice. Do not use under voltage! Risk of undercooling at longer skin contact.

### Packaging

- 400 ml Spray

# PRODUCT INFORMATION



**KLÜBER**  
a product brand of **LUBRICATION**

## OKS 2711 Refrigerating Spray

### Technical data

	Standard	Conditions	Unit	Value
<b>Main components</b>				
base oil				solvent mixture
<b>Application related technical data</b>				
colour				colourless
density	DIN EN ISO 3838	at 20°C	g/cm <sup>3</sup>	0.56
<b>Properties and approvals</b>				
UFI				9XG1-607N-D00H-WQET

**Klüber Lubrication München GmbH & Co. KG**  
Geisenhausenerstraße 7 / 81379 München /  
Germany / phone +49 89 7876-0

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.