




## OKS 2731 Compressed-Air Spray



### Description

OKS 2731 is a compressed-air spray for removal of loose dirt particles at inaccessible points.

### Applications

- For removing dust prior to maintenance and repair work, e.g. on magnetic plates, reading heads, audio-visual magnetic tape recording and playback heads, phonograph pick-ups, record turntables or phonograph records
- For cleaning vacuum sealing surfaces, sealing rings, high-voltage insulators, sample containers etc.
- For vacuum systems and device groups under clean-room conditions for semiconductor production
- Cleaning of opto-electronic reading units for bank checks and contactless cleaning of optical devices
- For maintenance of automated teller machines, quartz clocks or display panels
- For dedusting precision mechanical parts and assemblies in office machines, copiers, fax machines etc.

### Advantages and benefits

- Excellently suited for dedusting, blowing out and blowing off dust and liquids of all kinds
- Dry, oil-free compressed gas leaves behind no residues
- Replacement for ultrapure compressed air

### Branches

- Iron and steel industry
- Maintenance and servicing
- Municipal services
- Plant and machine (tool) engineering
- Rail vehicle technology
- Glass and foundry industry
- Paper and packaging industry
- Rubber and plastic processing
- Chemical industry
- Logistics
- Shipbuilding and marine technology

### Application tips

Spray on areas to be cleaned in short intervals from approx. 10 cm distance. Do not shake tin before use! Keep tin in vertical position while spraying. If not used correctly liquid gas can escape and undercool the object. Do not use under voltage! To be used only in good ventilated rooms - no smoking.

### Packaging

- 400 ml Spray

OKS 2731

Compressed-Air Spray

Technical data

|                                    | Standard        | Conditions | Unit  | Value               |
|------------------------------------|-----------------|------------|-------|---------------------|
| Main components                    |                 |            |       |                     |
| base oil                           |                 |            |       | solvent mixture     |
| Application related technical data |                 |            |       |                     |
| colour                             |                 |            |       | colourless          |
| density                            | DIN EN ISO 3838 | at 20°C    | g/cm³ | 0.56                |
| Properties and approvals           |                 |            |       |                     |
| UFI                                |                 |            |       | A1H1-P0X1-Q001-J20V |

OKS Spezialschmierstoffe GmbH

Ganghoferstraße 47

82216 Maisach

+49 8142 3051 - 500

info@oks-germany.com

www.oks-germany.com

a brand of

FREUDENBERG

The information in this publication reflects state-of-the-art technology, as well as extensive testing and experience. Due to the diversity of possible applications and technical realities, they can only serve as recommendations and are not arbitrarily transferable. Therefore, no obligations, liability or warranty claims can be derived from them. We only accept liability for the suitability of our products for particular purposes, and for certain properties of our products, in the event that we have accepted such liability in writing in the individual case. Any case of justified warranty claims shall be limited to the delivery of replacement goods free of defects, in the event that this subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular the liability for consequential injuries or damage, shall always be excluded. Prior to use, the customer must conduct its own testing to prove suitability. The data are subject to change for the sake of progress. ® = Registered trademark

**Product restricted to professional users.** Safety data sheet available for download at [www.oks-germany.com](http://www.oks-germany.com)

Our Customer and Technical service will be pleased to help should you have any further questions.