

# OKS 2650

## Industrial Cleaner



### Description

Highly concentrated cleaner on water basis for removing oily, greasy and sooty soiling.

### Applications

- Cleaning of cooling devices, beverage and goods vending machines
- Cleaning of tiles, ceramics or natural stone
- Cleaning of construction machines and lorries, tarpaulins
- Cleaning of machine tools and workshop floors

### Branches

- Catering equipment and food processing technology
- Paper and packaging industry
- Logistics
- Iron and steel industry
- Glass and foundry industry
- Shipbuilding and marine technology
- Plant and machine (tool) engineering
- Chemical industry
- Rubber and plastic processing
- Maintenance and servicing
- Municipal services
- Rail vehicle technology

### Advantages and benefits

- NSF A1 registered
- No classification marks according to (EG) No. 1272/2008
- Free of organic solvents and phosphates
- Readily biodegradable
- Good separation behaviour
- Gentle to plastics, seals, rubber and sensitive metal surfaces
- Depending on the degree of soiling, can be diluted up to 1:10
- Suitable for use with high-pressure cleaners
- MOSH/MOAH-free (as per recipe)

### Application tips

OKS 2650 is supplied ready for use. Additional dilution is usually not required. The cleaner has to be diluted more (1:10) to clean mirrors and glass surfaces. After spraying on, rub in mechanically and let it soak in for some minutes. Then rinse with clear water. Repeat the application at stubborn soiling. Caution: In the case of metal surfaces that can corrode when in contact with water dry the cleaned service thoroughly. OKS 2650 is not suitable for cleaning alkali-sensitive materials, acrylic and polycarbonate glass. We recommend therefore that you check the resistance of the surface before use.

### Packaging

- |                       |                 |                    |
|-----------------------|-----------------|--------------------|
| • 500 ml Pump sprayer | • 5 l Canister  | • 200 l Drum       |
| • 1 l Bottle          | • 25 l Canister | • 1000 l container |



**KLÜBER**  
a product brand of LUBRICATION

# OKS 2650 Industrial Cleaner

**Technical data**

	Standard	Conditions	Unit	Value
<b>Main components</b>				
basis				water
additives				silicates
additives				non-ionic surfactants
<b>Application related technical data</b>				
colour				red
density	DIN EN ISO 3838	at 20°C	g/cm <sup>3</sup>	1.03
<b>Product specific technical data</b>				
dilution				with water, max. 1:10
pH value				10.7 (concentrate)
biodegradability	OECD 301 B: 1992-07	≥ 60 %; 28 days	%	86
<b>Properties and approvals</b>				
approval for food processing technology				<a href="#">NSF A1_Reg.-Nr. 129003</a>

**Klüber Lubrication München GmbH & Co. KG**  
Geisenhausenerstraße 7 / 81379 München /  
Germany / phone +49 89 7876-0

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.