




### **OKS 611**

# MoS<sub>2</sub>-Rust Remover, Spray



#### Description

OKS 611 is a universal rust dissolver with molybdenum disulphide for industry, workshop and maintenance applications.

#### **Applications**

- Loosening of rusted-on connections such as screws, nuts, levers, joints or locks
- Non-destructive disassembly of seized or rusted-in parts such as bolts, chain links, springs, valves or hinges

#### **Branches**

- · Iron and steel industry
- Glass and foundry industry
- · Shipbuilding and marine technology
- · Rubber and plastic processing
- · Municipal services
- · Rail vehicle technology
- · Plant and machine (tool) engineering
- Chemical industry
- · Logistics
- · Maintenance and servicing
- · Paper and packaging industry

#### **Advantages and benefits**

- · High effectiveness thanks to gap penetration properties
- Minimizing of the effort required to loosen seized parts and restoring of mobility
- Good lubricating properties thanks to MoS<sub>2</sub>
- Loosened parts are protected against new corrosion forming
- Eliminates squeaking noises
- · Displaces moisture

#### **Application tips**

For optimum effectiveness, first clean contamination away from surface mechanically. Spray on generously. Allow to work in for time corresponding to depth of penetration required. If necessary, repeat the treatment several times. Lubrication in adequate quantity. Remove any excess. Only mix with suitable lubricants.

### **Packaging**

· 400 ml Spray











### **OKS 611**

## MoS<sub>2</sub>-Rust Remover, Spray

#### **Technical data**

	Standard	Conditions	Unit	Value
Main components				
base oil				mineral oil
solid lubricants				MoS <sub>2</sub>
Application related technical	al data			
viscosity	DIN 51 562-1	40°C, with solvent	mm²/s	> 3
lower operating temperature			°C	-30
upper operating temperature		with solvent	°C	60
upper operating temperature		after evaporation of the solvent	°C	150
colour				green-black
density	DIN EN ISO 3838	at 20°C	g/cm³	0.68
Properties and approvals				
UFI				KRN1-H0VV-J007-XU2E

#### **OKS Spezialschmierstoffe GmbH**

Ganghoferstraße 47 82216 Maisach

📞 +49 8142 3051 - 500

☑ info@oks-germany.com

★ www.oks-germany.com





The information in this publication reflects state-of-the-art technology, as well as extensive testing and experience. Due to the diversity of possible applications and technical realities, they can only serve as recommendations and are not arbitrarily transferable. Therefore, no obligations, liability or warranty claims can be derived from them. We only accept liability for the suitability of our products for particular purposes, and for certain properties of our products, in the event that we have accepted such liability in writing in the individual case. Any case of justified warranty claims shall be limited to the delivery of replacement goods free of defects, in the event that this subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular the liability for consequential injuries or damage, shall always be excluded. Prior to use, the customer must conduct its own testing to prove suitability. The data are subject to change for the sake of progress. \* = Registered trademark

**Product restricted to professional users.** Safety data sheet available for download at www.oks-germany.com Our Customer and Technical service will be pleased to help should you have any further questions.





