


OKS 2631 Multi-Foam Cleaner, Spray



Description

OKS 2631 is a multi-foam cleaner.

Applications

- Removes strongly adherent organic residues as well as coverings of nicotine, fat, silicone and rubber wear
- Suitable for in- and outdoor application
- Cleans aluminium and stainless steel parts, plastics, glass, chrome and rubber
- For the manifold application in the section of gastronomy, office and automotive, for hobby and sport equipment like e.g. kitchen furnishing, bars, mirrors, window glasses and frames, glass surfaces, tiles, china, screens, machine housings, boats, caravans, surfboards, bikes, polycarbonate screens and acryl glass, visor of helmets, windscreens, lights, a.s.o.

Branches

- Maintenance and servicing
- Municipal services
- Iron and steel industry
- Plant and machine (tool) engineering
- Shipbuilding and marine technology
- Glass and foundry industry
- Logistics
- Paper and packaging industry
- Rail vehicle technology
- Chemical industry
- Rubber and plastic processing

Application tips

Shake spray can very well before use. Spray evenly onto the surface from 20–30 cm distance. After a short residence time wipe away in a damp condition with a clean, non-fuzzing cloth or pulp. Test compatibility with special coatings. Store frost-free.

Advantages and benefits

- Easy application and through the active cleaning foam ideal suitable for vertical areas, no expiration
- Cleans material-gentle and without leaving stripes or streaks behind
- Does not attack paints, rubber or plastic and acts colour-refreshing
- Pleasant, citric like odour, eudermic
- Free from toxic substances like chlorine, CFC, PCB
- Silicone free
- Suitable for acryl-glasses
- Acts anti-static

OKS 2631

Multi-Foam Cleaner, Spray

Packaging

- 400 ml Spray

Technical data

	Standard	Conditions	Unit	Value
Main components				
basis				water
additives				additives
additives				anionic surfactants
Application related technical data				
colour				slightly bluish
density	DIN EN ISO 3838	at 20°C	g/cm ³	0.99
Product specific technical data				
stress crack test	DIN EN ISO 22088-3			passed
Properties and approvals				
UFI				EJ22-X0R1-500Y-GPW1

Klüber Lubrication München GmbH & Co. KG
 Geisenhausenerstraße 7 / 81379 München /
 Germany / phone +49 89 7876-0

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.