


OKS 2661

Fast Cleaner, Spray

KLÜBER
a product brand of **LUBRICATION**



Description

Residue-free evaporating fast cleaner (brake cleaner) for cleaning machine parts and material surfaces.

Applications

- Degreasing all surfaces and parts of non-absorbent materials, e.g. metals, ceramic or plastics and elastomers
- Cleaning of adhesive surfaces for coatings, paints or adhesives and sealants
- Cleaning of friction surfaces on which high friction forces are transmitted such as clutch and brake linings (brake cleaners)
- Removal of aged and gummy oil and grease residues, of residues of brake fluids and silicones, as well as of residues of simple coatings, adhesives and sealants

Advantages and benefits

- Highly effective due to actively cleaning substances
- Modern cleaner on a solvent base
- Fast and residue-free evaporation of the cleaner
- Also available as Duo label

Branches

- Municipal services
- Logistics
- Plant and machine (tool) engineering
- Shipbuilding and marine technology
- Glass and foundry industry
- Rail vehicle technology
- Rubber and plastic processing
- Paper and packaging industry
- Iron and steel industry
- Maintenance and servicing
- Chemical industry

Application tips

Wetting of the surfaces to be cleaned to excess. Cleaning is made even more effective if you simultaneously rub away at the surface with paper or cellulose cloths. If necessary, repeat the application at stubborn soiling. Subsequently allow to dry completely at room temperature. Dab away running cleaner with absorbent material and allow to evaporate in open air. Caution: Use only in well-ventilated rooms or in the open air. Some types of plastic or rubber (e.g. thermoplastics such as PVC, plexiglass, polystyrene) and paints could be attacked. We recommend therefore that you check the resistance before using the cleaner.

Packaging

- 600 ml Spray



OKS 2661
Fast Cleaner, Spray

Technical data

	Standard	Conditions	Unit	Value
Main components				
basis				solvent mixture
Application related technical data				
colour				colourless
density	DIN EN ISO 3838	at 20°C	g/cm³	0.71
Properties and approvals				
UFI				EK30-K0P5-Q00M-UA57

Klüber Lubrication München GmbH & Co. KG
Geisenhausenerstraße 7 / 81379 München /
Germany / phone +49 89 7876-0

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.