



OKS 2801 Leak Detector, Spray



Description

Leak detector for locating of leaks on lines, apparatuses and containers under internal pressure.

Applications

- Piping and hoses, for example steel bottles, compressors, breathing devices, oxyacetylene gas and inert-gas arc welding devices and burners
- Fittings, flanges, valves, screwed connections, soldered and welded connections of pressure gas systems and lines
- Suitable for compressed air, refrigerant, acetylene, butane, natural gas, carbon dioxide, gaseous oxygen, propane, town gas, nitrogen, hydrogen and, ammonia

Branches

- Paper and packaging industry
- · Shipbuilding and marine technology
- · Rail vehicle technology
- · Rubber and plastic processing
- · Glass and foundry industry
- Municipal services
- · Maintenance and servicing
- · Plant and machine (tool) engineering
- Logistics
- Iron and steel industry
- Chemical industry

Application tips

Spray OKS 2801 on. A leak is indicated by the formation of foam bubbles. Caution: When using on polyamide lines, wash off with water after the test. Protect packaging against frost.

Packaging

400 ml Spray

Advantages and benefits

- · Acts non-corrosive
- Allows direct visual inspection of the leakage point through bubble formation
- Tested by the DVGW in accordance with DIN EN 14291
- Suitable for spraying overhead









OKS 2801 Leak Detector, Spray

Technical data

	Standard	Conditions	Unit	Value
Main components				
basis				water
additives				corrosion protection
additives				active ingredients
Application related technical	al data			
lower operating temperature	DIN 51 805		°C	> 0
upper operating temperature	DIN 51 821-2		°C	50
colour				transparent
density	DIN EN ISO 3838	at 20°C	g/cm³	1.02
Properties and approvals				
UFI				E6AE-C0R5-000Q-T1C1
DVGW approval	DIN EN 14 291			RegNr. NG-5170CM208

OKS Spezialschmierstoffe GmbH

Ganghoferstraße 47 82216 Maisach

4 +49 8142 3051 - 500

☑ info@oks-germany.com

★ www.oks-germany.com



The information in this publication reflects state-of-the-art technology, as well as extensive testing and experience. Due to the diversity of possible applications and technical realities, they can only serve as recommendations and are not arbitrarily transferable. Therefore, no obligations, liability or warranty claims can be derived from them. We only accept liability for the suitability of our products for particular purposes, and for certain properties of our products, in the event that we have accepted such liability in writing in the individual case. Any case of justified warranty claims shall be limited to the delivery of replacement goods free of defects, in the event that this subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular the liability for consequential injuries or damage, shall always be excluded. Prior to use, the customer must conduct its own testing to prove suitability. The data are subject to change for the sake of progress. ** = Registered trademark** **Product restricted to professional users.** Safety data sheet available for download at www.oks-germany.com

Product restricted to professional users. Safety data sheet available for download at www.oks-germany.com Our Customer and Technical service will be pleased to help should you have any further questions.





