



OKS 621 Rust Remover, Spray





Description

OKS 621 is a fast-acting rust dissolver for industry, workshop and hobby applications. The solvent contained in OKS 621 cools down the assembled parts/screws rapidly to -40°C. This results in a slight shrinkage of the affected profile. Capillary cracks in the corrosion layer appear, allowing an easier penetration of the creeping oil.

Applications

 High-performance rust remover for fast and nondestructive disassembly of extremely seized-up parts or bolts, e.g. for vehicles, agricultural or construction machinery, vessels and port facilities; also for all machinery in industry and trade

Branches

- · Rail vehicle technology
- Plant and machine (tool) engineering
- · Chemical industry
- Municipal services
- · Shipbuilding and marine technology
- · Iron and steel industry
- · Rubber and plastic processing
- · Maintenance and servicing
- · Glass and foundry industry
- Logistics
- Paper and packaging industry

Application tips

Clean components from dirt. Shake well before use. Spray from a distance of 10–15 cm on to the parts/screws and allow OKS 621 to react for 1–2 min. Repeat treatment if necessary.

Packaging

400 ml Spray

Advantages and benefits

- Contrary to a heat treatment of seized-up bolts OKS 621 does not cause heating damages in the environment
- · No damages through overheating
- Resin and acid-free
- · Without silicone











OKS 621

Rust Remover, Spray

Technical data

	Standard	Conditions	Unit	Value
Main components				
base oil				solvent
base oil				mineral oil
Application related technical	al data			
lower operating temperature			°C	-10
upper operating temperature			°C	40
colour				light-coloured
density (at 20°C)	DIN EN ISO 3838		g/cm³	0.6
Properties and approvals				
UFI				81Y1-60ER-M00P-DQ0D

OKS Spezialschmierstoffe GmbH

Ganghoferstraße 47 82216 Maisach

4 +49 8142 3051 - 500

☑ info@oks-germany.com

★ www.oks-germany.com



The information in this publication reflects state-of-the-art technology, as well as extensive testing and experience. Due to the diversity of possible applications and technical realities, they can only serve as recommendations and are not arbitrarily transferable. Therefore, no obligations, liability or warranty claims can be derived from them. We only accept liability for the suitability of our products for particular purposes, and for certain properties of our products, in the event that we have accepted such liability in writing in the individual case. Any case of justified warranty claims shall be limited to the delivery of replacement goods free of defects, in the event that this subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular the liability for consequential injuries or damage, shall always be excluded. Prior to use, the customer must conduct its own testing to prove suitability. The data are subject to change for the sake of progress. * = Registered trademark

Product restricted to professional users. Safety data sheet available for download at www.oks-germany.com Our Customer and Technical service will be pleased to help should you have any further questions.





