

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 20.08.2025 | Print Date: |
| 5.0 | 05.06.2026 | Date of first issue: 09.07.2016 | 05.06.2026 |

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 451

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Lubricant spray

Recommended restrictions on use : Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH
Ganghoferstr. 47
82216 Maisach
Germany
Tel.: +49 8142 3051-500
info@oks-germany.com

E-mail address of person responsible for the SDS : mcm@oks-germany.com

National contact : Klüber Lubrication France S.A.S.
Z.I. des Auréats, 10 à 16 Allée Ducretet
26014 Valence Cedex
France
+33-4-75448426
Fax: +33-4-75449336
KLF.contact@fr.klueber.com

1.4 Emergency telephone number

Emergency telephone number : +33 1 45 42 59 59 ORFILA
+33 1 72 11 00 03 NCEC
+49 8142 3051 517

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 20.08.2025 | Print Date: |
| 5.0 | 05.06.2026 | Date of first issue: 09.07.2016 | 05.06.2026 |

Eye irritation, Category 2

H319: Causes serious eye irritation.

Skin sensitisation, Category 1

H317: May cause an allergic skin reaction.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing mist.
P280 Wear protective gloves/ eye protection/ face protection.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

Version 5.0 Revision Date: 05.06.2026 Date of last issue: 20.08.2025 Print Date: 05.06.2026
Date of first issue: 09.07.2016

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Propellant
Synthetic hydrocarbon oil

Components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification | specific concentration limit M-Factor Notes Acute toxicity estimate | Concentration (% w/w) |
|--|---|---|---|--------------------------|
| propane | 74-98-6 200-827-9 601-003-00-5 01-2119486944-21-XXXX | Flam. Gas 1; H220 Press. Gas Compr. Gas; H280 | Note U (Table 3) | $\geq 10 - < 20$ |
| isobutane | 75-28-5 200-857-2 601-004-00-0 01-2119485395-27-XXXX | Flam. Gas 1A; H220 Press. Gas Compr. Gas; H280 | Note U (Table 3), Note C | $\geq 10 - < 20$ |
| Sulfonic acids, petroleum, calcium salts | 61789-86-4 263-093-9 01-2119488992-18-XXXX | Skin Sens. 1B; H317 | ≥ 10 % Skin Sens.1B, | $\geq 0,1 - < 1$ |
| Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate | 947-946-9 01-2120772600-59-XXXX | Skin Irrit. 2; H315 Skin Sens. 1B; H317 Aquatic Chronic 4; H413 | | $\geq 0,25 - < 1$ |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

Version 5.0 Revision Date: 05.06.2026 Date of last issue: 20.08.2025 Print Date: 05.06.2026
Date of first issue: 09.07.2016

| Substances with a workplace exposure limit : | | | | |
|--|--|---|----------------------------------|--------------|
| butane | 106-97-8 203-448-7 601-004-00-0 01-2119474691-32-XXXX | Flam. Gas 1; H220 Press. Gas Compr. Gas; H280 | Note U (Table 3), Note C, Note S | >= 30 - < 50 |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash off immediately with soap and plenty of water.
Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
Seek medical advice.
- If swallowed : Move the victim to fresh air.
Keep respiratory tract clear.
Do NOT induce vomiting.
Rinse mouth with water.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Inhalation may provoke the following symptoms:
Unconsciousness
Dizziness
Drowsiness
Headache
Nausea
Tiredness
- Risks : May cause an allergic skin reaction.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 20.08.2025 | Print Date: |
| 5.0 | 05.06.2026 | Date of first issue: 09.07.2016 | 05.06.2026 |

Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Fire Hazard
Do not let product enter drains.
Contains gas under pressure; may explode if heated.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion products : Carbon oxides
Nitrogen oxides (NOx)

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not breathe vapours or spray mist.
Refer to protective measures listed in sections 7 and 8.
Only qualified personnel equipped with suitable protective equipment may intervene.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 20.08.2025 | Print Date: |
| 5.0 | 05.06.2026 | Date of first issue: 09.07.2016 | 05.06.2026 |

6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water courses.
Prevent further leakage or spillage if safe to do so.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.
Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not use in areas without adequate ventilation.
Do not breathe vapours or spray mist.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin and eyes.
For personal protection see section 8.
Keep away from fire, sparks and heated surfaces.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
Do not get in eyes or mouth or on skin.
Do not get on skin or clothing.
Do not ingest.
Do not use sparking tools.
These safety instructions also apply to empty packaging which may still contain product residues.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|----------------|------------------------------|---|---------------------------|
| Version 5.0 | Revision Date: 05.06.2026 | Date of last issue: 20.08.2025 Date of first issue: 09.07.2016 | Print Date: 05.06.2026 |
|----------------|------------------------------|---|---------------------------|

or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular national regulations.

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|--|----------|-------------------------------|------------------------------------|------------------------|
| butane | 106-97-8 | VME | 800 ppm 1.900 mg/m ³ | FR VLE (2005-02-01) |
| Further information: Permissible limit values (circular) | | | | |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|---|---------|-----------------|----------------------------|-------------------------|
| Benzene, mono-C10-13-alkyl derivs., distn. residues | Workers | Inhalation | Long-term systemic effects | 2,2 mg/m ³ |
| | Workers | Skin contact | Long-term systemic effects | 3,15 mg/kg bw/day |
| Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate | Workers | Inhalation | Long-term systemic effects | 4,93 mg/m ³ |
| | Workers | Dermal | Long-term systemic effects | 1,4 mg/kg bw/day |
| Sulfonic acids, petroleum, calcium salts | Workers | Inhalation | Long-term systemic effects | 11,75 mg/m ³ |
| | Workers | Skin contact | Long-term systemic effects | 3,33 mg/m ³ |
| | Workers | Skin contact | Long-term local effects | 1,03 mg/cm ² |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

| Substance name | Environmental Compartment | Value |
|---|------------------------------------|------------|
| Benzene, mono-C10-13-alkyl derivs., distn. residues | Fresh water | 0,001 mg/l |
| | Intermittent use/release | 0,001 mg/l |
| | Marine water | 0 mg/l |
| | Microbiological Activity in Sewage | 2 mg/l |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

Version 5.0 Revision Date: 05.06.2026 Date of last issue: 20.08.2025 Print Date: 05.06.2026
Date of first issue: 09.07.2016

| | Treatment Systems | |
|--|--|-----------------|
| | Fresh water sediment | 16,5 mg/kg |
| | Marine sediment | 1,65 mg/kg |
| | Soil | 3,7 mg/kg |
| Sulfonic acids, petroleum, calcium salts | Fresh water | 1 mg/l |
| | Marine water | 1 mg/l |
| | Intermittent use/release | 10 mg/l |
| | Microbiological Activity in Sewage Treatment Systems | 1000 mg/l |
| | Fresh water sediment | 226000000 mg/kg |
| | Marine sediment | 226000000 mg/kg |
| | Soil | 271000000 mg/kg |

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye/face protection : Safety glasses with side-shields

Hand protection

Material : butyl-rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : For prolonged or repeated contact use protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.
The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Short term only

Filter type : Filter type A-P

Protective measures : The type of protective equipment must be selected according

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 20.08.2025 | Print Date: |
| 5.0 | 05.06.2026 | Date of first issue: 09.07.2016 | 05.06.2026 |

to the concentration and amount of the dangerous substance
at the specific workplace.

Environmental exposure controls

Air : No special environmental precautions required.
Soil : The product should not be allowed to enter drains, water
courses or the soil.
Water : The product should not be allowed to enter drains, water
courses or the soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : aerosol

Colour : brown

Odour : characteristic

Odour Threshold : No data available

Melting point/ range : No data available

Boiling point/boiling range : -42 °C (1.013 hPa)

Flammability : Flammability (solid, gas):
Extremely flammable aerosol.

Upper explosion limit / Upper
flammability limit : 10,9 %(V)

Lower explosion limit / Lower
flammability limit : 1,5 %(V)

Flash point : -60 °C
Method: DIN 51755, closed cup

Auto-ignition temperature : > 350 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 20.08.2025 | Print Date: |
| 5.0 | 05.06.2026 | Date of first issue: 09.07.2016 | 05.06.2026 |

Decomposition temperature : No data available

pH : Not applicable
substance/mixture is non-soluble (in water)

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : < 20,5 mm²/s (40 °C)

Solubility(ies)
Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-
octanol/water : No data available

Vapour pressure : 3.000 hPa (20 °C)

Relative density : 0,67 (20 °C)
Reference substance: Water
The value is calculated

Density : 0,67 g/cm³
(20 °C)

Bulk density : No data available

Relative vapour density : No data available

9.2 Other information

Explosives : Not explosive

Oxidizing properties : No data available

Self-ignition : not auto-flammable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 20.08.2025 | Print Date: |
| 5.0 | 05.06.2026 | Date of first issue: 09.07.2016 | 05.06.2026 |

Metal corrosion rate : Not corrosive to metals

Evaporation rate : No data available

Sublimation point : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.
Strong sunlight for prolonged periods.
Risk of receptacle bursting.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity : Remarks: This information is not available.

Acute inhalation toxicity : Symptoms: Inhalation may provoke the following symptoms:,
Respiratory disorder

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 20.08.2025 | Print Date: |
| 5.0 | 05.06.2026 | Date of first issue: 09.07.2016 | 05.06.2026 |

Acute dermal toxicity : Symptoms: Redness, Local irritation

Components:

isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: gas

Sulfonic acids, petroleum, calcium salts:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 1,9 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute
inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Acute dermal toxicity : Symptoms: Redness, Local irritation

butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: gas

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Product:

Remarks : This information is not available.

Components:

Sulfonic acids, petroleum, calcium salts:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 20.08.2025 | Print Date: |
| 5.0 | 05.06.2026 | Date of first issue: 09.07.2016 | 05.06.2026 |

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Species : reconstructed human epidermis (RhE)
Exposure time : 15 min
Assessment : Irritating to skin.
Method : OECD Test Guideline 439
Result : Irritating to skin.
GLP : yes

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Result : Eye irritation

Components:

Sulfonic acids, petroleum, calcium salts:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Species : Bovine cornea
Exposure time : 10 min
Assessment : No eye irritation
Method : OECD Test Guideline 437
Result : No eye irritation
GLP : yes

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Product:

Assessment : May cause sensitisation by skin contact.
Result : May cause sensitisation by skin contact.

Components:

Sulfonic acids, petroleum, calcium salts:

Test Type : Buehler Test
Species : Guinea pig

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 20.08.2025 | Print Date: |
| 5.0 | 05.06.2026 | Date of first issue: 09.07.2016 | 05.06.2026 |

Assessment : The product is a skin sensitiser, sub-category 1B.
Result : The product is a skin sensitiser, sub-category 1B.

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Test Type : Local lymph node assay (LLNA)
Species : Mouse
Assessment : The product is a skin sensitiser, sub-category 1B.
Method : OECD Test Guideline 429
Result : The product is a skin sensitiser, sub-category 1B.
GLP : yes

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

Sulfonic acids, petroleum, calcium salts:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: Micronucleus test
Species: Mouse
Application Route: Oral
Method: OECD Test Guideline 474
Result: negative

Germ cell mutagenicity-Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
GLP: yes

Test Type: in vitro micronucleus test
Test system: Human lymphocytes
Metabolic activation: with and without metabolic activation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 20.08.2025 | Print Date: |
| 5.0 | 05.06.2026 | Date of first issue: 09.07.2016 | 05.06.2026 |

Method: OECD Test Guideline 487
Result: negative
GLP: yes

Test Type: In vitro mammalian cell gene mutation test
Test system: mouse lymphoma cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 490
Result: negative
GLP: yes

Germ cell mutagenicity-
Assessment : Weight of evidence does not support classification as a germ
cell mutagen.

Carcinogenicity

Based on available data, the classification criteria are not met.

Product:

Remarks : No data available

Components:

Sulfonic acids, petroleum, calcium salts:

Carcinogenicity -
Assessment : Not classifiable as a human carcinogen.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Product:

Effects on fertility : Remarks: No data available

Effects on foetal
development : Remarks: No data available

Components:

Sulfonic acids, petroleum, calcium salts:

Effects on fertility : Test Type: reproductive and developmental toxicity study
Species: Rat
Application Route: Oral
General Toxicity - Parent: NOAEL: > 500
General Toxicity F1: NOAEL: > 500
Method: OECD Test Guideline 415

Reproductive toxicity -
Assessment : - Fertility -
No toxicity to reproduction
- Teratogenicity -
No toxicity to reproduction

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 20.08.2025 | Print Date: |
| 5.0 | 05.06.2026 | Date of first issue: 09.07.2016 | 05.06.2026 |

||

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Reproductive toxicity - Assessment : - Fertility -
Animal testing did not show any effects on fertility.

STOT - single exposure

Based on available data, the classification criteria are not met.

Product:

Remarks : No data available

Components:

||

Sulfonic acids, petroleum, calcium salts:

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Product:

Remarks : No data available

Components:

||

Sulfonic acids, petroleum, calcium salts:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Components:

||

Sulfonic acids, petroleum, calcium salts:

Species : Rat
NOAEL : 500 mg/kg
Application Route : Oral
Method : OECD Test Guideline 407

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Species : Rat, male and female

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 20.08.2025 | Print Date: |
| 5.0 | 05.06.2026 | Date of first issue: 09.07.2016 | 05.06.2026 |

NOAEL : 100 mg/kg
Application Route : oral (gavage)
Exposure time : 28 d
Number of exposures : daily
Method : OECD Test Guideline 422
GLP : yes
Remarks : Not classified due to data which are conclusive although insufficient for classification.

Aspiration toxicity

Based on available data, the classification criteria are not met.

Product:

This information is not available.

11.2 Information on other hazards

Endocrine disrupting properties

Based on available data, the classification criteria are not met.

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Information given is based on data on the components and the toxicology of similar products.

Components:

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Remarks : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 20.08.2025 | Print Date: |
| 5.0 | 05.06.2026 | Date of first issue: 09.07.2016 | 05.06.2026 |

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

Sulfonic acids, petroleum, calcium salts:

Toxicity to fish : LC50 (Cyprinodon variegatus (sheepshead minnow)): > 10.000 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: yes
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1.000 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
Remarks: No toxicity at the limit of solubility

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1.500 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Remarks: No toxicity at the limit of solubility

Toxicity to microorganisms : EC50 (activated sludge): > 10.000 mg/l
Exposure time: 3 h
Test Type: static test
Method: OECD Test Guideline 209
GLP: yes

Ecotoxicology Assessment

Chronic aquatic toxicity : This product has no known ecotoxicological effects., No toxicity at the limit of solubility

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203
GLP: yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 20.08.2025 | Print Date: |
| 5.0 | 05.06.2026 | Date of first issue: 09.07.2016 | 05.06.2026 |

Remarks: May cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

Toxicity to microorganisms : EC50 (activated sludge): > 1.000 mg/l
Exposure time: 3 h
Test Type: Respiration inhibition
Analytical monitoring: no
Method: OECD Test Guideline 209
GLP: yes

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

Components:

Sulfonic acids, petroleum, calcium salts:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: Not rapidly biodegradable
Biodegradation: 8 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
GLP: yes

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Biodegradability : Result: Not rapidly biodegradable
Biodegradation: 11 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 20.08.2025 | Print Date: |
| 5.0 | 05.06.2026 | Date of first issue: 09.07.2016 | 05.06.2026 |

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

propane:

Partition coefficient: n-octanol/water : log Pow: 2,36

isobutane:

Partition coefficient: n-octanol/water : log Pow: 2,88
Method: OECD Test Guideline 107

Sulfonic acids, petroleum, calcium salts:

Bioaccumulation : Remarks: Due to the distribution coefficient n-octanol/water, accumulation in organisms is possible.

Partition coefficient: n-octanol/water : log Pow: 10,88 (20 °C)
Method: OECD Test Guideline 117
GLP: yes

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Partition coefficient: n-octanol/water : log Pow: > 4

butane:

Partition coefficient: n-octanol/water : log Pow: 2,89
Method: OECD Test Guideline 107

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 20.08.2025 | Print Date: |
| 5.0 | 05.06.2026 | Date of first issue: 09.07.2016 | 05.06.2026 |

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : No information on ecology is available.

Components:

Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate:

Additional ecological information : May cause long lasting harmful effects to aquatic life.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Offer empty spray cans to an established disposal company.
Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied
16 05 04*, gases in pressure containers (including halons)
containing hazardous substances

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 20.08.2025 | Print Date: |
| 5.0 | 05.06.2026 | Date of first issue: 09.07.2016 | 05.06.2026 |

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS
IATA : Aerosols, flammable

14.3 Transport hazard class(es)

| | Class | Subsidiary risks |
|------|-------|------------------|
| ADN | : 2 | 2.1 |
| ADR | : 2 | 2.1 |
| RID | : 2 | 2.1 |
| IMDG | : 2.1 | |
| IATA | : 2.1 | |

14.4 Packing group

ADN
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1

ADR
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

RID
Packing group : Not assigned by regulation
Classification Code : 5F
Hazard Identification Number : 23
Labels : 2.1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 20.08.2025 | Print Date: |
| 5.0 | 05.06.2026 | Date of first issue: 09.07.2016 | 05.06.2026 |

IMDG

Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 40
This substance/mixture shall not be used in aerosol dispensers intended

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 20.08.2025 | Print Date: |
| 5.0 | 05.06.2026 | Date of first issue: 09.07.2016 | 05.06.2026 |

for supply to the general public for entertainment and decorative purposes.

Number on list 75
If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). (EU SVHC) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Regulation (EU) No 2024/590 on substances that deplete the ozone layer (EC 2024/590) : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) (EU POP) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals (EU PIC) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) (EU. REACH-Annex XIV) : Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors : Not applicable

P2

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P3a FLAMMABLE AEROSOLS

18 Liquefied flammable gases (including LPG) and natural gas

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 20.08.2025 | Print Date: |
| 5.0 | 05.06.2026 | Date of first issue: 09.07.2016 | 05.06.2026 |

Installations classified for the protection of the environment (Environment Code R511-9) : 4320, 4718, 4310

Occupational Illnesses (R-461-3, France) : 36, 34

Reinforced medical supervision (R4624-23) : The product has no CMR properties category 1, 1A or 1B

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 55 %

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

H220 : Extremely flammable gas.
H280 : Contains gas under pressure; may explode if heated.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H413 : May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard
Flam. Gas : Flammable gases
Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
Note S : This substance may not require a label according to Article 17 (see Section 1.3 of Annex I) (Table 3).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 20.08.2025 | Print Date: |
| 5.0 | 05.06.2026 | Date of first issue: 09.07.2016 | 05.06.2026 |

- Note U (Table 3) : When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).
- Press. Gas : Gases under pressure
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
FR VLE : France. Occupational Exposure Limits
FR VLE / VME : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Aerosol 1 H222, H229

Classification procedure:

Based on product data or assessment

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878 - FR



OKS 451

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 20.08.2025 | Print Date: |
| 5.0 | 05.06.2026 | Date of first issue: 09.07.2016 | 05.06.2026 |

| | | |
|--------------|------|-------------------------------------|
| Eye Irrit. 2 | H319 | Based on product data or assessment |
| Skin Sens. 1 | H317 | Based on product data or assessment |

|| Relevant changes compared to the last edition are highlighted at the left margin. This version replaces all previous editions.

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.