OKS 2610

Version	Revision Date:	Date of last issue: 17.04.2026	Print Date:
4.0	23.09.2026	Date of first issue: 23.06.2016	23.09.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 2610

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Detergent
Cleaning agent / Cleaner

Recommended restrictions on use : Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH
Ganghoferstr. 47
82216 Maisach
Germany
Tel.: +49 8142 3051-500
info@oks-germany.com

E-mail address of person responsible for the SDS : mcm@oks-germany.com

National contact : Klüber Lubrication France S.A.S.
Z.I. des Auréats, 10 à 16 Allée Ducretet
26014 Valence Cedex
France
+33-4-75448426
Fax: +33-4-75449336
KLF.contact@fr.klueber.com

1.4 Emergency telephone number

Emergency telephone number : +33 1 45 42 59 59 ORFILA

+33 1 72 11 00 03 NCEC

+49 8142 3051 517

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 — H225: Highly flammable liquid and vapour.

Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements :

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273	Avoid release to the environment.

Response:

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331	Do NOT induce vomiting.
P370 + P378	In case of fire: Use alcohol-resistant foam, carbon dioxide or water mist to extinguish.
P391	Collect spillage.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Hazardous components which must be listed on the label:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

propan-2-ol

acetone

cyclohexane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Solvent mixture

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	920-750-0 01-2119473851-33-xxxx	Flam. Liq. 2; H225 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	Note P	>= 30 - < 50

propan-2-ol	67-63-0 200-661-7 603-117-00-0 02-2119457558-25-XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)		>= 30 - < 50
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49-XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066		>= 20 - < 30
cyclohexane	110-82-7 203-806-2 601-017-00-1	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	M-Factor: 1/1	>= 1 - < 2,5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Call a physician or poison control centre immediately.
Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact : Take off all contaminated clothing immediately.
Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
Wash skin thoroughly with soap and water or use recognized skin cleanser.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
Seek medical advice.

If swallowed : Move the victim to fresh air.
If accidentally swallowed obtain immediate medical attention.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
Do NOT induce vomiting.
Rinse mouth with water.
Never give anything by mouth to an unconscious person.
Aspiration hazard if swallowed - can enter lungs and cause damage.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:
Unconsciousness
Dizziness
Drowsiness
Headache
Nausea
Tiredness
Skin contact may provoke the following symptoms:
Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Risks : Central nervous system depression
Can be absorbed through skin.
Risk of product entering the lungs on vomiting after ingestion.
Health injuries may be delayed.

May be fatal if swallowed and enters airways.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting	:	Do not let product enter drains. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Hazardous combustion products	:	Carbon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposition products may be a hazard to health.
Further information	:	Standard procedure for chemical fires. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Evacuate personnel to safe areas. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Do not breathe vapours or spray mist. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions	:	Do not allow contact with soil, surface or ground water. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.

OKS 2610

Version	Revision Date:	Date of last issue: 17.04.2026	Print Date:
4.0	23.09.2026	Date of first issue: 23.06.2016	23.09.2026

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Use only in an area containing explosion proof equipment.
Do not use in areas without adequate ventilation.
Do not breathe vapours or spray mist.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin and eyes.
For personal protection see section 8.
Keep away from fire, sparks and heated surfaces.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
Ensure all equipment is electrically grounded before beginning transfer operations.
Do not get in eyes or mouth or on skin.
Do not get on skin or clothing.
Do not ingest.
Do not use sparking tools.
Do not enter areas where used or stored until adequately ventilated.
Do not repack.
Do not re-use empty containers.
These safety instructions also apply to empty packaging which may still contain product residues.
Keep container closed when not in use.

Advice on protection against fire and explosion : Keep away from heat and sources of ignition.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep container closed when not in use. Keep in a cool place away from oxidizing agents. Keep in a dry, cool and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with the particular national regulations. Keep in properly labelled containers.

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

OKS 2610

Version	Revision Date:	Date of last issue: 17.04.2026	Print Date:
4.0	23.09.2026	Date of first issue: 23.06.2016	23.09.2026

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
propan-2-ol	67-63-0	VLCT (VLE)	400 ppm 980 mg/m3	FR VLE (2005-02-01)
	Further information: Permissible limit values (circular)			
acetone	67-64-1	TWA	500 ppm 1.210 mg/m3	2000/39/EC (1991-07-05)
	Further information: Indicative			
		VME	500 ppm 1.210 mg/m3	FR VLE (2007-12-01)
	Further information: Regulatory binding exposure limits			
		VLCT (VLE)	1.000 ppm 2.420 mg/m3	FR VLE (2007-12-01)
	Further information: Regulatory binding exposure limits			
cyclohexane	110-82-7	TWA	200 ppm 700 mg/m3	2006/15/EC (2006-02-09)
	Further information: Indicative			
		VME	200 ppm 700 mg/m3	FR VLE (2012-07-01)
	Further information: Regulatory binding exposure limits			
		VLCT (VLE)	375 ppm 1.300 mg/m3	FR VLE (2012-07-01)
	Further information: Permissible limit values (circular)			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	Workers	Inhalation	Acute systemic effects	1286,4 mg/m3
	Workers	Inhalation	Long-term local effects	837,5 mg/m3
propan-2-ol	Workers	Inhalation	Long-term systemic effects	500 mg/m3
	Workers	Skin contact	Long-term systemic effects	888 mg/kg
acetone	Workers	Inhalation	Long-term systemic effects	1210 mg/m3
	Workers	Skin contact	Long-term systemic effects	186 mg/kg
cyclohexane	Workers	Inhalation	Long-term systemic effects	700 mg/m3
	Workers	Skin contact	Long-term systemic effects	2016 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
acetone	Fresh water	10,6 mg/l
	Marine water	1,06 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	30,4 mg/kg
	Marine sediment	3,04 mg/kg
	Soil	29,5 mg/kg
cyclohexane	Fresh water	0,0447 mg/l
	Marine water	0,00447 mg/l
	Sewage treatment plant	3,24 mg/l
	Fresh water sediment	3,6 mg/kg
	Marine sediment	0,36 mg/kg
	Soil	0,694 mg/kg

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye/face protection : Safety glasses with side-shields

Hand protection
- Material : Nitrile rubber
- Break through time : > 10 min
- Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.
The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Recommended Filter type:

Organic gas and low boiling vapour type (AX)

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance

at the specific workplace.

Environmental exposure controls

Air	:	Should not be released into the environment. Exhaust air must be cleaned using approved equipment before returning it to the work place.
Soil	:	Do not allow contact with soil, surface or ground water. The product should not be allowed to enter drains, water courses or the soil.
Water	:	Do not allow contact with soil, surface or ground water. The product should not be allowed to enter drains, water courses or the soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	colourless
Odour	:	characteristic
Odour Threshold	:	No data available
Melting point/ range	:	No data available
Boiling point/boiling range	:	67,2 °C (1.013 hPa)
Flammability	:	Flammability (solid, gas): Not applicable
Upper explosion limit / Upper flammability limit	:	13 %(V)
Lower explosion limit / Lower flammability limit	:	1,0 %(V)
Flash point	:	< 0 °C Method: ISO 2719

Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
pH	:	Not applicable substance/mixture is non-polar/aprotic
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	< 20,5 mm2/s (40 °C)
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	9,4 hPa (20 °C)
Relative density	:	0,7568 (20 °C) Reference substance: Water The value is calculated
Density	:	0,76 g/cm3 (20 °C)
Bulk density	:	No data available
Relative vapour density	:	No data available

9.2 Other information

Explosives	:	Not explosive
Oxidizing properties	:	No data available

Self-ignition	:	not auto-flammable
Metal corrosion rate	:	Not corrosive to metals
Evaporation rate	:	No data available
Sublimation point	:	No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.
Strong sunlight for prolonged periods.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.

Symptoms: Inhalation may provoke the following symptoms:, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central nervous system depression

Acute dermal toxicity : Remarks: Prolonged or repeated skin contact with liquid may cause defatting resulting in drying, redness and possible blistering.

Symptoms: Skin disorders

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:
Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

propan-2-ol:
Acute oral toxicity : LD50 Oral (Rat): 5.840 mg/kg

acetone:
Acute oral toxicity : LD50 Oral (Rat): 5.800 mg/kg

cyclohexane:
Acute oral toxicity : LD50 Oral: > 5.000 mg/kg
Method: OECD Test Guideline 401

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Product:
Remarks : This information is not available.

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:
Result : Repeated exposure may cause skin dryness or cracking.

acetone:
Result : Repeated exposure may cause skin dryness or cracking.

cyclohexane:
Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : This information is not available.

Components:

propan-2-ol:

Species : Rabbit
Result : Eye irritation

acetone:

Species : Rabbit
Result : Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Product:

Remarks : This information is not available.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity

Based on available data, the classification criteria are not met.

Product:

Remarks : No data available

Reproductive toxicity

Based on available data, the classification criteria are not met.

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure

May cause drowsiness or dizziness.

Product:

Remarks : No data available

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Assessment : May cause drowsiness or dizziness.

propan-2-ol:

Assessment : May cause drowsiness or dizziness.

acetone:

Exposure routes : Inhalation
Assessment : May cause drowsiness or dizziness.

cyclohexane:

Exposure routes : Inhalation
Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Product:

Remarks : No data available

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

This information is not available.

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

May be fatal if swallowed and enters airways.

cyclohexane:
May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Based on available data, the classification criteria are not met.

Product:

Assessment	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks	:	Information given is based on data on the components and the toxicology of similar products.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish	:	Remarks: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available
Toxicity to algae/aquatic plants	:	Remarks: No data available
Toxicity to microorganisms	:	Remarks: No data available

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Ecotoxicology Assessment

Chronic aquatic toxicity	:	Toxic to aquatic life with long lasting effects.

cyclohexane:

Toxicity to daphnia and other	:	EC50 (Daphnia magna (Water flea)): 0,9 mg/l

aquatic invertebrates		Exposure time: 48 h
M-Factor (Acute aquatic toxicity)	:	1
M-Factor (Chronic aquatic toxicity)	:	1

Ecotoxicology Assessment

Acute aquatic toxicity	:	Very toxic to aquatic life.
Chronic aquatic toxicity	:	Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Product:

Biodegradability	:	Remarks: No data available
Physico-chemical removability	:	Remarks: No data available

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Biodegradability	:	Result: Readily biodegradable.

propan-2-ol:

Biodegradability	:	Result: Readily biodegradable.

acetone:

Biodegradability	:	Result: Readily biodegradable.

cyclohexane:

Biodegradability	:	Result: Readily biodegradable. Biodegradation: 77 % Exposure time: 28 d

12.3 Bioaccumulative potential

Product:

Bioaccumulation	:	Remarks: No data available

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Bioaccumulation	:	Remarks: Not applicable

Partition coefficient: n-octanol/water : Remarks: No data available

propan-2-ol:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 0,05

acetone:

Bioaccumulation : Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 0,2

cyclohexane:

Bioaccumulation : Bioconcentration factor (BCF): 167

Partition coefficient: n-octanol/water : log Pow: 3,44 (20 °C)

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Dispose of waste product or used containers according to local regulations.

The following Waste Codes are only suggestions:

Waste Code : 14 06 03*, other solvents and solvent mixtures

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1993

ADR : UN 1993

RID : UN 1993

IMDG : UN 1993

IATA : UN 1993

14.2 UN proper shipping name

ADN : FLAMMABLE LIQUID, N.O.S.
(Isopropanol, Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics)

ADR : FLAMMABLE LIQUID, N.O.S.
(Isopropanol, Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics)

RID	:	FLAMMABLE LIQUID, N.O.S. (Isopropanol, Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics)
IMDG	:	FLAMMABLE LIQUID, N.O.S. (Isopropanol, Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics)
IATA	:	Flammable liquid, n.o.s. (Isopropanol, Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics)

14.3 Transport hazard class(es)

		Class	Subsidiary risks
ADN	:	3	
ADR	:	3	
RID	:	3	
IMDG	:	3	
IATA	:	3	

14.4 Packing group

ADN

Packing group	:	II
Classification Code	:	F1
Hazard Identification Number	:	33
Labels	:	3

ADR

Packing group	:	II
Classification Code	:	F1
Hazard Identification Number	:	33
Labels	:	3
Tunnel restriction code	:	(D/E)

RID

Packing group	:	II
Classification Code	:	F1
Hazard Identification Number	:	33
Labels	:	3

IMDG

Packing group	:	II
Labels	:	3
EmS Code	:	F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft)	:	364
Packing instruction (LQ)	:	Y341

Packing group : II
Labels : Flammable Liquids

IATA (Passenger)
Packing instruction (passenger aircraft) : 353
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

14.5 Environmental hazards

ADN
Environmentally hazardous : yes

ADR
Environmentally hazardous : yes

RID
Environmentally hazardous : yes

IMDG
Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries must be considered::
Number on list 3

Number on list 40
This substance/mixture shall not be used in aerosol dispensers intended for supply to the general public for entertainment and decorative purposes.

Number on list 57: cyclohexane

Number on list 75

			If you intend to use this product as tattoo ink, please contact your vendor.
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). (EU SVHC)	:		This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).
Regulation (EU) No 2024/590 on substances that deplete the ozone layer (EC 2024/590)	:		Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast) (EU POP)	:		Not applicable
Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals (EU PIC)	:		Not applicable
REACH - List of substances subject to authorisation (Annex XIV) (EU. REACH-Annex XIV)	:		Not applicable
Regulation (EU) 2019/1148 on the marketing and use of explosives precursors This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.			acetone (ANNEX II);
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.		E2	ENVIRONMENTAL HAZARDS
		P5c	FLAMMABLE LIQUIDS
		34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating

oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Installations classified for the protection of the environment (Environment Code R511-9)	:	4331, 4511, 4734
Occupational Illnesses (R-461-3, France)	:	84, 36
Reinforced medical supervision (R4624-23)	:	The product has no CMR properties category 1, 1A or 1B
Volatile organic compounds	:	Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 100 %
Regulation (EC) No. 648/2004, as amended	:	Ingredients >= 30%: Aliphatic hydrocarbons

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

H225	:	Highly flammable liquid and vapour.
H304	:	May be fatal if swallowed and enters airways.
H315	:	Causes skin irritation.
H319	:	Causes serious eye irritation.

H336	:	May cause drowsiness or dizziness.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.
EUH066	:	Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Note P	:	The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply.
Skin Irrit.	:	Skin irritation
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC	:	Europe. Indicative occupational exposure limit values
FR VLE	:	France. Occupational Exposure Limits
2000/39/EC / TWA	:	Limit Value - eight hours
2006/15/EC / TWA	:	Limit Value - eight hours
FR VLE / VME	:	Time Weighted Average
FR VLE / VLCT (VLE)	:	Short Term Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; BGW - Biological Limit Values; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); LSPN - List of Hazardous Notified Substances (Chile); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration;

NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:		**Classification procedure:**
Flam. Liq. 2	H225	Based on product data or assessment
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 2	H411	Calculation method

|| Relevant changes compared to the last edition are highlighted at the left margin. This version replaces all previous editions.

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.

OKS 2610

Version	Revision Date:	Date of last issue: 17.04.2026	Print Date:
4.0	23.09.2026	Date of first issue: 23.06.2016	23.09.2026

Ingredients (Regulation (EC) No. 648/2004, as amended)

Naphtha (petroleum), hydrotreated light
propan-2-ol
acetone
cyclohexane

https://ec.europa.eu/growth/tools-databases/cosing/index.cfm?fuseaction=search.simple